

Control & Signalling Units ϕ 22.5mm Metal

Assemblies for Illuminated, Non-Illuminated type
Push Buttons & Selector Switches



PB-BZ101



PB-BE101



PB-BW06



PB-BWL7

Body assemblies with fixing collar & contact blocks (screw clamp terminal connections)

Description	Contact	Type	Reference
For Push Buttons, Selector and Key Switches	NO	Standard	PB-BZ101
	NC	Standard	PB-BZ102
	NO+NO	Standard	PB-BZ103
	NC+NC	Standard	PB-BZ104
	NO+NC	Standard	PB-BZ105

Additional / Replacement Contact Blocks

Description	Contact	Type	Reference
For making up Body Assemblies with 3, 4, 5 or Maximum of 6 Contact Blocks or Replacing 1 st OR 2 nd Contact	NO	Standard	PB-BE101
	NC	Standard	PB-BE102

Body assemblies for illuminated Push Buttons & Selectors with or w/o Contacts

Description	Supply Voltage	Contact	Colour	Reference
Direct BA 9s Filament Bulb* Supplied	12V / 24V / 48V / 110V / 130V (AC)(DC) ϕ	NO + NC		PB-BW065■
		W/O Contact Blocks		PB-BW06■
Through Resistor BA 9s, 130V Filament Bulb Supplied	220V (AC)(DC)	NO + NC		PB-BW075
		W/O Contact Blocks		PB-BW07
Through Resistor & Diode BA 9s 130V Bulb Supplied	240V (AC)	NO + NC		PB-BWD075
		W/O Contact Blocks		PB-BWD07
Direct BA 9s Neon Bulb Supplied	220V / 380V / 415V (AC)(DC)	NO + NC	● Green	PB-BWN0635■
			■ Natural	PB-BWN0655■
		W/O Contact Blocks	● Green	PB-BWN063■
			■ Natural	PB-BWN065■
With Integral Circuit & Cluster LED	12V, 24V, 48V (AC)(DC) 110VAC, 110VDC 240V (AC) 220V (DC)	NO + NC	○ White	PB-BWL715■
			● Green	PB-BWL735■
			● Red	PB-BWL745■
			● Amber	PB-BWL755■
			● Blue	PB-BWL765■
			Clear	PB-BWL775■
			● Yellow	PB-BWL785■
		W/O Contact Blocks	○ White	PB-BWL71■
			● Green	PB-BWL73■
			● Red	PB-BWL74■
			● Amber	PB-BWL75■
			● Blue	PB-BWL76■
			Clear	PB-BWL77■
			● Yellow	PB-BWL78■

- ○ Body assemblies (suitable for bulb 2.6W max.) upto 230V max. available without bulb
- * Bulb rating 12V to 130V, 2.6W (max.);
- ■ Please mention voltage while ordering
- For accessories refer page C-9 & C-10