


STANDARD SUPPORT GRIPS



Standard Support Grips are designed to sustain and shore up the weight of cable in vertical or sloping applications. Constructed of non-magnetic tin-bronze wire, they assist in absorbing strain and flexure; and resist pullout, flexure and vibration. Standard Support Grips are available in a wide selection of eye styles and cable ranges. They will support cable rods and tubing with loads up to 600 lbs. Not recommended for runs over 100 feet.



G



Double Eye



Single Eye



Offset Eye



Universal Bail

Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Closed Mesh – Double Eye – Single Weave					
.50- .62	2201-001	R050-DE	770	4	11
.63- .74	2201-002	R062-DE	1150	4	11
.75- .99	2201-003	R075-DE	1320	4	14
1.00-1.24	2201-004	R100-DE	1920	5	15
1.25-1.49	2201-005	R125-DE	1920	5	16
1.50-1.74	2201-006	R150-DE	1920	5	18
1.75-1.99	2201-007	R175-DE	3150	6	20
2.00-2.49	2201-008	R200-DE	3360	6	22
2.50-2.99	2201-009	R250-DE	3360	6	24
3.00-3.49	2201-010	R300-DE	5280	8	26
3.50-3.99	2201-011	R350-DE	5280	8	28
Closed Mesh – Single Eye – Single Weave					
.50- .62	2201-013	R050-SE	770	7	11
.63- .74	2201-014	R062-SE	1150	8	11
.75- .99	2201-015	R075-SE	1320	8	14
1.00-1.24	2201-016	R100-SE	1920	9	15
1.25-1.49	2201-017	R125-SE	1920	10	16
1.50-1.74	2201-018	R150-SE	1920	12	18
1.75-1.99	2201-019	R175-SE	3150	14	20
2.00-2.49	2201-020	R200-SE	3360	16	22
2.50-2.99	2201-021	R250-SE	3360	18	24
3.00-3.49	2201-022	R300-SE	5280	21	26
3.50-3.99	2201-023	R350-SE	5280	24	28
Closed Mesh – Offset Eye – Single Weave					
.50- .62	2201-025	R050-OFS	770	4	11
.63- .74	2201-026	R062-OFS	960	4	11
.75- .99	2201-027	R075-OFS	960	4	14
1.00-1.24	2201-028	R100-OFS	1680	5	15
1.25-1.49	2201-029	R125-OFS	1680	5	16
1.50-1.74	2201-030	R150-OFS	1680	5	18
1.75-1.99	2201-031	R175-OFS	2640	6	20
2.00-2.49	2201-032	R200-OFS	3760	6	22
2.50-2.99	2201-033	R250-OFS	3760	6	24
3.00-3.49	2201-034	R300-OFS	5040	9	26
3.50-3.99	2201-035	R350-OFS	5040	9	28
Closed Mesh – Universal Bail – Single Weave					
.50- .62	2201-037	R050UB-18"	770	18	11
.63- .74	2201-038	R062UB-18"	1150	18	11
.75- .99	2201-039	R075UB-18"	1320	18	14
1.00-1.24	2201-040	R100UB-18"	1920	18	15
1.25-1.49	2201-041	R125UB-18"	1920	18	16
1.50-1.74	2201-042	R150UB-18"	1920	18	18
1.75-1.99	2201-043	R175UB-18"	3150	18	20
2.00-2.49	2201-044	R200UB-18"	3360	18	22
2.50-2.99	2201-045	R250UB-18"	3360	18	24
3.00-3.49	2201-046	R300UB-18"	5280	18	26
3.50-3.99	2201-047	R350UB-18"	5280	18	28

All mesh is available as double weave or stainless steel. Consult factory for availability.