

TUFF-SEAL™

MULTIPLE HOLE BUSHINGS



The Tuff Seal family of Multiple Hole Bushings are ideal for use when multiple conductors need to be terminated into one fitting. Standard bushings are made from Neoprene but optional materials include silicone for high-temperature applications and Viton® for enhanced corrosion resistance.

Remke Multiple Hole Bushings can be made to fit into cord connectors made from aluminum, nickel-plated aluminum, steel and stainless steel, nylon or Valox™.

MULTIPLE HOLE BUSHINGS

Bushing Only Part Number	Form Size	Number of Holes	Diameter Each Hole (IN)	Conduit Size
SRB-100-UF1	2	1	Oval - .425 x .225	1/2" or 3/4"
SRB-100-UF2	2	1	Oval - .610 x .225	1/2" or 3/4"
SRB-103-2	2	2	.187	1/2" or 3/4"
SRB-104-2	2	2	.250	1/2" or 3/4"
SRB-104-3	2	3	.250	1/2" or 3/4"
SRB-10532-2	2	2	.156	1/2" or 3/4"
SRB-10532-3	2	3	.156	1/2" or 3/4"
SRB-10532-4	2	4	.156	1/2" or 3/4"
SRB-10564-2	2	2	.078	1/2" or 3/4"
SRB-10732-2	2	2	.218	1/2" or 3/4"
SRB-10732-3	2	3	.218	1/2" or 3/4"
SRB-10932-2	2	2	.281	1/2" or 3/4"
SRB-201764-2	3	2	.265	1/2" or 3/4"
SRB-201764-3	3	3	.265	1/2" or 3/4"
SRB-201964-2	3	2	.296	1/2" or 3/4"
SRB-201964-3	3	3	.296	1/2" or 3/4"
SRB-201964-4	3	4	.296	1/2" or 3/4"
SRB-202164-2	3	2	.328	1/2" or 3/4"
SRB-203-4	3	4	.187	1/2" or 3/4"
SRB-204-2	3	2	.250	1/2" or 3/4"
SRB-204-3	3	3	.250	1/2" or 3/4"
SRB-204-4	3	4	.250	1/2" or 3/4"
SRB-205-2	3	2	.312	1/2" or 3/4"
SRB-20516-3	3	3	.312	1/2" or 3/4"
SRB-20732-2	3	2	.218	1/2" or 3/4"
SRB-20732-4	3	4	.218	1/2" or 3/4"
SRB-20932-3	3	3	.281	1/2" or 3/4"
SRB-300-3SP1	4	3	.300	3/4" or 1"
SRB-300-3SP2	4	3	.225	3/4" or 1"
SRB-300-4SP1	4	4	.220	3/4" or 1"
SRB-300-4SP2	4	4	.340	3/4" or 1"
SRB-301964-2	4	2	.296	3/4" or 1"
SRB-301964-4	4	4	.296	3/4" or 1"
SRB-301964-5	4	5	.296	3/4" or 1"
SRB-303-3	4	3	.187	3/4" or 1"
SRB-303-4	4	4	.187	3/4" or 1"
SRB-304-5	4	5	.250	3/4" or 1"
SRB-305-3	4	3	.312	3/4" or 1"
SRB-306-2	4	2	.375	3/4" or 1"
SRB-500-2	5	2	.500/.375	1 1/4" or 1 1/2"
SRB-506-3	5	3	.375	1 1/4" or 1 1/2"
SRB-508-2	5	2	.500	1 1/4" or 1 1/2"
SRB-509-3	5	3	.562	1 1/4" or 1 1/2"
SRB-510-2	5	2	.625	1 1/4" or 1 1/2"

ACCESSORIES

These seals and locknuts can be used with all external conduit threads, except Pg and I.S.O. metric threads.

Seal O-Rings	Size	Steel Locknuts	Stainless Steel Locknuts
SOR-38	3/8"	LN-38	LNSS-38
SOR-1-VNT	1/2"	LN-50	LNSS-50
SOR-2	3/4"	LN-75	LNSS-75
SOR-3	1"	LN-100	LNSS-100
SOR-4	1 1/4"	LN-125	LNSS-125
SOR-51	1 1/2"	LN-150	LNSS-150
SOR-16	2"	LN-200	LNSS-200
	2 1/2"	LN-250	LNSS-250
	3"	LN-300	LNSS-300