TOTO_®

SW583/SW584

Washlet[®] S350e

FEATURES

- Gentle Aerated, Warm Water, Dual Action Spray • with oscillating and pulsating feature
- Adjustable water temperature and volume •
- Instant water heating system for continuous warm water and energy saving
- Warm air drying with five variable ٠ temperature settings
- Automatic air deodorizer •
- New slim design seat, at just under 4 inches •
- Convenient slim wireless remote, with illuminated • touch pad.
- 2 user setting ٠
- Auto open/close lid •
- Docking Station Easy to Install and Clean Heated Seat with Temperature Control •
- eWater+ on wands and bowl •
- Water pre-mist of bowl before each use •
- Night light

MODELS

- SW584 Elongated front
- SW583 Round front

COLORS/FINISHES

Standard #01 Cotton #12 Sedona Beige



ewater+

For more information on ewater+ please go to www.totousa.com/Washlet/NewS300eS350e.aspx

PRODUCT SPECIFICATION

Seat shall be model # SW584 or # SW583_ Seat shall have gentle aerated, warm water, dual action spray with cycling movement and massage feature. Seat shall have adjustable water temperature and volume. Seat shall have warm air drying with five variable temperature settings. Seat shall have automatic air deodorizer. Seat shall include wireless remote control. Seat shall be solid plastic with closed front seat and cover. Seat shall include power cord, and water supply hoses. Seat shall have auto open/ close lid with eWater+. Seat shall have night light.

CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 #68
- Certifications: IAPMO(cUPC), State of • Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



SPECIFICATIONS

•	Power Rating: Power Cord:	120V AC, 60Hz, 835W Maximum length: 3.94 ft/120 cm, 3 prong	•	Drying Feature:	Air temperature: High: about 140°F/60°C Low: about 95°F/35°C	
		grounded plug	•	Dryer Air Capacity:		ft ³ /min
•	Water Feature:	Adjustable Water Flow Rate: Front washing - 10.2 - 14.1 oz/min	•	Seat Warming Feature	Ð:	Surface Temperature: Minimum: 82°F/28°C Maximum: 97°F/36°C
		Wide Front - from 11.5 -	•	Safety Device:	Therr	mal fuse
		14.1 oz/min	٠	Water Supply Pressure: Minimum: 7.25 psi		Minimum: 7.25 psi
		Rear washing 9.0 -				Maximum: 108.75 psi
		14.1 oz/min	•	Ambient Temperature	Ambient Temperature: Range: 32°F/1°C to 104°F/40°C	
		Soft Rear - from 10.2 -				
		14.1 oz/min	•	Warranty:	One	Year Limited Warranty
•	Washing Spray Temp:	Minimum: 86°F/30°C	•	Shipping weight:	13.5lbs.	
		Maximum: 104°F/40°C	•	Shipping dimensions:	s: 23" x 19-1/4" x 5-1/2"	

Thermal fuse.

• Safety Device:

- INSTALLATION NOTES
- Washlet S350e may not fit certain toilet bowl designs.
- If possible, with your order, please include your model number (from the underside of the tank lid).
- Warning: Rated power consumption 835W

It is highly recommended to use a surge protector to prevent damage in the event of a power surge.



These dimensions and specifications are subject to change without notice