Infrared Thermometer w/ Circular Laser Targeting



Functions

- Temperature range: -76˚ to 1022˚F (-60˚ to 550˚C)
- 12:1 Distance-to-spot ratio

Features

- Circular laser targeting
- Protective rubber grip
- Max value capture
- Selectable emissivity: 0.95 or 0.70
- Auto power off
- 1-Year limited warranty



Includes

- Holster/pouch
- Batteries (AAA) 2
- Manual (17300)



Applications

- Check register temperatures
- Hard to reach registers and appliances
- Faulty breakers and panels
- Motors, fans or other moving parts
- Boilers, hanging heaters and radiators
- Troubleshoot hydronic systems

Specifications

Temperature Range	-76˚ to 1022˚F (-60˚ to 550˚C)
Operating Temperature	32˚ to 122˚F (0˚ to 50˚C)
Accuracy (Tobj=15-35˚C, Tamb=25˚C)	± 2.7˚F (1.5˚C)
Accuracy (Tamb=23 ± 3˚C)	Tobj=0~550˚C: ±2% of reading or 2˚C(4˚F) whichever is greater Tobj=-60~0˚C: ±(2˚C+0.05/degree C)
Emissivity	0.95 or 0.70 (0.95 is default)
Resolution	0.1°C/0.1°F at -76.0 to 999.9(°C/°F), otherwise 1°C/1°F
Response Time	1 sec.
Distance-to-Spot Ratio	12:1
Dimension	6.43" x 4.62" x 1.92" (163.4 × 117.5 × 48.8 mm)
Weight	7.87 oz (223g) including batteries

Downloads

Manual Data Sheet

H26-252

0 53533 50741 6

Made in CHINA

Copyright ©2026 Kane USA Inc. All Rights Reserved. INF165C DATA SHEET L394