## **PEX-a Pipe Support**

Submittal Information Revision D: Dec. 23, 2014

### **Project Information**

#### Job Name:

Manufacturer's Representative:	Approved By:				
Contractor:	Submitted By:				
Engineer:	Date Submitted:				
Location:	Part No. Ordered:				
Job Name:					

#### **Technical Data**

Material:

۱

Commercial-grade (Type B) galvanized steel

#### **Product Information and Application Use**

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX<sup>®</sup> or Wirsbo hePEX<sup>™</sup> PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



1	Description	Part Number	Height	Width	Length	Gauge	Weight
•			-		-	-	
	1/2" PEX-a Pipe Support, 9-ft. length	F7040500	0.42"	0.75"	108"	23	1.10 lbs.
	¾" PEX-a Pipe Support, 9-ft. length	F7040750	0.56"	1.00"	108"	23	1.50 lbs.
	1" PEX-a Pipe Support, 9-ft. length	F7041000	0.64"	1.13"	108"	23	1.91 lbs.
	1¼" PEX-a Pipe Support, 9-ft. length	F7041250	0.79"	1.38"	108"	23	2.10 lbs.
	11/2" PEX-a Pipe Support, 9-ft. length	F7041500	0.93"	1.63"	108"	23	2.50 lbs.
	2" PEX-a Pipe Support, 9-ft. length	F7042000	1.14"	2.00"	108"	23	3.60 lbs.
	21/2" PEX-a Pipe Support, 9-ft. length	F7042500	1.25"	2.52"	108"	23	4.60 lbs.
	3" PEX-a Pipe Support, 9-ft. length	F7043000	1.90"	3.12"	108"	23	6.20 lbs.
	31/2" PEX-a Pipe Support, 9-ft. length	F7043500	2.16"	3.60"	108"	23	6.40 lbs.

#### Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

#### Accessories

Q7410510: PEX-a Pipe Support Strapping ( $\frac{1}{2}$ ",  $\frac{3}{4}$ ", 1" PEX) Q7411220: PEX-a Pipe Support Strapping ( $\frac{1}{4}$ ",  $\frac{1}{2}$ ", 2" PEX) Q7412540: PEX-a Pipe Support Strapping ( $\frac{2}{2}$ ", 3",  $\frac{3}{2}$ ", 4" PEX)

#### Standards

ASTM E84 (up to 3")

#### Codes

IMC, UMC, NBCC

#### Listings

QAI P321 (up to 3")

#### **Related Applications**

PEX-a Plumbing Systems Radiant Heating and Cooling Systems AquaSAFE™ Fire Safety Systems

#### **Contact Information**

Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: 800.321.4739 Fax: 952.891.2008 www.uponorpro.com Uponor Ltd. 2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Phone: 888.994.7726 Fax: 800.638.9517 www.uponorpro.com

# uponor