# **ProPEX<sup>®</sup> Lead-free (LF) Brass Elbow**

Submittal Information Revision A: Jan. 28, 2010

### Project Information

| Project mion                   | nation                     |                   |  |  |
|--------------------------------|----------------------------|-------------------|--|--|
| Job Name:                      |                            |                   |  |  |
| Location:                      |                            | Part No. Ordered: |  |  |
| Engineer:                      |                            | Date Submitted:   |  |  |
| Contractor:                    |                            | Submitted By:     |  |  |
| Manufacturer's Representative: |                            | Approved By:      |  |  |
| Technical Dat                  | а                          |                   |  |  |
| Material:                      | C69300 Brass               |                   |  |  |
| Product Infor                  | mation and Application Use |                   |  |  |
|                                |                            |                   |  |  |

The ProPEX<sup>®</sup> Lead-free Brass Elbow is available for use in hot and cold domestic potable water systems, hydronic heating systems, all Uponor plumbing systems and in the AquaSAFE<sup>TM</sup> Residential Fire Safety System.<sup>1</sup>

Each end features the ProPEX Fitting for connections to Wirsbo hePEX<sup>TM</sup> tubing or Uponor AquaPEX<sup>®</sup> tubing. This product is safe for direct burial in soil.



| $\checkmark$ | Description                                 | Part Number | Α     | В     | С     | Weight    |
|--------------|---------------------------------------------|-------------|-------|-------|-------|-----------|
|              | ProPEX LF Brass Elbow, 3/4" PEX x 3/4" PEX* | LF4710750   | 2.04" | 1.75" | 0.75" | 0.20 lbs. |
|              | ProPEX LF Brass Elbow, 1" PEX x 1" PEX*     | LF4711000   | 2.61" | 2.28" | 1.00" | 0.30 lbs. |

## Installation

ProPEX Tool and ProPEX Rings (sold separately) are required for connecting the PEX tubing. Refer to the AquaPEX Professional Plumbing Installation Guide, the Radiant Floor Heating Installation Handbook or the AquaSAFE Residential Fire Sprinkler Installation Guide for additional information.

#### Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

#### Codes

IPC; UPC; NSPC; NPC of Canada

#### Listings

ANSI/NSF 14- and 61-certified; U.P. Code; ICC ESR 1099; HUD MR 1269; \*UL 1821; \*ULC/ORD C199P; U.P. Code, Annex G

| Related Applications                   | Contact Information                |                                      |  |  |
|----------------------------------------|------------------------------------|--------------------------------------|--|--|
| PEX-a Plumbing Systems                 | Uponor, Inc.                       | Uponor Ltd.                          |  |  |
| Uponor Residential Fire Safety Systems | 5925 148 <sup>th</sup> Street West | 2000 Argentia Rd., Plaza 1, Ste. 200 |  |  |
| Radiant Heating and Cooling Systems    | Apple Valley, MN 55124 USA         | Mississauga, ON L5N 1W1 CANADA       |  |  |
| Snow and Ice Melting Systems           | Phone: (800) 321-4739              | Phone: (888) 994-7726                |  |  |
| Permafrost Protection Systems          | Fax: (952) 891-2008                | Fax: (800) 638-9517                  |  |  |
| Turf Conditioning Systems              | www.uponor-usa.com                 | www.uponor.ca                        |  |  |

<sup>1</sup>ProPEX<sup>®</sup> is a registered trademark of Uponor, Inc. ProPEX<sup>™</sup> is a trademark of Uponor Ltd.

# uponor