

ProPEX® Brass Elbow with MIP

Submittal Information
Revision A: April 20, 2011

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Material: C36000 Brass

Maximum Temperature
(no pressure): 320°F (160°C)

Maximum Working
Temperature/Pressure: 210°F at 150 psi (99°C at 10.3 bar)



Product Information and Application Use

Uponor's ProPEX® Brass Elbow with MIP makes 90-degree connections for 1/2" Uponor PEX tubing to 3/8" male NPT thread.

✓	Description	Part Number	Length	Width	Height	Weight
	ProPEX Brass Elbow, 1/2" PEX x 3/8" MIP	Q4743850	1.68"	0.82"	1.78"	0.25 lbs.

Installation

ProPEX Tool required. Use the appropriate ProPEX Ring (sold separately) for connecting to PEX tubing. Refer to the Uponor AquaPEX® Professional Plumbing Installation Guide or Radiant Floor Heating Installation Handbook for additional information.

Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

IAPMO 3558; ANSI/NSF 14- and 61-certified; HUD MR 1269; ICC ESR 1099

Related Applications

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Road, Plaza 1, Suite 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca