



WARDFLEX® Valve

Ward Manufacturing, LLC.

117 Gulick Street
 Blossburg, PA 16912
 Tel. (800)248-1027
 www.wardmfg.com

Description:

The 3/8" thru 1-1/4" WARDFLEX® tubing is terminated using the patented, STEPSAVER double seal fitting. The 1-1/2" and 2" tubing utilize the WARDFLEX® traditional gasketed fitting design. Only fittings designed and listed for use with the WARDFLEX® and WARDFLEX® MAX CSST Piping Systems shall be used when connecting to the flexible piping.

Features:

- Male NPT thread
- Gas shut off valve
- One corrugation crush seal
- Reusable
- Patented STEPSAVER fittings
 - Primary metal to metal seal
 - Secondary gasket seal

Components:

- Valve Body
- Retainer Ring
- Nut
- Gasket

Listings:

- CSA: File# 112940_0_000
- IAPMO: File# 3353
- ICC: Report# ESR-1879

Technical Data:

General

| | |
|------------------------------|--------|
| Certified Operating Pressure | 25 psi |
|------------------------------|--------|

Material

| | |
|----------------------------|------------------------|
| Body, Retainer Ring, & Nut | Brass |
| Valve Handle | Steel (Painted Yellow) |
| Gasket | Composite Fiber |



Dimensions

| Price Sheet Item # | CSST Size | NPT Size | Nut Hex | Maximum Tightening Torque (ft-lbs) | Approximate Weight (lbs) |
|--------------------|-----------|----------|---------|------------------------------------|--------------------------|
| 370 | 3/8" | 1/2" | 1-1/16" | 50 | 0.64 |
| 371 | 1/2" | 1/2" | 1-3/16" | 50 | 0.55 |
| 372 | 3/4" | 3/4" | 1-1/2" | 120 | 1.02 |
| 373 | 1" | 3/4" | 1-3/4" | 160 | 1.13 |