

# Innovations

and Autumn-Winter Campaign 2019/2020






Kraftform Micro Big Pack


Wera Micro screwdriver set for fine mechanical screw connections. By supporting the hand on the rotating cap, and by the fast rotating zone below the rotating cap, lightning fast turning is possible. Time-consuming hand switching is eliminated. Storage and transport in a robust roll-bag, so the correct tool is always at hand. With "Take it easy" tool finder: colour coding by profile and size stamping.




Kraftform Micro




"Take it easy" Tool Finder




Screwdrivers with "Take it easy" tool finder: colour coding according to profile and size stamp.




TORX® HF profile




In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!



The refined screwdriver for electronics technicians



The Kraftform Micro, with its three zones and their specific arrangement, satisfies these requirements perfectly. The free-turning cap that provides support for the hand works with these advantages, enabling quick and easy precision work.




**Application:** Slotted screws, Phillips-head, Phillips-Recess, TORX® Internal Transducers (TX 5, TX 6, TX 7, TX 8, TX 10 with holding function), Internal TORX PLUS® IPR, internal and external hex and Microstix® screws, "Take it easy" tool finder: colour coding according to profile and size stamp. 1 chip lifter to remove stuck components on circuit boards after soldering

**Design:** 25 pieces; in roll bag; suitable for Wera 2go

05134000001	
+	2050 PH Micro 1 x PH 000x40 <sup>1) 2)</sup> ; 1 x PH 00x40 <sup>1) 2)</sup> ; 1 x PH 0x40 <sup>3)</sup>
⊕	2067 TORX® 1 x TX 5x40; 1 x TX 6x40
⊗	2067 TORX® HF 1 x TX 5x40; 1 x TX 6x40; 1 x TX 7x60; 1 x TX 8x60; 1 x TX 10x60
⊙	2067 TORX PLUS® IPR Micro 1 x 1 IPRx40
○	2054 Micro 1 x 0,9x40; 1 x 1,3x40; 1 x 1,5x60; 1 x 2x60
●	2035 Micro 1 x 0,23x1,5x40; 1 x 0,30x1,8x60; 1 x 0,35x2,5x40; 1 x 0,40x2,0x60; 1 x 0,40x2,5x80; 1 x 0,50x3,0x80
⦿	2069 Micro 1 x 4,0x60; 1 x 5,5x60
⦿	2072 1 x mx40
⦿	1429 1 x 1,0x3,5x50

NEW Kraftform Micro Big Pack 1 Screwdriver set for electronic applications



<sup>1)</sup> Optimised for Asian PH screws  
<sup>2)</sup> On the output side, the blade is turned to a nominal length of 10 mm.  
<sup>3)</sup> Size 0 modified according to JCS 0 (Japanese Camera Industrial Standard)





# Kraftform Kompakt VDE with Knipex pliers

Individually tested tools as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.  
14 VDE interchangeable blades (each 154 mm long) with reduced blade diameter (articles KK 60 i 0,4x2,5 and KK 67 i TX 10 conventional diameter), so that sunken screws and spring elements can be accessed and actuated. Two 817 VDE blade-holding handles for Wera VDE interchangeable blades; Kraftform handle for ergonomic work; in robust belt pouch. One pair of Knipex VDE 13 96 200 electrical installation pliers; the pliers replace up to 6 individual tools for electrical installation: cutting, stripping, gripping, bending, deburring and crimping - all in one tool. With pawl for gentle gripping. Chrome-plated for better rust protection, with insulated multi-component grip sheaths.

NEW

Kraftform Kompakt VDE 17 extra slim 1



## Kraftform Kompakt VDE



Individually tested



Each Kraftform Kompakt VDE set has been tested individually at 10,000 volts, in accordance with IEC 60900. This ten-times-higher testing load guarantees safe working at their maximum permitted load of 1,000 volts.

## Handle/interchangeable blade system



The system "one handle – many interchangeable blades" makes Kraftform Kompakt VDE compact screwdriving sets for in-house as well as mobile electrical applications out of the sets. The belt pouch is practical for tidy storage and transportation. Also available with electrical cabinet keys conforming to the industrial standards.

17-piece set  
2 Kraftform handles 817 VDE for Wera VDE interchangeable blades only

14 VDE interchangeable blades (each 154 mm long) with reduced blade diameter (articles KK 60 i 0,4x2,5 and KK 67 i TX 10 conventional diameter) with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated

1 pair of Knipex electrical installation pliers VDE 13 96 200; for cutting, stripping, gripping, bending, deburring and crimping. With pawl for gentle gripping. Chrome-plated for better rust protection, with insulated multi-component grip sheaths.

05136027001		
●	817 VDE	2 x 9x102
⊕	KK 62 iS	1 x PH 1x154; 1 x PH 2x154
⊕	KK 65 iS PZ	1 x PZ 1x154; 1 x PZ 2x154
⊕	KK 65 iS PZ/S	1 x # 1x154; 1 x # 2x154
⊕	KK 67 i TORX®	1 x TX 10x154
⊕	KK 67 iS TORX®	1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
⊖	KK 60 i	1 x 0,4x2,5x154
⊖	KK 60 iS	1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154
KNIPLEX 13 96 200		





# Wera Bicycle Sets

NEW

## Bicycle Set 2



13-piece set, in a pouch; 1 816 R Kraftform bit-holding screwdriver handle with Rapidaptor quick-release chuck, suitable for 1/4" hex bits as per DIN ISO 1173-C 6.3 and E 6.3 and Wera series 1 and 4; 12 bits, 89 mm long, tough, for universal use

05004171001		
●	816 R	1 x 1/4"x119
⊕	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89
⊗	867/4 Z TORX®	1 x TX 10x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
○	840/4 Z Hex-Plus	1 x 2,0x89; 1 x 2,5x89; 1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89

NEW

## Bicycle Set 3



39-piece set

28 bits, 1 813 bit-holding screwdriver handle suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1, 1 Rapidaptor bit holder, 1 adaptor 870/1 (1/4" hexagon to 1/4" square), 7 sockets (1/4"); 1 Wera Bit Ratchet Zyklop Mini 1, drop-forged full steel design suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 and Wera connection series 1 and 4; the use of 1/4" sockets is also possible with the application of the Wera adaptor 870/1. 1 Bit-Check, empty, for a reduced selection, e.g. for taking along on bicycle tours. One robust textile pouch for tidy storage.

05004172001		
	8001 A	1 x 1/4"x87,0
●	813	1 x 1/4"x78
⊗	889/4/1 K	1 x 1/4"x50
⊗	870/1	1 x 1/4"x25 <sup>1)</sup>
●	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 13,0x23,0; 1 x 15,0x23,0
⊕	851/1 TZ PH	1 x PH 1x25; 2 x PH 2x25; 1 x PH 3x25
⊕	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 2 x TX 20x25; 2 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
⊖	800/1 TZ	1 x 0,5x4,0x25; 1 x 0,6x4,5x25; 1 x 1,0x5,5x25
○	840/1 Z Hex-Plus	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25
○	842/1 Z	1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

<sup>1)</sup> With friction ball; for manual nut spinner sockets

## Zyklop Mini



The Zyklop Mini 1 can withstand at least 65 Nm. That is far more power than can normally be transferred to such a small tool.

## Bicycle Set 3



Bicycle Set 3 is a practical assortment for the independent execution of assembly work and repairs on road bikes, mountain bikes and e-bikes. Especially useful: a Bit-Check (empty) is also included, which can be equipped individually with tools on the way: less weight on bike rides.



## Rapidaptor holder




Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool.





NEW

#### Bicycle Set 4



9-piece set in pouch

**Application:** Hexagonal socket screws and TORX® screws

**Design:** BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

**Tip:** 950 SPKL HF: Hex-Plus, ball-end hexagon on long arm, with holding function for hexagonal socket screws; 950 SPKL: Hex-Plus, ball-end hexagon on long arm, without holding function; 967 SXL HF: With holding function for TORX® screws to Acument Intellectual Properties specification.

05004173001		
○	950 SPKL Multicolour	1 x 2x101; 1 x 2,5x112
○	950 SPKL HF Multicolour	1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195
⊕	967 SXL HF TORX® Multicolour	1 x TX 10x112; 1 x TX 25x154

NEW

#### Kraftform Kompakt 20 Tool Finder 2 with pouch



**Application:** Suitable for 1/4" DIN ISO 1173-C 6.3 and E 6.3 hexagon socket insert bits and Wera Series 1 and 4

**Design:** Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology; "Take it easy" tool finder: Output colour coding and large stamp to enable the desired bit to be easily located; bits with high corrosion protection due to nickel chemical coating.

**Handle:** Kraftform with non-roll feature, multi-component, integrated magazine

05051017001		
⊕	889/4 R	1 x 1/4"x100
⊕	851/1 BTZ PH	1 x PH 1x25; 1 x PH 2x25
⊕	855/1 BTZ PZ	1 x PZ 1x25; 1 x PZ 2x25
⊕	867/1 TORX® BTZ	1 x TX 20x25; 1 x TX 25x25
⊕	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89
⊕	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89
⊕	867/4 Z TORX®	1 x TX 20x89; 1 x TX 25x89

NEW

#### 950/9 Hex-Plus Multicolour 2 L-key set, metric, BlackLaser



9-piece set in a two-component clip

**Application:** Hexagon socket screws

**Design:** BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

**Tip:** Hex-Plus, ball-end hexagon on long arm

05133164001		
○	950 SPKS Multicolour	1 x 1,5x50; 1 x 2,0x56; 1 x 2,5x63; 1 x 3,0x71; 1 x 4,0x80; 1 x 5,0x90; 1 x 6,0x100; 1 x 8,0x112; 1 x 10,0x125



#### Bicycle Set 4



Compact screwdriving tool set for bicycle applications, also for mobile use.



#### L-keys with holding function for hexagon socket screws




The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

#### Kraftform Kompakt Tool Finder 2



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.



#### Ball-end



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.



## Wera's new socket expertise

We also wanted to transfer the special features of the proven Wera sockets to important special applications.

We listened to our users and found solutions for the following applications:

### Impaktor

Impact sockets for extreme requirements



### Deep sockets

for low-lying screwdriving and protruding threaded rods



### VDE bit sockets

for work under tension





# Impaktor sockets for extreme requirements


Impaktor socket for use with electric or pneumatic impact wrenches with 12.5mm = 1/2" drive. The Impaktor technology ensures above-average service life even under extreme working conditions.

With "Take it easy" tool finder with colour coding by size – for easy and fast location of the required tool. With hexagonal profile and grooved socket. For hexagon headed bolts, screws and nuts.



NEW

## Belt C Impaktor 1 Socket set, 1/2" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Impaktor sockets with 1/2" drive, with hexagonal profile and grooved socket. For use with electric or pneumatic powered impact wrenches with 12.5mm = 1/2" drive. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily selected.

05004580001		
8790 C Impaktor	1 x 13,0x38,0; 1 x 14,0x38,0; 1 x 15,0x38,0; 1 x 16,0x38,0; 1 x 17,0x38,0; 1 x 18,0x38,0; 1 x 19,0x38,0; 1 x 20,0x38,0; 1 x 21,0x38,0	
Belt C Impaktor 0/9	1 x 71,0x210,0	

NEW

## 8790 C Impaktor socket with 1/2" drive



**Application:** Hexagon headed bolts, screws and nuts

**Design:** For use with electric or pneumatic impact wrenches with 12.5mm = 1/2" drive, with retaining pin hole, chrome-molybdenum, matte black finish. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily located.

		mm	mm	mm	mm
05004570001		13,0	38,0	21,0	24,0
05004571001		14,0	38,0	22,0	24,0
05004572001		15,0	38,0	24,0	24,0
05004573001		16,0	38,0	24,0	24,0
05004574001		17,0	38,0	26,0	26,0
05004575001		18,0	38,0	28,0	28,0
05004576001		19,0	38,0	28,0	28,0
05004577001		20,0	38,0	26,0	30,0
05004578001		21,0	38,0	26,0	30,0

## Impaktor sockets



For electric or pneumatic impact wrenches



The Impaktor technology ensures above-average service life of the Impaktor socket wrench plug-ins even under extreme conditions.

## Profile-friendly power transmission



The hexagon profile allows the transmission of high forces and puts less strain on the edges of bolts or screw heads than a double hexagon profile. Fine-toothed ratchets also make the use of a double hexagon profile superfluous, even in confined spaces, thanks to their small back-pivoting angle.

## Cross-bore and ring socket



Due to the groove and the ring socket, the tool can be secured with a locking pin or O-ring on the power tool.



## Practical nonwoven strips



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.



# Deep sockets for for low-lying screwdriving and protruding threaded rods

Long 1/4", 3/8", 1/2" manual and mechanical socket wrench inserts (ISO 2725 part 3) from Wera for use in manual and machine operation (non-impact) even with low-lying screwdriving and protruding threaded rods. With "Take it easy" tool finder with colour coding by size – for easy and fast location of the required tool. Easy to grasp even with oily hands, thanks to knurling on the lower end. With hexagonal profile and ball-catching groove. For external hexagonal bolts and sockets.



NEW

Belt A Deep 1 socket set, 1/4" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Smooth turning Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 sockets with 1/4" drive. Long design for low-profile screwdriving and protruding threaded rods, with hexagonal profile. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily selected.

05004525001		
●	8790 HMA Deep	1 x 5,0x50,0; 1 x 5,5x50,0; 1 x 6,0x50,0; 1 x 7,0x50,0; 1 x 8,0x50,0; 1 x 10,0x50,0; 1 x 11,0x50,0; 1 x 12,0x50,0; 1 x 13,0x50,0
	Belt A 0/9	1 x 39,0x238,0

NEW

8790 HMA Deep 1/4" socket



**Application:** Hexagon headed bolts, screws and nuts

**Design:** Manual and (non-impact) machine applications, ball intercept ring, long design for low-lying screwdriving and protruding threaded rods; with hexagonal profile; knurls at base for precision handling in manual operations, chrome vanadium, matte chrome-plated finish. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily located.

		mm	mm	mm	mm
05004500001		4,0	50,0	6,7	11,8
05004501001		5,0	50,0	8,0	11,8
05004502001		5,5	50,0	8,6	11,8
05004503001		6,0	50,0	9,2	11,8
05004504001		7,0	50,0	10,8	11,8
05004505001		8,0	50,0	11,8	11,0
05004506001		9,0	50,0	12,8	12,0
05004507001		10,0	50,0	14,7	12,8
05004508001		11,0	50,0	15,8	14,0
05004509001		12,0	50,0	16,8	15,0
05004510001		13,0	50,0	17,8	16,0
05004511001		14,0	50,0	19,8	17,0
05004512001		15,0	50,0	20,8	18,0

## Deep sockets

### Long design



Due to the long design of the socket, screwdriving can also be achieved in small spaces. Fittings with protruding threaded rods are also possible.

### Knurling



Knurling on lower end for more grip when used manually

### Profile-friendly power transmission



The hexagon profile allows the transmission of high forces and puts less strain on the edges of bolts or screw heads than a double hexagon profile. Fine-toothed ratchets also make the use of a double hexagon profile superfluous, even in confined spaces, thanks to their small back-pivoting angle.

### Practical nonwoven strips




The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.





NEW

Belt B Deep 1 socket set, 3/8" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Smooth turning Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 sockets with 3/8" drive. Long design for low-profile screwdriving and protruding threaded rods, with hexagonal profile. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily selected.

05004545001		
●	8790 HMB Deep	1 x 8,0x64,0; 1 x 10,0x64,0; 1 x 12,0x64,0; 1 x 13,0x64,0; 1 x 15,0x64,0; 1 x 16,0x64,0; 1 x 17,0x64,0; 1 x 18,0x64,0; 1 x 19,0x64,0
	Belt B 0/9	1 x 45,0x310,0

NEW

8790 HMB Deep 3/8" socket



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, long design for low-lying screwdriving and protruding threaded rods; with hexagonal profile; knurls at base for precision handling in manual operations, chrome vanadium, matte chrome-plated finish. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily located.

		mm	mm	mm	mm
05004530001		8,0	64,0	12,2	17,0
05004531001		9,0	64,0	13,5	17,0
05004532001		10,0	64,0	14,5	17,0
05004533001		11,0	64,0	15,7	17,0
05004534001		12,0	64,0	16,5	18,0
05004535001		13,0	64,0	19,0	17,0
05004536001		14,0	64,0	20,0	18,0
05004537001		15,0	64,0	22,0	20,0
05004538001		16,0	64,0	22,0	20,0
05004539001		17,0	64,0	24,0	22,0
05004540001		18,0	64,0	26,0	23,0
05004541001		19,0	64,0	26,0	23,0
05004542001		20,0	64,0	28,0	25,0
05004543001		21,0	64,0	28,0	25,0
05004544001		22,0	64,0	30,0	26,0

NEW

Belt C Deep 1 socket set, 1/2" drive



6-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Smooth turning Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

6 sockets with 1/2" drive. Long design for low-profile screwdriving and protruding threaded rods, with hexagonal profile. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily selected.

05004565001		
●	8790 HMC Deep	1 x 10,0x83,0; 1 x 13,0x83,0; 1 x 15,0x83,0; 1 x 16,0x83,0; 1 x 17,0x83,0; 1 x 19,0x83,0
	Belt C 0/6	1 x 45,0x275,0

NEW

8790 HMC Deep socket with 1/2" drive



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, long design for low-lying screwdriving and protruding threaded rods; with hexagonal profile; knurls at base for precision handling in manual operations, chrome vanadium, matte chrome-plated finish. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily located.

		mm	mm	mm	mm
05004550001		10,0	83,0	15,5	21,8
05004551001		11,0	83,0	16,7	22,0
05004552001		12,0	83,0	18,0	22,0
05004553001		13,0	83,0	19,2	22,0
05004554001		14,0	83,0	20,5	22,0
05004555001		15,0	83,0	22,0	20,7
05004556001		16,0	83,0	22,0	20,7
05004557001		17,0	83,0	24,0	22,2
05004558001		18,0	83,0	26,0	23,2
05004559001		19,0	83,0	26,0	23,2
05004560001		20,0	83,0	28,0	25,2
05004561001		21,0	83,0	28,0	25,2
05004562001		22,0	83,0	30,0	27,2
05004563001		24,0	83,0	32,0	28,2





# VDE bit sockets for work under tension

VDE 3/8" with increased safety due to yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. Individually tested tool as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V.



## Individually tested



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



## Practical nonwoven strips



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.



## Secure hold and easy removal



The all new smooth turning mechanism guarantees both secure and rattle-free storage, yet allows easy removal of the tool.

## NEW Belt B VDE 1 Zyklop bit-socket set TORX®/hexagonal socket with holding function, 3/8" drive



10-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the bit-sockets.

10 Zyklop bit sockets, with 3/8" drive. Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. With holding function for TORX® screws made according to Acument Intellectual Properties specifications and hexagonal socket screws. Short bit-sockets with the benefits of the Wera bit technology.

05004930001		
⊗	8767 B VDE HF	1 x TX 20x55,0; 1 x TX 25x55,0; 1 x TX 27x55,0; 1 x TX 30x55,0; 1 x TX 40x55,0; 1 x TX 45x59,0
○	8740 B VDE HF	1 x 4,0x55,0; 1 x 5,0x55,0; 1 x 6,0x55,0; 1 x 8,0x59,0
	Belt B VDE 0/10	1 x 71,0x209,0



VDE bit sockets



Bit-sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!



Bit-sockets with holding function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Increased security



The Zyklop VDE sockets and extensions offer increased safety thanks to their 2-component isolation with yellow insulation core under red insulation outer layer.

NEW

8740 B VDE HF Zyklop bit-socket, insulated, with holding function, 3/8" drive



**Application:** Hexagon socket screws

**Design:** Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. Short bit-sockets with the benefits of the Wera bit technology; with holding function for hexagonal socket screws.

	mm	mm	mm	mm
05004900001	4,0	55,0	23,0	9,0
05004901001	5,0	55,0	23,0	9,0
05004902001	6,0	55,0	23,0	9,0
05004903001	8,0	59,0	23,0	13,0

NEW

8767 B VDE HF TORX® Zyklop bit-socket, insulated, with holding function, 3/8" drive



**Application:** TORX® socket screws

**Design:** Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer, holding function for TORX® screws made according to Acument Intellectual Properties specifications. Short bit-sockets with the benefits of the Wera bit technology; with holding function for hexagonal socket screws.

		mm	mm	mm
05004920001	TX 20	55,0	23,0	9,0
05004921001	TX 25	55,0	23,0	9,0
05004922001	TX 27	55,0	23,0	9,0
05004923001	TX 30	55,0	23,0	9,0
05004924001	TX 40	55,0	23,0	9,0
05004925001	TX 45	59,0	23,0	13,0

NEW

8760 B VDE XZN Zyklop bit-socket, insulated, 3/8" drive, for multi-point socket screws



**Application:** Multi-point socket screws

**Design:** Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer. Short bit-sockets with the benefits of the Wera bit technology; with holding function for hexagonal socket screws.

		mm	mm	mm
05004940001	M 8	59,0	23,0	13,0
05004941001	M 10	59,0	23,0	13,0
05004942001	M 12	59,0	23,0	13,0





# Wera 2go 2 XL Tool Container

The Wera 2go 2 XL Tool Container with extra low-profile compartments, with its hook and loop fastener system and its compactness, is the ideal solution for individual and convenient tool transport. The inner and outer hook and loop fastener zones provide extremely high flexibility and space utilisation. This fits an incredible amount of tools in and on the container. Wera 2go 2 XL makes for light luggage, because only the essential tools are taken. The robust and sturdy material protects the enclosed tools from damage and moisture, and increases the service life of the tool container. The padded and adjustable wide belt and the close-fitting position of the container provide a comfortable fit. The hands remain free during transport. Including one Wera 2go 4 Tool Quiver with individually adjustable hook and loop fastener divider for screwdrivers and other tools. Four of these holders can be stowed effortlessly.

NEW

## Wera 2go 2 XL Tool Container



### Wera 2go 2 XL Tool Container



Many tools can be taken in this particularly large tool container (Wera 2go 2 XL: 455.0x330.0x170.0 mm; Wera 2go 2: 355.0x330.0x115.0 mm). Up to four Wera 2go 4 Tool Quivers can be stored in the XL container. This ensures order and clarity of contents.

### Robust and dimensionally stable



The robust and dimensionally stable material protects the tools carried against damage and moisture and enhances the service life of the tool container.

1 dimensionally stable, robust Tool Container for up to four Wera 2go 4 Tool Quivers; with hook and loop fastener system for the attachment of other Wera 2go components as well as Wera textile boxes and pouches with hook and loop fastener zones; high resistance against cuts and stabs; 1 handle and 1 Shoulder Strap with adjustable-width padding, adjustable in length, detachable; 1 removable Tool Quiver with handle

05004357001	
Wera 2go XL Container	1 x 455,0x330,0x170,0
Wera 2go 6	1 x 38,0x1470,0
Wera 2go 4	1 x 165,0x165,0x105



Wacken Set 1


A must for every Wacken festival-goer!

The ultimate festival set for survival in (almost) every difficult situation. In W:O:A design with Wacken logo for outing as a Wacken festival fan. A 17-piece tool set for successful repairs on large festival fun items such as campers, tents, buses, but also on small objects such as glasses, shisha, e-cigarettes or many technical devices.



NEW

Wacken Set 1



17-piece set with 1 817 R bit-holding screwdriver handle with telescopic blade and Rapidaptor quick-release chuck; suitable for 1/4" DIN ISO 1173-C 6.3 and E 6.3 hexagon socket insert bits and Wera Series 1 and 4 With "Take it easy" tool finder; with colour coding by size as well as size stamping - for easy and quick location of the desired bit. Six Micro Vario bits, tough, for universal use.

NEW

Counter Display Wacken Set 1



05134004001	
817 R Wacken	1 x 1/4"x133
851/1 BTZ PH	1 x PH 1x25; 1 x PH 2x25
855/1 BTZ PZ	1 x PZ 1x25; 1 x PZ 2x25
867/1 TORX® BTZ	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25
800/1 BTZ	1 x 1,0x5,5x25
822 Wacken	1 x 1/4"x78
851 Micro Vario	1 x PH 00x30; 1 x PH 0x30
867 Micro Vario TORX®	1 x TX 4x30; 1 x TX 5x30; 1 x TX 6x30
800 Micro Vario	1 x 0,23x1,5x30

6x Wacken Set 1

Customers who cannot enter a stocked display in their merchandise management system, please order the following:



Counter Display Wacken, empty	1 x 99134005001	211545
Wacken Set 1	6 x 05134004001	209597

05134005001	6 x Wacken Set 1	4013288	210906
817 R Wacken	1 x 1/4"x133		
851/1 BTZ PH	1 x PH 1x25; 1 x PH 2x25		
855/1 BTZ PZ	1 x PZ 1x25; 1 x PZ 2x25		
867/1 TORX® BTZ	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25		
800/1 BTZ	1 x 1.0x5.5x25		
822 Wacken	1 x 1/4"x78		
851 Micro Vario	1 x PH 00x30; 1 x PH 0x30		
867 Micro Vario TORX®	1 x TX 4x30; 1 x TX 5x30; 1 x TX 6x30		
800 Micro Vario	1 x 0.23x1.5x30		



**BiTorsion Bits**



BiTorsion bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20% in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits.




**Kraftform Micro bit holder**



Slim Kraftform Micro bit holder with Micro bits.



Bicycle Set 1



12-piece set, in a pouch; 1 Wera Bit Ratchet Zyklop Mini 1, drop-forged full steel design, suitable for 1/4" hex bits as per DIN ISO 1173-C 6.3 and E 6.3 and Wera series 1 and 4; can also be used with 1/4" sockets by using the Wera socket adaptor 870/1; 1 universal bit holder (100 mm) with stainless steel sleeve, retaining ring, and strong permanent magnet; 10 bits, tough, for universal use

05004170001		
	8001 A	1 x 1/4"x87,0
●○	899/4/1	1 x 1/4"x100
⊕	851/1 Z PH	1 x PH 2x25
⊗	867/1 TORX®	1 x TX 10x25; 1 x TX 25x25
○	840/1 Z Hex-Plus	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25



The tool set to go



The Bicycle Set 1 contains tools for the most popular screw profiles on road bikes, mountain bikes and e-bikes. Thanks to the compact textile-folding pouch, the set is also the ideal companion for cycling tours.

Bicycle Set Torque 1



16 piece-set; in a surface protecting, compact and extremely robust textile box; low volume and weight for simplified mobility.

1 Click-Torque torque wrench A 5 with 1/4" square drive, covering a range of 2.5 Nm-25 Nm, accuracy  $\pm 4\%$  of the set value, as per DIN EN ISO 6789-1: 2017-07, for clockwise torque control, reversible ratchet, 45 teeth, easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached, ergonomic 2-component handle, 4 Zyklop sockets, with 1/4" drive, 4 Zyklop bit sockets for TORX® screws, with 1/4" drive, with holding function, 7 bit sockets for hexagon socket screws with 1/4" drive with holding function; "Take it easy" tool finder: Colour coding to enable the desired bit socket to be easily selected


05004180001		
	Click-Torque A 5	1 x 1/4", 2,5-25 Nm
●	8790 HMA	1 x 10,0x23,0; 1 x 13,0x23,0; 1 x 14,0x23,0; 1 x 15,0x23,0
⊗	8767 A HF	1 x TX 10x28,0; 1 x TX 20x28,0; 1 x TX 25x28,0; 1 x TX 30x28,0
○	8740 A HF	1 x 3,0x28,0; 1 x 4,0x28,0; 1 x 5,0x28,0; 1 x 5,0x100,0; 1 x 6,0x28,0; 1 x 6,0x100,0; 1 x 8,0x28,0

Click-Torque A 5 torque wrench

Simple and safe



Easy setting and saving of the desired torque value; readable on the main and fine scales.




Simple setting



With audible and tactile clicks when adjusting the scale values.

Release mechanism



When the set torque value is reached, an audible and tactile mechanism triggers.





### Click-Torque A 6 Set 1



20 piece-set; in a surface protecting, compact and extremely robust textile box; low volume and weight for simplified mobility.

1 Click-Torque A 6 torque wrench with 1/4" hexagon drive, covering a range of 2.5 Nm-25 Nm, accuracy  $\pm 4\%$  of the set value, as per DIN EN ISO 6789-1: 2017-07, for clockwise torque control, reversible ratchet, 45 teeth, easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached, ergonomic 2-component handle, 6 Zyklop sockets, 1 adapter 1/4 " hexagon to 1/4" square, 1 Zyklop extension with free-turning sleeve, short,11 bits

05130110001	
	Click-Torque A 6 1 x 1/4", 2,5-25 Nm
⊕	851/4 TZ PH 1 x PH 2x50
⊕	867/4 Z TORX® 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50; 1 x TX 40x50
○	840/4 Z Hex-Plus 1 x 3,0x50; 1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50
○ ○	870/1 1 x 1/4"x25 <sup>1)</sup>
○ ○	8794 SA 1 x 1/4"x75,0
●	8790 HMA 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0

<sup>1)</sup> With friction ball; for manual nut spinner sockets

### Click-Torque C 3 Set 1



13 piece-set; in a surface protecting, compact and extremely robust textile box; low volume and weight for simplified mobility.

1 Click-Torque torque wrench C 3 with 1/2" square drive, covering a range of 40 Nm-200 Nm, accuracy  $\pm 3\%$  of the set value, as per DIN EN ISO 6789-1: 2017-07, for clockwise torque control, reversible ratchet, 45 teeth, easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached, ergonomic 2-component handle, 4 Zyklop sockets, 4 Zyklop bit sockets with holding function for TORX® screws made according to Acument Intellectual Properties specifications, 3 Zyklop bit sockets with holding function for hexagon socket screws, 1 Zyklop extension with free-turning sleeve

05075680001	
	Click-Torque C 3 1 x 1/2", 40-200 Nm
●	8790 HMC 1 x 10,0x37,0; 1 x 13,0x37,0; 1 x 17,0x37,0; 1 x 19,0x37,0
⊕	8767 C HF 1 x TX 30x60,0; 1 x TX 40x60,0; 1 x TX 45x60,0; 1 x TX 50x60,0
○	8740 C HF 1 x 6,0x60,0; 1 x 8,0x60,0; 1 x 10,0x60,0
○ ○	8794 SC 1 x 1/2"x125,0



### Wera 2go 2 Tool Container



1 dimensionally stable, robust Tool Container with hook and loop fastener system for the attachment of other Wera 2go components as well as Wera textile boxes and pouches with hook and loop fastener zones; high resistance against cuts and stabs; 1 handle and 1 Shoulder Strap with adjustable-width padding, adjustable in length, detachable; 1 removable Tool Quiver with handle and a variable hook and loop fastener partition for a division into as many as 5 inner sections.

05004351001	
Wera 2go Container	1 x 355,0x330,0x115,0
Wera 2go 6	1 x 38,0x1470,0
Wera 2go 4	1 x 165,0x165,0x105

### Wera 2go 3 Tool Box



1 dimensionally stable and robust Tool Box, empty, equipped with handle for the storage and transport of tools and small parts; high resistance against cuts and stabs; comes with hook and loop fastener zone for docking with the Wera 2go system.

	mm  mm  mm
05004352001	130,0 325,0 80

### Wera 2go 7 High Tool Box




1 sturdy, robust High Tool Box, with carrying handle, for storage and transport of long tools and spare parts. High resistance against cuts and stabs. With hook and loop fastener zones for docking onto the Wera 2go system.

	mm  mm  mm
05004356001	295,0 100,0 100,0

## Wera 2go

### Variable thanks to the hook and loop fastener system



The inner and outer hook and loop fastener sections mean that other Wera 2go system components can be just as easily attached as all other Wera tools in boxes and pouches with hook and loop fastener zones. This enables an individual composition of the tools needed for a specific job.



## 8100 SA All-in Zyklop Speed Ratchet Set, 1/4" drive, with holding function, metric



## 8100 SA 6 Zyklop Speed Ratchet Set, 1/4" drive, metric



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

05004016001		
⊖	8000 A	1 x 1/4"x152,0
⊕	8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 9,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
⊖	8794 LA	1 x 1/4"x150,0
⊖	8794 A	1 x 1/4"x56,0
⊖	8784 A1	1 x 1/4"x1/4"x37,0
⊕	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
⊕	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50
⊕	867/4 Z TORX®	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50
⊖	840/4 Z Hex-Plus	1 x 3,0x50; 1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50

## 8100 SB 6 Zyklop Speed Ratchet Set, 3/8" drive, metric



29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 3/8" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05004046001		
⊖	8000 B	1 x 3/8"x199,0
⊕	8790 HMB	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0
⊖	8794 LB	1 x 3/8"x200,0
⊖	8794 B	1 x 3/8"x76,0
⊖	8784 B1	1 x 1/4"x3/8"x44,0
⊕	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
⊕	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50; 1 x PZ 3x50
⊕	867/4 Z TORX®	1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50; 1 x TX 40x50
⊖	840/4 Z Hex-Plus	1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50; 1 x 8,0x50
⊖	800/4 Z	1 x 1,0x5,5x50



### Pivots freely



The ratchet head pivots freely and can be locked into any defined position by using the slide switch that is positioned on either side. It is even possible to work in very confined and difficult-to-access areas with enhanced hand clearance. The predefined locking at 0°, 15° and 90°, both to the right and left, ensure safe working without any slipping of the ratchet head.



### Sockets with retaining function for hexagon headed bolts, screws and nuts



The clamping of the screw is achieved by a twin spring loaded ball retention system. The tubing is effectively protected against mechanical wear and tear by a steel ring. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

42-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

1 Zyklop Speed Ratchet with 1/4" drive, 13 Zyklop sockets with 1/4" drive with fastener holding function, 9 Zyklop bit sockets for TORX® screws, with 1/4" drive, with holding function, 8 bit sockets for hexagon socket screws with 1/4" drive with holding function (sizes 2.0 and 2.5 without holding function) and Hex-Plus high torque geometry, 3 Zyklop bit sockets with 1/4" drive for Phillips screws, 3 Zyklop bit sockets with 1/4" drive for Pozidriv screws, 2 Zyklop bit sockets with 1/4" drive for slotted screws, "Take it easy" tool finder: Colour coding to enable the desired bit socket to be easily selected, 1 tool for the simple removal of nuts from sockets with holding function, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension.

05003755001		
⊖	8000 A	1 x 1/4"x152,0
⊖	8796 LA	1 x 1/4"x150,0
⊖	8794 A	1 x 1/4"x56,0
⊕	8790 HMA HF	1 x 4,0x23,0; 1 x 4,5x23,0; 1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 9,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0; 1 x 14,0x23,0
⊕	8767 A HF	1 x TX 8x28,0; 1 x TX 9x28,0; 1 x TX 10x28,0; 1 x TX 15x28,0; 1 x TX 20x28,0; 1 x TX 25x28,0; 1 x TX 27x28,0; 1 x TX 30x28,0; 1 x TX 40x28,0
⊖	8740 A	1 x 2,0x28,0; 1 x 2,5x28,0
⊖	8740 A HF	1 x 3,0x28,0; 1 x 4,0x28,0; 1 x 5,0x28,0; 1 x 6,0x28,0; 1 x 7,0x28,0; 1 x 8,0x28,0
⊕	8751 A	1 x PH 1x28,0; 1 x PH 2x28,0; 1 x PH 3x28,0
⊕	8755 A	1 x PZ 1x28,0; 1 x PZ 2x28,0; 1 x PZ 3x28,0
⊖	8700 A FL ME1	1 x 0,8x5,5x28,0; 1 x 1,2x6,5x28,0; 1 x 14,0x43,0



8100 SC 6 Zyklop Speed Ratchet Set, 1/2" drive, metric




28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits



8100 SA 7 Zyklop Metal Ratchet Set with push-through square, 1/4" drive, metric



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with push-through square and 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

8100 SB 7 Zyklop Metal Ratchet Set with push-through square, 3/8" drive, metric



29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with 3/8" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

8100 SC 7 Zyklop Metal Ratchet Set with push-through square, 1/2" drive, metric



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with push-through square and 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits



function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

"Take it easy" tool finder system - with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding

05004017001		
8003 A	1 x 1/4"x141,0	
8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0	
8794 LA	1 x 1/4"x150,0	
8794 A	1 x 1/4"x56,0	
8784 A1	1 x 1/4"x1/4"x37,0	
851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25	
855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25	
867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25	
840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25	

05004047001		
8003 B	1 x 3/8"x222,0	
8790 HMB	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0	
8794 LB	1 x 3/8"x200,0	
8794 B	1 x 3/8"x76,0	
8784 B1	1 x 1/4"x3/8"x44,0	
851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25	
855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25	
867/1 TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25	
840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25	

05004077001		
8003 C	1 x 1/2"x281,0	
8790 HMC	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0	
8794 LC	1 x 1/2"x250,0	
8794 C	1 x 1/2"x52,0	
8784 C2	1 x 5/16"x1/2"x50,0	
851/2 Z PH	1 x PH 2x32; 1 x PH 3x32	
867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 27x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35	
840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30	



8100 SA 8 Zyklop Metal Ratchet Set with switch lever, 1/4" drive, metric



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

05004018001	
8004 A	1 x 1/4"x141,0
8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
8794 LA	1 x 1/4"x150,0
8794 A	1 x 1/4"x56,0
8784 A1	1 x 1/4"x1/4"x37,0
851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25
840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

8100 SC 8 Zyklop Metal Ratchet Set with switch lever, 1/2" drive, metric



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits

05004078001	
8004 C	1 x 1/2"x281,0
8790 HMC	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0
8794 LC	1 x 1/2"x250,0
8794 C	1 x 1/2"x52,0
8784 C2	1 x 5/16"x1/2"x50,0
851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 27x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30

Belt A 1 Zyklop socket set with holding function, 1/4" drive



10-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with 1/4" drive with fastener holding function. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily selected. 1 tool for the simple removal of nuts from sockets with holding function.

05003880001	
8790 HMA HF	1 x 4,0x23,0; 1 x 4,5x23,0; 1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 13,0x23,0
ME1	1 x 14,0x43,0
Belt A 0/9	1 x 39,0x238,0

Belt A 3 TORX® HF Zyklop bit socket set with holding function, 1/4" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the tool sockets.

9 Zyklop bit sockets for TORX® screws, with 1/4" drive, with holding function. "Take it easy" tool finder: Colour coding to enable the desired bit socket to be easily selected.

05003882001	
8767 A HF	1 x TX 8x28,0; 1 x TX 9x28,0; 1 x TX 10x28,0; 1 x TX 15x28,0; 1 x TX 20x28,0; 1 x TX 25x28,0; 1 x TX 27x28,0; 1 x TX 30x28,0; 1 x TX 40x28,0
Belt A 0/9	1 x 39,0x238,0

Belt A 2 Zyklop In-Hex-Plus bit socket set with holding function, 1/4" drive




8-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

8 bit sockets for hexagon socket screws with 1/4" drive with holding function (sizes: 2.0 and 2.5 without holding function) and Hex-Plus high torque geometry. "Take it easy" tool finder: Colour coding to enable the desired bit socket to be easily selected.

05003881001	
8740 A	1 x 2,0x28,0; 1 x 2,5x28,0
8740 A HF	1 x 3,0x28,0; 1 x 4,0x28,0; 1 x 5,0x28,0; 1 x 6,0x28,0; 1 x 7,0x28,0; 1 x 8,0x28,0
Belt A 0/8	1 x 39,0x220,0

Belt A 4 Zyklop socket set, 1/4" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Smooth turning Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with 1/4" drive. "Take it easy" tool finder: Colour coding to enable the desired socket to be easily selected.

05003883001	
8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
Belt A 0/9	1 x 39,0x238,0



Small return angle



Fine-pitched with 72 teeth for a return angle of only 5°.



Reversible



Switch lever for convenient change of direction.





### 8740 A HF: Zyklop bit socket with holding function



The clamping of the screw is achieved by a twin spring load-  
ed ball retention system. The tubing is effectively protected  
against mechanical wear and tear by a steel ring. The holding  
function is especially helpful  
in confined, hard-to-reach  
spaces, where there is no room  
for a second hand to secure  
the screw.



### Practical nonwoven strips



The textile belt can be attached  
by means of the nonwoven  
reverse side and the hook and  
loop strips e.g. to a wall, shelf,  
tool trolley and to the Wera 2go  
tool transport system.

### Comes with convenient snap hook




The robust textile belt can be  
secured to a belt loop or pocket  
by means of the snap hook.

### Nut extractor tool



This tool enables hexagon  
nuts to be easily removed from  
sockets with holding function.

### Belt A Imperial 1 Zyklop In-Hex-Plus bit socket set with holding function, 1/4" drive




9-piece; robust textile socket belt, including snap hook to enable secure  
fastening to a belt loop or pocket. Non-woven reverse side and hook and loop  
strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera  
2go tool transport system. Fast and easy Twist to Unlock mechanism for  
secure storage and simple removal of the sockets.

9 bit sockets for hexagon socket screws with 1/4" drive with holding function  
(sizes: 5/64", 3/32" and 7/64" without holding function) and Hex-Plus high torque  
geometry. "Take it easy" tool finder: Colour coding to enable the desired bit  
socket to be easily selected.

05003884001		
8740 A	1 x 5/64"x28,0; 1 x 3/32"x28,0; 1 x 7/64"x28,0	
8740 A HF	1 x 1/8"x28,0; 1 x 9/64"x28,0; 1 x 5/32"x28,0; 1 x 3/16"x28,0; 1 x 7/32"x28,0; 1 x 1/4"x28,0	
Belt A 0/8	1 x 39,0x220,0	

### Belt B 1 Zyklop socket set with holding function, 3/8" drive




10-piece; robust textile socket belt, including snap hook to enable secure  
fastening to a belt loop or pocket. Non-woven reverse side and hook and loop  
strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera  
2go tool transport system. Fast and easy Twist to Unlock mechanism for  
secure storage and simple removal of the sockets.

9 Zyklop sockets with 3/8" drive with fastener holding function. "Take it easy"  
tool finder: Colour coding to enable the desired socket to be easily selected. 1  
tool for the simple removal of nuts from sockets with holding function.

05003970001		
8790 HMB HF	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x29,0; 1 x 17,0x29,0; 1 x 18,0x29,0; 1 x 19,0x29,0	
ME1	1 x 14,0x43,0	
Belt B 0/9	1 x 45,0x310,0	

### Belt B 2 Zyklop In-Hex-Plus bit socket set with holding function, 3/8" drive




8-piece; robust textile socket belt, including snap hook to enable secure  
fastening to a belt loop or pocket. Non-woven reverse side and hook and loop  
strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera  
2go tool transport system. Fast and easy Twist to Unlock mechanism for  
secure storage and simple removal of the sockets.

8 bit sockets for hexagon socket screws with 3/8" drive with holding function  
and Hex-Plus high torque geometry. "Take it easy" tool finder: Colour coding  
to enable the desired bit socket to be easily selected.

05003971001		
8740 B HF	1 x 3,0x35,0; 1 x 4,0x35,0; 1 x 5,0x35,0; 1 x 6,0x35,0; 1 x 7,0x38,5; 1 x 8,0x38,5; 1 x 9,0x38,5; 1 x 10,0x38,5	
Belt B 0/8	1 x 45,0x275,0	

### Belt B 3 TORX® HF Zyklop bit socket set with holding function, 3/8" drive




9-piece; robust textile socket belt, including snap hook to enable secure  
fastening to a belt loop or pocket. Non-woven reverse side and hook and loop  
strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera  
2go tool transport system. Fast and easy Twist to Unlock mechanism for  
secure storage and simple removal of the tool sockets.

9 Zyklop bit sockets for TORX® screws, with 3/8" drive, with holding function.  
"Take it easy" tool finder: Colour coding to enable the desired bit socket to be  
easily selected.

05003972001		
8767 B HF	1 x TX 10x35,0; 1 x TX 15x35,0; 1 x TX 20x35,0; 1 x TX 25x35,0; 1 x TX 27x35,0; 1 x TX 30x35,0; 1 x TX 40x35,0; 1 x TX 45x38,5; 1 x TX 50x38,5	
Belt B 0/9	1 x 45,0x310,0	

### Belt B 4 Zyklop socket set, 3/8" drive




9-piece; robust textile socket belt, including snap hook to enable secure  
fastening to a belt loop or pocket. Non-woven reverse side and hook and loop  
strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera  
2go tool transport system. Smooth turning Fast and easy Twist to Unlock  
mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with 3/8" drive. "Take it easy" tool finder: Colour coding to  
enable the desired socket to be easily selected.

05003973001		
8790 HMB	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0	
Belt B 0/9	1 x 45,0x310,0	

### Belt C 1 Zyklop socket set with holding function, 1/2" drive



7-piece; robust textile socket belt, including snap hook to enable secure  
fastening to a belt loop or pocket. Non-woven reverse side and hook and loop  
strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera  
2go tool transport system. Fast and easy Twist to Unlock mechanism for  
secure storage and simple removal of the sockets.

6 Zyklop sockets with 1/2" drive with fastener holding function. "Take it easy"  
tool finder: Colour coding to enable the desired socket to be easily selected. 1  
tool for the simple removal of nuts from sockets with holding function.

05003995001		
8790 HMC HF	1 x 10,0x37,0; 1 x 13,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 19,0x37,0	
ME1	1 x 14,0x43,0	
Belt C 0/6	1 x 45,0x275,0	



Belt C 2 Zyklop In-Hex-Plus bit socket set with holding function, 1/2" drive



6-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

6 bit sockets for hexagon socket screws with 1/2" drive with holding function and Hex-Plus high torque geometry. "Take it easy" tool finder: Colour coding to enable the desired bit socket to be easily selected.

05003996001	
8740 C HF	1 x 4,0x60,0; 1 x 5,0x60,0; 1 x 6,0x60,0; 1 x 7,0x60,0; 1 x 8,0x60,0; 1 x 10,0x60,0
Belt C 0/6	1 x 45,0x275,0

Belt C 3 TORX® HF Zyklop bit socket set with holding function, 1/2" drive



6-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the tool sockets.

6 Zyklop bit sockets for TORX® screws, with 1/2" drive, with holding function. "Take it easy" tool finder: Colour coding to enable the desired bit socket to be easily selected.

05003997001	
8767 C HF	1 x TX 25x60,0; 1 x TX 30x60,0; 1 x TX 40x60,0; 1 x TX 45x60,0; 1 x TX 50x60,0; 1 x TX 55x60,0
Belt C 0/6	1 x 45,0x275,0



For tight spaces



The extremely slim design of the Zyklop VDE ratchet makes it easy to work, even in confined spaces.

Ball lock



The ball lock ensures sockets and accessories are securely fitted, providing increased safety during operation. A short press on the release button allows the tool to be changed quickly.

Switch lever



Switch lever for convenient change of direction.

8007 B VDE Zyklop ratchet, insulated, with switch lever, with 3/8" drive



**Application:** 3/8" square sockets as well as for 3/8" adaptors with square drive, with ball locking device

**Design:** Individually tested as per IEC 60900 at 10,000V for safe working at the approved voltage of 1,000V; slim design to enable work in very confined spaces; fine-tooth mechanism with 80 teeth for a return angle of only 4.5°; switch lever for convenient change of direction; secure socket locking function by push button

05004966001	3/8"	222,0
-------------	------	-------

8100 SB VDE 1 Zyklop Ratchet set, insulated, switch lever, 3/8" drive, metric



17 pieces; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility. Fleece backing and hook and loop fastener system for easy attachment, e. g. on wall, shelf, workshop trolley and the Wera 2go tool transport system. Smooth rotating mechanism for safe storage and easy removal of the Zyklop VDE sockets.

1 Zyklop Ratchet 8007 B VDE, with switch lever, with 3/8" drive, 14 Zyklop VDE sockets, 2 Zyklop VDE extensions, one long, one short, all tools insulated, individually tested as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V. The Zyklop VDE sockets and extensions offer increased safety through 2-component isolation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer.

05004970001	
8007 B VDE	1 x 3/8"x222,0
8790 B VDE	1 x 6,0x46,0; 1 x 7,0x46,0; 1 x 8,0x46,0; 1 x 9,0x46,0; 1 x 10,0x46,0; 1 x 11,0x46,0; 1 x 12,0x46,0; 1 x 13,0x46,0; 1 x 14,0x46,0; 1 x 15,0x46,0; 1 x 16,0x46,0; 1 x 17,0x46,0; 1 x 18,0x46,0; 1 x 19,0x46,0
8794 SB VDE	1 x 3/8"x91,0
8794 LB VDE	1 x 3/8"x166,0





#### Joker Set of ratcheting combination wrenches SB



Set of ratcheting combination wrenches  
4-piece set  
Durable pouch

05073290001	Joker	1 x 10x159; 1 x 13x177; 1 x 17x224; 1 x 19x246	4013288 164407
-------------	-------	---	-------------------

#### Joker Set of ratcheting combination wrenches



Set of ratcheting combination wrenches  
11-piece set  
Durable pouch

05020013001	Joker	1 x 8x144; 1 x 10x159; 1 x 11x165; 1 x 12x170,7; 1 x 13x177; 1 x 14x188; 1 x 15x200; 1 x 16x212; 1 x 17x224; 1 x 18x235; 1 x 19x246
-------------	-------	--

#### Joker Switch Set of ratcheting combination wrenches



Set of ratcheting combination wrenches, reversible  
4-piece set  
Durable pouch


05020090001	Joker Switch	1 x 10x159; 1 x 13x179; 1 x 17x225; 1 x 19x246
-------------	--------------	---

#### Joker Switch Set of ratcheting combination wrenches




Set of ratcheting combination wrenches, reversible  
11-piece set  
Durable pouch

05020091001	Joker Switch	1 x 8x144; 1 x 10x159; 1 x 11x165; 1 x 12x171; 1 x 13x179; 1 x 14x187; 1 x 15x199; 1 x 16x213; 1 x 17x225; 1 x 18x234; 1 x 19x246
-------------	--------------	--



#### Holding function



The Joker's holding function means that nuts and bolts can be held in the jaw and easily positioned where they are needed. Fastening on to the thread can then be done quickly and safely, thanks to the innovative special stop-plate which holds the fastener. No more time-wasting searches for dropped nuts and bolts! After applying and positioning the nut or bolt, fastening can begin immediately – no additional tools required.



#### Integrated limit-stop



Constant re-positioning of the wrench? Difficulty holding fasteners in confined spaces? Easing off to avoid any risks of injury or fastener damage? That was yesterday. Today, the Joker prevents slipping off of the fastener head with its integrated limit-stop – no longer is the thumb needed to act as a depth stop. This makes applications much easier and allows significantly more force to be applied during fastening jobs.




#### Small return angle



Instead of 60°, the Joker only has a 30° return angle thanks to its unique double-hex design. Along with the Joker's straight neck, this means that flipping the wrench has become a thing of the past. With the Joker, you can now loosen and tighten nuts and bolts, in situations where conventional tools fail. Particularly in confined spaces, where conventional open-jawed wrenches cannot be used. The combination of limit stop and small return angle enables effective work, even on screw pipe connections.



Kraftform Kompakt 60



Pouch with 89 mm bits

17-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05059295001		
816 R	1 x 1/4"x119	
851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89	
855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89	
867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89	
800/4 Z	1 x 1,0x5,5x89	
840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89	

Kraftform Kompakt 60

Handle/interchangeable blade system



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.

Storage and transport



The tools can be stored and carried either in a solid plastic case or a robust pouch. In this way the tool is always to hand.

Kraftform Kompakt SH 2 PlumbKit



15-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility.

1 Kraftform chiseldriver 932 A (slotted) with pound-thru hexagonal blade and integrated impact cap for screwdriving and light chiselling; 2 socket wrench screwdrivers 395 HO with hollow shaft for tightening or loosening nuts on protruding threaded rods as well as fixed screws; 1 Kraftform Kompakt VDE handle, 4 Kraftform Kompakt VDE interchangeable blades with reduced blade diameter and integrated protective insulation, so low-lying screws can be accessed, individually tested as per IEC 60900; 1 voltage tester 247, 2 Joker Switch ratcheting combination wrenches with holding function for nuts and bolts, protecting against slippage, double hexagon geometry and extremely hard tips on the metal plate to protect against slippage at high torques, with a small return angle of 30°, switch lever for a comfortable direction change, ring end angled at 15° from the handle; 4 L-keys with Hex-Plus profile (prevents the rounding of hexagon socket screws), with holding function for hexagon socket screws, hexagonal ball-end on the long arm, BlackLaser surface, plastic sleeve, all L-keys are easily identified by their colour coding and size marking.

05136026001		
395 HO	1 x 10,0x90; 1 x 13,0x90	
932 A	1 x 1,2x7,0x125	
Joker Switch	1 x 10x159; 1 x 13x179	
950 SPKL HF Multicolour	1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172	
817 VDE	1 x 9x102	
KK 62 iS	1 x PH 1x154; 1 x PH 2x154	
KK 60 iS	1 x 0,6x3,5x154; 1 x 1,0x5,5x154	
247	1 x 0,5x3,0x70	

Product not available in the USA and Canada.

Kraftform Kompakt SH 2 PlumbKit



Compact tool set with the 15 most important screwdriving tools for plumbing and heating applications.



Hollow shaft nutsetter 395 HO



A screwdriver with a hollow shaft is needed whenever there are screwdriving jobs involving threaded rods i.e. the threaded rod through the nut can slip into the hollow shaft of the screwdriver.

Kraftform Kompakt W 1 Maintenance



The perfect set for diverse maintenance jobs both indoors as well as outdoors - applications: electronics, mechanics, building technology, photovoltaic etc. etc. etc.

Handle/interchangeable blade system – Kraftform Kompakt VDE



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.

Kraftform Kompakt W 1 Maintenance



35-piece set; in surface-protecting, compact textile box, highly robust; low volume and weight for simplified mobility.

Compact tool set with the most important screwdriving tools for maintenance jobs both indoors as well as outdoors. VDE hand holder including 12 VDE blades; 1 Joker double open-ended wrench with holding function, limit stop, small return angle and extremely high-grip toothing; incl. the incredibly fast 1/4" Zyklop Speed ratchet with accessories; 8 manual and power tool sockets in sizes 5.5-13, 1 universal bit holder; 7 25mm bits; 1 screw gripper to firmly hold screws; 1 voltage tester 247; textile box that is very robust and durable; can be positioned upright in the workshop shelf for tidy storage; additional surface protection thanks to the textile outer material; low weight and volume for simplified mobility.

05135926001		
817 VDE	1 x 9x102	
KK 60 i	1 x 0,4x2,5x154	
KK 60 iS	1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154	
KK 62 iS	1 x PH 1x154; 1 x PH 2x154	
KK 65 iS PZ	1 x PZ 1x154; 1 x PZ 2x154	
KK 67 i TORX®	1 x TX 10x154	
KK 67 iS TORX®	1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154	
1440	1 x 4,5 - 6,0x41,0	
247	1 x 0,5x3,0x70	
Joker Double	1 x 10x13x167	
8000 A	1 x 1/4"x152,0	
8784 A1	1 x 1/4"x1/4"x37,0	
8794 SA	1 x 1/4"x75,0	
8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0	
893/4/1 K	1 x 1/4"x50	
855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25	
840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25	
867/1 TORX®	1 x TX 25x25	

Product not available in the USA and Canada.



Tool-Check PLUS



28 bits, 1 hand holder 813 suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6.3 and Wera connection series 1, 1 Rapidaptor bit holder, 1 adaptor 870/1 (1/4" hexagon to 1/4" square), 7 sockets (1/4"); 1 Wera Bit Ratchet Zyklop Mini 1, drop-forged full steel design suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 and Wera connection series 1 and 4; the use of 1/4" sockets is also possible with the application of the Wera adaptor 870/1

05056490001	
	8001 A 1 x 1/4"x87,0
●	813 1 x 1/4"x78
●○	889/4/1 K 1 x 1/4"x50
○	870/1 1 x 1/4"x25 <sup>1)</sup>
●	8790 HMA 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
⊕	851/1 TZ PH 2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
⊕	855/1 TH PZ 1 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
⊕	867/1 TZ 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; TORX® 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
⊕	867/1 Z 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; TORX® BO 1 x TX 25x25; 1 x TX 30x25
○	840/1 Z Hex-Plus 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25
●	800/1 TZ 1 x 1,0x5,5x25

<sup>1)</sup> With friction ball; for manual nut spinner sockets

Bit-Check 30 Metal 1



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 29 bits, tough, for universal use.

05057434001	
●○	899/4/1 1 x 1/4"x50
⊕	851/1 Z PH 3 x PH 1x25; 3 x PH 2x25; 2 x PH 3x25
⊕	855/1 Z PZ 3 x PZ 1x25; 3 x PZ 2x25; 3 x PZ 3x25
⊕	867/1 TORX® 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
●	800/1 Z 1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25
○	840/1 Z Hex-Plus 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

Bit-Check 30 Wood 2



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 29 bits, tough, for universal use.

05057432001	
●○	899/4/1 1 x 1/4"x50
⊕	851/1 Z PH 1 x PH 2x25
⊕	855/1 Z PZ 2 x PZ 1x25; 5 x PZ 2x25; 2 x PZ 3x25
⊕	867/1 TORX® 3 x TX 10x25; 4 x TX 15x25; 4 x TX 20x25; 4 x TX 25x25; 3 x TX 30x25; 1 x TX 40x25

Bit-Check 30 TX Universal 1



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 29 bits, tough, for universal use.

05057908001	
●○	899/4/1 1 x 1/4"x50
⊕	867/1 TORX® 3 x TX 10x25; 5 x TX 15x25; 8 x TX 20x25; 7 x TX 25x25; 4 x TX 30x25; 2 x TX 40x25

Bit-Box 15 Impaktor PH



**Application:** Phillips screws

**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders

**Design:** The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. "Take it easy" tool finder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

05057752001	851/1 IMP DC ⊕ 15 x PH 2x25	4013288 187918
-------------	-----------------------------	-------------------

Bit-Box 15 Impaktor PZ



**Application:** Suitable for Pozidriv screws

**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders

**Design:** The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. "Take it easy" tool finder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

05057763001	855/1 IMP DC ⊕ 15 x PZ 2x25	4013288 187901
-------------	-----------------------------	-------------------

Bit-Box 15 Impaktor TX



**Application:** TORX® socket screws

**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders

**Design:** The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. "Take it easy" tool finder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

05057772001	867/1 IMP DC ⊕ 15 x TX 20x25	4013288 187871
05057775001	867/1 IMP DC ⊕ 15 x TX 25x25	187888
05057776001	867/1 IMP DC ⊕ 15 x TX 30x25	187895

Bit-Box 20 BTH PZ



**Application:** Suitable for Pozidriv screws

**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders

**Design:** BiTorsion for long service life, extra-hard. "Take it easy" tool finder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

05057762001	855/1 BTH PZ ⊕ 20 x PZ 2x25	4013288 187963
-------------	-----------------------------	-------------------

Bit-Box 20 BTZ PH



**Application:** Phillips screws

**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders

**Design:** BiTorsion for long service life, extra-tough, for universal use. "Take it easy" tool finder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

05057751001	851/1 BTZ PH ⊕ 20 x PH 2x25	4013288 187956
-------------	-----------------------------	-------------------

Bit-Box 20 BTZ PZ



**Application:** Suitable for Pozidriv screws

**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders

**Design:** BiTorsion for long service life, extra-tough, for universal use. "Take it easy" tool finder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

05057761001	855/1 BTZ PZ ⊕ 20 x PZ 2x25	4013288 187970
-------------	-----------------------------	-------------------



Bit-Box 20 BTZ TX



**Application:** TORX® socket screws  
**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders  
**Design:** BiTorsion for long service life, extra-tough, for universal use. "Take it easy" tool finder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

			4013288
05057771001	867/1 TORX®	20 x TX 20x25	187932
05057774001	867/1 TORX®	20 x TX 25x25	187949

Bit-Box 20 PH



**Application:** Phillips screws  
**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders  
**Design:** for universal use

			4013288
05057750001	851/1 PH	20 x PH 2x25	188014

Bit-Box 20 PZ



**Application:** Suitable for Pozidriv screws  
**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders  
**Design:** for universal use

			4013288
05057760001	855/1 PZ	20 x PZ 2x25	188052

Bit-Box 20 RZ PH



**Application:** Drywall screws  
**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders  
**Design:** Reduced shaft diameter, tough, for universal use

			4013288
05057753001	851/1 RZ PH	20 x PH 2x25	187987

Bit-Box 20 TX



**Application:** TORX® socket screws  
**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders  
**Design:** for universal use

			4013288
05057770001	867/1 TORX®	20 x TX 20x25	187994
05057773001	867/1 TORX®	20 x TX 25x25	188007

Bit-Box 20 V Robertson




**Application:** Square socket head screws  
**Drive:** 1/4" hexagon, suitable for DIN ISO 1173-D 6.3 bit holders  
**Design:** Tough, for universal use, with holding function

			4013288
05057790001	868/1 V	20 x # 2x25	188083




3950/9 Hex-Plus Multicolour Stainless 1 L-key set, metric, stainless



9-piece set in a two-component clip  
**Application:** Hexagon socket screws  
**Design:** Stainless steel, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.  
**Tip:** Hex-Plus, ball-end hexagon on long arm

05022669001	3950 SPKL Multicolour	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112; 1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195; 1 x 10,0x224

950/9 Hex-Plus Multicolour HF 1 L-key set, metric, BlackLaser, with holding function



9-piece set in a two-component clip  
**Application:** Hexagon socket screws  
**Design:** BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.  
**Tip:** Hex-Plus, ball-end hexagon on long arm, holding function for hexagon socket screws, sizes: 1,5, 2,0 and 2,5 without holding function

05022210001	950 SPKL Multicolour	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112
	950 SPKL HF Multicolour	1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195; 1 x 10,0x224





### L-keys 950 L HF: With retaining function on long arm



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to sec



### "Take it easy" tool finder system



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

### 950/9 Hex-Plus Multicolour 1 SB Multicolour L-key set, metric, BlackLaser



9-piece set in a two-component clip

**Application:** Hexagon socket screws

**Design:** BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

**Tip:** Hex-Plus, ball-end hexagon on long arm

05073593001	950 SPKL Multicolour	1 x 1.5x90; 1 x 2.0x101; 1 x 2.5x112; 1 x 3.0x123; 1 x 4.0x137; 1 x 5.0x154; 1 x 6.0x172; 1 x 8.0x195; 1 x 10.0x224	4013288 165688
-------------	----------------------	---	----------------

### 950/9 L Hex-Plus HF 1 L-key set, metric, chrome-plated, with holding function



9-piece set in a two-component clip

**Application:** Hexagon socket screws


**Design:** Chrome-plated

**Tip:** Hex-Plus, holding function for hexagon socket screws on long arm, sizes: 1,5, 2,0 and 2,5 without holding function

05022130001			
○	950 L	1 x 1,5x90 <sup>1)</sup> ; 1 x 2,0x100; 1 x 2,5x112	
○	950 L HF	1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180; 1 x 8,0x200; 1 x 10,0x219	

<sup>1)</sup> Regular hexagon

### 950/9 Hex-Plus 1 SB L-key set, metric, chrome-plated



9-piece set in a two-component clip

**Application:** Hexagon socket screws


**Design:** Chrome-plated

**Tip:** Hex-Plus, ball-end hexagon on long arm

05073391001	950 PKL	1 x 1.5x90 <sup>1)</sup> ; 1 x 2.0x100; 1 x 2.5x112; 1 x 3.0x126; 1 x 4.0x140; 1 x 5.0x160; 1 x 6.0x180; 1 x 8.0x200; 1 x 10.0x219	4013288 030160
-------------	---------	--	----------------

<sup>1)</sup> Regular hexagon

### 950/9 Hex-Plus 6 SB L-key set, metric, BlackLaser



9-piece set in a two-component clip

**Application:** Hexagon socket screws

**Design:** BlackLaser surface

**Tip:** Hex-Plus, ball-end hexagon on long arm

05073596001	950 PKL BM	1 x 1.5x90 <sup>1)</sup> ; 1 x 2.0x100; 1 x 2.5x112; 1 x 3.0x126; 1 x 4.0x140; 1 x 5.0x160; 1 x 6.0x180; 1 x 8.0x200; 1 x 10.0x219	4013288 106414
-------------	------------	--	----------------

<sup>1)</sup> Regular hexagon

### 3967/9 TX SXL Multicolour HF Stainless 1 L-key set with holding function, stainless



9-piece set in a two-component clip

**Application:** TORX® socket screws

**Design:** Stainless steel, round

**Tip:** TORX® on short arm, holding function for TORX® screws made according to Acument Intellectual Properties specifications on long arm, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

05022689001			
⊗	3967 SXL HF TORX® Multicolour	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112; 1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224	

### 967/9 TX XL Multicolour HF 1 L-key set with holding function, long



9-piece set in a two-component clip

**Application:** TORX® socket screws

**Design:** Zinc-phosphated, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

**Tip:** Holding function for TORX® screws made according to Acument Intellectual Properties specifications

05024470001			
⊗	967 SXL HF TORX® Multicolour	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112; 1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224	



967/9 TX XL Multicolour 1 Multicolour L-key set for TORX® screws, long



9-piece set in a two-component clip

**Application:** TORX® socket screws

**Design:** Round, zinc-phosphated, durable plastic sleeve. The contrast-ing inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

**Tip:** TORX® on short arm, TORX® ball end on long arm, TX 8, TX 9, TX 10: without ball-end at the long arm

05024480001		
⊕	967 SXL TORX® Multicolour	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112
⊕⊕	967 SPKXL TORX® Multicolour	1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224

967/9 TX Multicolour HF 1 L-key set with holding function



9-piece set in a two-component clip

**Application:** TORX® socket screws

**Design:** Round, zinc-phosphated, durable plastic sleeve. The contrast-ing inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

**Tip:** Holding function for TORX® screws made according to Acument Intellectual Properties specifications, BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

05024179001		
⊕	967 SL TORX® HF	1 x TX 8x76; 1 x TX 9x79; 1 x TX 10x85; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132



TORX® ball-end



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.



Holding function for recessed TORX® screws




The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

With thermoplastic sleeve



L-keys with a thermoplastic sleeve are manufactured out of easy-to-grip, circular material. The sleeve ensures that work is safe and comfortable even at low temperatures. Colour coding and large stamp to enable the desired L-key to be easily located.

Kraftform Micro 12 Universal 1 Screwdriver set for electronic applications




**Application:** Slotted and Phillips screws, TORX® socket screws, and Hexa-gon socket screws

**Content:** 12-piece set, in a belt pouch

05073675001		
⊕	2050 PH Micro <sup>1</sup>	1 x PH 00x60 <sup>1)</sup> ; 1 x PH 0x60 <sup>2)</sup>
⊕⊕	2067 TORX® HF	1 x TX 5x40; 1 x TX 6x40
⊕⊕⊕	2035 Micro	1 x 0,23x1,5x40; 1 x 0,30x1,8x60; 1 x 0,40x2,0x60; 1 x 0,40x2,5x80; 1 x 0,50x3,0x80
○	2054 Micro	1 x 0,9x40; 1 x 1,5x60; 1 x 2x60

<sup>1)</sup> Optimised for Asian PH screws  
<sup>2)</sup> Size 0 modified according to JCIS 0 (Japanese Camera Industrial Standard)

395 H0/3 Sanitary Nutdriver set



**Application:** Hexagon headed bolts, screws and nuts

**Content:** 3-piece set in display carton

**TIP:** The hollow shaft enables seized screws or those on long threads to be tightened and loosened

05134275001		
⊕	395 H0	1 x 10,0x90; 1 x 13,0x90; 1 x 7/16"x90

Kraftform Micro: Applications



Indispensable for many users, including electronics techni-cians, opticians, precision engi-neers, jewellers, EDP hardware fitters and model-makers.



Kraftform Micro: The refined screw-driver for electronics technicians



The Kraftform Micro, with its three zones and their specific arrangement, satisfies these requirements perfectly. The free-turning cap that provides support for the hand works with these advantages, ena-bling quick and easy precision work.

395 H0: With hollow shaft



The 395 H0 screwdrivers have a hollow shaft that can accom-modate protruding threaded rods. This is particularly useful when installing/removing mixer taps on washbasins.



Kraftform: Rapid hand repositioning




The hard materials used for the handle ensure rapid hand repositioning without any dan-ger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.





**Wera**  
BE A TOOL REBEL

### Kraftform Big Pack 300



Kraftform Plus – Series 300. With Lasertip blade, voltage tester and rack. "Take it easy" tool finder: colour coding according to profile and size stamp.

**Application:** Slotted, cross, Phillips-Recess, Pozidriv and TORX® screws  
**Content:** 14-piece set in display carton

05105630001		
+	350 PH	1 x PH 1x80; 1 x PH 2x100; 1 x PH 3x150
+	355 PZ	1 x PZ 1x80; 1 x PZ 2x100; 1 x PZ 3x150
+	367 TORX®	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115
●	334	1 x 1,2x6,5x150
●	335	1 x 0,6x3,5x100; 1 x 0,8x4,0x100
	Rack	2 x 190,0x50,0

### 334/6 Rack screwdriver set Kraftform Plus Lasertip and rack




Lasertip round blades and rack. "Take it easy" tool finder: colour coding according to profile and size stamp.

**Application:** Slotted and Phillips screws  
**Content:** 6-piece set and rack in display carton

05105650001		
+	350 PH	1 x PH 1x80; 1 x PH 2x100
●	334	1 x 1,2x6,5x150
●	335	1 x 0,5x3,0x80 <sup>1)</sup> ; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

### 334/355/6 Rack screwdriver set Kraftform Plus Lasertip and rack



Lasertip round blades and rack. "Take it easy" tool finder: colour coding according to profile and size stamp.

**Application:** Slotted and Pozidriv screws  
**Content:** 6-piece set and rack in display carton

05105656001		
+	355 PZ	1 x PZ 1x80; 1 x PZ 2x100
●	334	1 x 1,2x6,5x150
●	335	1 x 0,5x3,0x80 <sup>1)</sup> ; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

<sup>1)</sup>without Lasertip




### "Take it easy" Tool Finder



Screwdrivers with "Take it easy" tool finder: colour coding according to profile and size stamp.



Kraftform Big Pack 100 VDE



Kraftform: The safety screwdriver with Lasertip blade, voltage tester and rack. "Take it easy" tool finder: colour coding according to profile and size stamp.


**Application:** Slotted, Phillips, PlusMinus (Pozidriv/slotted), Pozidriv and TORX® screws

**Content:** 14-piece set in display carton

05105631001	
+	162 i PH VDE 1 x PH 1x80; 1 x PH 2x100
+	165 i PZ VDE 1 x PZ 1x80; 1 x PZ 2x100
+	165 i PZ/S VDE 1 x # 1x80; 1 x # 2x100
+	167 i TORX® VDE 1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x80
-	160 iS 1 x 0,6x3,5x100
-	160 i VDE 1 x 0,4x2,5x80 <sup>1)</sup> ; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
-	247 1 x 0,5x3,0x70
	Rack 2 x 190,0x50,0

<sup>1)</sup> without Lasertip  
Product not available in the USA and Canada.

160 i/7 Rack screwdriver set Kraftform Plus Series 100, voltage tester and rack



Kraftform: The safety screwdriver with Lasertip blade, voltage tester and rack. "Take it easy" tool finder: colour coding according to profile and size stamp.



**Application:** Slotted and Phillips screws

**Content:** 7-piece set and rack in display carton

05006147001	
+	162 i PH VDE 1 x PH 1x80; 1 x PH 2x100
-	160 i VDE 1 x 0,4x2,5x80 <sup>1)</sup> ; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
-	247 1 x 0,5x3,0x70

<sup>1)</sup> without Lasertip  
Product not available in the USA and Canada.

160 i/165 i/7 Rack screwdriver set Kraftform Plus Series 100, voltage tester and rack



Kraftform: The safety screwdriver with Lasertip blade, voltage tester and rack. "Take it easy" tool finder: colour coding according to profile and size stamp.

**Application:** Slotted and Pozidriv screws

**Content:** 7-piece set and rack in display carton

05006148001	
+	165 i PZ VDE 1 x PZ 1x80; 1 x PZ 2x100
-	160 i VDE 1 x 0,4x2,5x80 <sup>1)</sup> ; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
-	247 1 x 0,5x3,0x70

<sup>1)</sup> without Lasertip  
Product not available in the USA and Canada.

Big Pack 900 Screwdriver set Kraftform Wera: Chiseldriver and rack



**Application:** Slotted, Phillips, Pozidriv and TORX® socket screws

**Content:** 13-piece set

05133285001	
+	917 SPH 1 x PH 1x80; 1 x PH 2x100; 1 x PH 3x150
+	918 SPZ 1 x PZ 1x80; 1 x PZ 2x100; 1 x PZ 3x150
-	932 A 1 x 0,6x3,5x80 <sup>1)</sup> ; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125; 1 x 1,6x9,0x150
+	977 TORX® 1 x TX 20x90; 1 x TX 25x100
	Rack 2 x 190,0x50,0

<sup>1)</sup> No throughout blade, no impact cap and no hexagon bolster

932/6 Screwdriver set Kraftform Wera: Chiseldriver and rack



**Application:** Slotted and Phillips screws

**Content:** 6-piece set and rack in display carton

05018282001	
+	917 SPH 1 x PH 1x80; 1 x PH 2x100
-	932 A 1 x 0,6x3,5x80 <sup>1)</sup> ; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125

<sup>1)</sup> No throughout blade, no impact cap and no hexagon bolster

932/918/6 Screwdriver set Kraftform Wera: Chiseldriver and rack



**Application:** Slotted and Pozidriv screws

**Content:** 6-piece set and rack in display carton

05018287001	
+	918 SPZ 1 x PZ 1x80; 1 x PZ 2x100
-	932 A 1 x 0,6x3,5x80 <sup>1)</sup> ; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125

<sup>1)</sup> No throughout blade, no impact cap and no hexagon bolster

Kraftform Plus – Series 100 VDE



Individually tested

The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Kraftform Plus – Series 900



Integrated impact cap

An integrated impact cap lengthens the service life and reduces the danger of splintering. Nevertheless, always wear protective goggles.






Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal

Phone: +49 (0)202/4045-0  
Fax: +49 (0)202/403634  
E-Mail: [info@wera.de](mailto:info@wera.de)  
[www.wera.de](http://www.wera.de)

No liability for printing errors or mistakes  
shall be assumed.

Wera Tools (UK) LTD.  
Railway View  
Clay Cross  
Chesterfield  
Derbyshire, S45 9FR

Phone: +44 (0)1246 / 277756  
Fax: +44 (0)1246 / 273335  
eMail: [queries@wera-tools.co.uk](mailto:queries@wera-tools.co.uk)  
Internet: [www.wera-tools.co.uk](http://www.wera-tools.co.uk)



EN 05 510262 019 - 0053701 - 01