



<b>EAN:</b>	4013288111685	<b>Size:</b>	150x115x35 mm
<b>Part number:</b>	05104651001	<b>Weight:</b>	289 g
<b>Article number:</b>	847/7 HSS	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82075060

- Ideal for mobile repair and assembly work
- Rapidaptor holder for rapid bit change
- 1/4" drive suitable for power screwdrivers
- Rapidaptor universal holder and combination tapping drill bits with 1/4" drive
- In practical and robust plastic box

7-piece combination tapping drill bit set by Wera in a stable plastic box. 1/4" drive suitable for holders as per DIN ISO 1173-D 6.3. Comes with Rapidaptor quick-release chuck for insertion in the power screwdriver or the chuck of the electric drill. The hexagonal shaft ensures very good power transfer. HSS = high speed steel. A finely-tuned material elasticity provides for great durability. Very good centring properties. Easy cutting. Perfect chip removal. Low tilt risk. Precise return movement.

#### Web link

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_bit\\_sets\\_bit\\_sets\\_for\\_special\\_applications\\_847\\_7\\_hss.html](https://products.wera.de/en/bits_holders_adaptors_bit_sets_bit_sets_for_special_applications_847_7_hss.html)

Wera - 847/7 HSS  
05104651001 - 4013288111685

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

### Combination drill bits



- Combination drill bits
- Application: Core-hole drilling, tapping and deburring in one operation
- 1/4" drive suitable for holders as per DIN 3126-D 6.3 (ISO 1173)
- Hexagon shaft for very high torque transfer
- HSS = high speed steel
- Finely adjusted material elasticity for long service life
- Excellent centring properties
- Straightforward cutting
- Perfect chip removal
- Low jamming risk
- Precise return control

### Rapidaptor holder



Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool.

### Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

### Rapid-out




Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

### Chuck-all




The Rapidaptor quick-release chucks hold 1/4" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

### Single-hand function



Every function of the Rapidaptor quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

### Rapid-spin



The free-turning sleeve allows screw steadying at the start of the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping. It can also be used as a short extension for 1/4" applications e.g. in combination with the Wera Zyklop Ratchets.

### Non-magnetic design



Non-magnetic bitholders that do not attract metal filings.

### Web link

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_bit\\_sets\\_bit\\_sets\\_for\\_special\\_applications\\_847\\_7\\_hss.html](https://products.wera.de/en/bits_holders_adaptors_bit_sets_bit_sets_for_special_applications_847_7_hss.html)

Wera - 847/7 HSS  
05104651001 - 4013288111685

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)