

Bits for Phillips Screws



<b>EAN:</b>	4013288163189	<b>Size:</b>	150x7x7 mm
<b>Part number:</b>	05203913001	<b>Weight:</b>	27 g
<b>Article number:</b>	853/4 ACR® SL	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For Phillips screws
- ACR (anti cam-out feature) to prevent any slipping out of the screw head
- Permanently magnetized, thus screws can be held securely on the tip of the bit
- With plastic sleeve, protects components from being damaged when screwdriving.
- 1/4" hexagon drive (Wera connecting series 4)

High quality bits with rough ribs (anti cam-out feature, ACR) to prevent any slipping out of the screw head, permanently magnetized, thus screws can be held securely on the tip of the bit; with plastic sleeve, protects components from being damaged when screwdriving. Tough viscous for universal use. 1/4" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.

Web link

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_the\\_range\\_of\\_bits\\_bits\\_for\\_phillips\\_screws\\_853\\_4\\_acr\\_sl.html](https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_phillips_screws_853_4_acr_sl.html)

Wera - 853/4 ACR® SL  
05203913001 - 4013288163189

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## Bits for Phillips Screws

## ACR®-Bits



ACR® stands for "anti-cam-out ribs". ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® is a registered trademark of Phillips Screw Company.

## With sleeve







With plastic sleeve, protects components from being damaged when screwdriving.

## Magnetic



Permanently magnetized, thus screws can be held securely on the tip of the bit.

## Further versions in this product family:

				
		mm	inch	mm
05323780001	PH 2	50	2	5.2
05323781001	PH 2	90	3 1/2	5.2
<b>05203913001</b>	<b>PH 2</b>	<b>150</b>	<b>6</b>	<b>5.2</b>
05203914001	PH 2	200	8	5.2

## Web link

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_the\\_range\\_of\\_bits\\_bits\\_for\\_phillips\\_screws\\_853\\_4\\_acr\\_sl.html](https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_phillips_screws_853_4_acr_sl.html)

Wera - 853/4 ACR® SL  
 05203913001 - 4013288163189

Wera Werkzeuge GmbH  
 Korzter Straße 21-25  
 D-42349 Wuppertal  
 Tel: +49 (0)2 02 / 40 45-0  
 E-Mail: [info@wera.de](mailto:info@wera.de)