

## **Z5950 Series**

Commercial Heavy Duty Toilet Seat

TAG \_\_\_\_\_



Z5955SS-EL shown above



Z5955SS-JUV shown above

## Architectural/Engineering Approval

These dimensions and specifications are subject to change without notice.

Fixture dimensions meet ANSI/ASME standard A112.19.2 and CAN/CSA B45 requirements.

## Z5950 Series

- Injection molded for rugged, heavy duty use.
- Highly resistant to cleansers and strong chemicals
- Stainless steel check hinge
- Integrally molded bumpers for
- lasting durability

Select your seat and check all options that apply

## **Engineering Specification:**

- □ **Z5955SS-EL** Elongated, standard white, open front toilet seat, less cover, with stainless steel check hinge.
  - □ -AM Anti-microbial protection
  - -AMFR Anti-microbial/Fire Retardant
  - □ -BK Black
  - □ -STS Self-sustaining stainless steel check hinge
- □ **Z5956SS-EL** Elongated, extra heavy duty, premium white, open front toilet seat, less cover, with stainless steel check hinge.
  - □-ADA 2" Lift
  - -AM Anti-microbial protection
  - □-BK Black
  - **-STS** Self-sustaining stainless steel check hinge
- □ **Z5957SS** White, open front toilet seat, with cover and stainless steel check hinge.
  - □ -AM Anti-microbial protection
  - □ -AMFR Anti-microbial/Fire Retardant
  - □ -BK Black
  - □ -EL Elongated
  - □ -RD Round
  - **-STS** Self-sustaining stainless steel check hinge
- □ **Z5958SS** White, closed front toilet seat, with cover and stainless steel check hinge.
  - -AMFR Anti-microbial/Fire Retardant
  - □ -EL Elongated
  - □-RD Round
  - **-STS** Self-sustaining stainless steel check hinge
- □ **Z5959SS-JUV** White, anti-microbial open front child's toilet seat, less cover, with stainless steel check hinge.

See Zurn One Systems for suggested packages.

ZURN INDUSTRIES, LLC. ♦ COMMERCIAL BRASS OPERATION ♦ 5900 ELWIN BUCHANAN DRIVE ♦ SANFORD NC 27330 Phone: 1-800-997-3876 ♦ Fax: 919-775-3541 ♦ www.zurn.com In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905-405-8272 Fax: 905-405-1292