



## FEATURES:

- One person installation
- Re-enterable, no special tools required
- Air and water tight
- No I.D. reduction
- Excellent pull out strength on HDPE, PVC, FRP and steel
- No-Stop version available for confined areas or repairs (\*NS)
- ETL Listed
- Listed to CSA STD C22.2 18.3-04
- Listed to UL STD 514B

Plastic coupler designed for coupling HDPE & PVC conduit. Can also be used to couple dissimilar conduits such as HDPE to PVC, threaded or non-threaded metal conduit, or fiberglass (FRP) conduit. The coupler features stainless steel band clamps (hand tightened using a 5/16" nut driver) and locking ring. A pre-lubricated O-ring forms an air-tight seal to withstand 125 psi. Also, a specialized coupler for use by electrical installers requiring ETL/UL listing. **NOTE:** Certain sizes ETL-Listed for use with HDPE and PVC for underground and concrete encased applications only! Not for use with PVC in above-ground applications. Not premise (indoor) rated.

| PART #   | SHUR-LOCK II COUPLER<br>HDPE to HDPE                                                      |     | NOMINAL<br>PULL-OUT STRENGTH | PACKAGING | SHIP<br>WEIGHT (lbs) |
|----------|-------------------------------------------------------------------------------------------|-----|------------------------------|-----------|----------------------|
| 20000118 | 1.00" Shur-Lock II Coupler SDR 1.315" ± 0.020"                                            | ETL | 600 lbs                      | 10/CTN    | 2.0                  |
| 20000119 | 1.00" Shur-Lock II Coupler HYB 1.350" ± 0.020"                                            |     | 600 lbs                      | 10/CTN    | 2.0                  |
| 20000120 | 1.25" Shur-Lock II Coupler SDR 1.660" ± 0.020"                                            | ETL | 700 lbs                      | 10/CTN    | 2.3                  |
| 20000121 | 1.25" Shur-Lock II Coupler HYB 1.590" ± 0.020"                                            |     | 700 lbs                      | 10/CTN    | 2.4                  |
| 20000177 | 1.25" Shur-Lock II Coupler 1.534" ± 0.020"                                                |     | 700 lbs                      | 10/CTN    | 2.4                  |
| 20000122 | 1.50" Shur-Lock II Coupler SDR 1.900" ± 0.020"                                            | ETL | 800 lbs                      | 10/CTN    | 2.6                  |
| 20000123 | 2.00" Shur-Lock II Coupler SDR 2.375" ± 0.020"                                            | ETL | 800 lbs                      | 10/CTN    | 3.2                  |
| 20000264 | 2.00" Shur-Lock II Coupler-Extended SDR 2.375" ± 0.020"<br>(8.25" long vs 5.75" standard) |     | 800 lbs                      | 10/CTN    | 3.7                  |
| 20000172 | 2.50" Shur-Lock II Coupler SDR 2.875" ± 0.020"                                            | ETL | 1,000 lbs                    | 6/CTN     | 3.45                 |
| 20000173 | 3.00" Shur-Lock II Coupler SDR 3.500" ± 0.020"                                            | ETL | 1,000 lbs                    | 6/CTN     | 4.6                  |
| 20000245 | 4.00" Shur-Lock II Coupler SDR 4.500" ± 0.020"                                            | ETL | 1,000 lbs                    | 4/CTN     | 5.0                  |
| 20000254 | 5.00" Shur-Lock II Coupler SDR 5.563" ± 0.020"                                            | ETL | 1,000 lbs                    | 2/CTN     | 3.75                 |
| 20000256 | 6.00" Shur-Lock II Coupler SDR 6.625" ± 0.020"                                            | ETL | 1,000 lbs                    | 2/CTN     | 4.45                 |

ETL Please specify if ETL listing is required.

Specialized couplers for coupling dissimilar-sized ducts within the ranges specified.

| PART #   | SHUR-LOCK II COUPLER<br>TRANSITION                                  | NOMINAL<br>PULL-OUT STRENGTH | PACKAGING | SHIP<br>WEIGHT (lbs) |
|----------|---------------------------------------------------------------------|------------------------------|-----------|----------------------|
| 20002290 | 1.00" Shur-Lock II SG/FC to SDR 1.400" -1.440" to 1.295" -1.335"    | 600 lbs                      | 10/CTN    | 2.0                  |
| 20002292 | 1.00" Shur-Lock II SG/FC to Hybrid 1.400" -1.440" to 1.330" -1.370" | 600 lbs                      | 10/CTN    | 2.0                  |
| 20002263 | 1.25" Shur-Lock II SG/FC to Hybrid 1.640" -1.680" to 1.570" -1.610" | 700 lbs                      | 10/CTN    | 2.45                 |

Center stop is removed to allow the coupler to be pulled back over the end of the duct for limited clearance installations.

| PART #   | SHUR-LOCK II COUPLER<br>NO STOP (NS)                                                                                                                                        | NOMINAL<br>PULL-OUT STRENGTH | PACKAGING | SHIP<br>WEIGHT (lbs) |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------|----------------------|
| 20002340 | 1.00" Shur-Lock II Coupler SDR 1.315" $\pm$ 0.020"                                         | 600 lbs                      | 10/CTN    | 2.0                  |
| 20000236 | 1.25" Shur-Lock II Coupler SDR 1.660" $\pm$ 0.020"                                         | 700 lbs                      | 10/CTN    | 2.3                  |
| 20002341 | 1.50" Shur-Lock II Coupler SDR 1.900" $\pm$ 0.020"                                         | 800 lbs                      | 10/CTN    | 2.6                  |
| 20002374 | 1.50" Shur-Lock II Coupler-Extended SDR 1.900" + 0.020" <br>(8.75" long vs 5.75" standard) | 800 lbs                      | 10/CTN    | 3.0                  |
| 20000237 | 2.00" Shur-Lock II Coupler SDR 2.375" $\pm$ 0.020"                                         | 800 lbs                      | 10/CTN    | 3.2                  |
| 20000251 | 2.00" Shur-Lock II Coupler-Extended SDR 2.375" $\pm$ 0.020"<br>(8.25" long vs 5.75" standard)                                                                               | 800 lbs                      | 10/CTN    | 3.7                  |
| 20000238 | 2.50" Shur-Lock II Coupler SDR 2.875" $\pm$ 0.020"                                         | 1,000 lbs                    | 6/CTN     | 3.45                 |
| 20000239 | 3.00" Shur-Lock II Coupler SDR 3.500" $\pm$ 0.020"                                         | 1,000 lbs                    | 6/CTN     | 4.6                  |
| 20000260 | 4.00" Shur-Lock II Coupler SDR 4.500" $\pm$ 0.020"                                        | 1,000 lbs                    | 4/CTN     | 5.0                  |
| 20001531 | 5.00" Shur-Lock II Coupler SDR 5.563" $\pm$ 0.020"                                       | 1,000 lbs                    | 2/CTN     | 3.75                 |
| 20000261 | 6.00" Shur-Lock II Coupler SDR 6.625" $\pm$ 0.020"                                       | 1,000 lbs                    | 2/CTN     | 4.45                 |

| PART #   | PALM RATCHET                                                                                  | PACKAGING | SHIP<br>WEIGHT (lbs) |
|----------|-----------------------------------------------------------------------------------------------|-----------|----------------------|
| 20002747 | Palm Ratchet with 5/16" and 7/16" Sockets.<br>Used with Shur-Lock II and Split-Lock couplers. | EACH      | 1                    |



 Please specify if ETL listing is required.