

THREAD INSTALL ROD HANGER WITH ANGLE BRACKET, 0.25" HOLE 1, PLAIN, 0.375" HOLE 2, THREADED

CATALOG NUMBER

6TIB



CERTIFICATIONS



FEATURES

Suspends threaded rod from horizontal structures such as laminated wood or concrete beams, joists, ceilings and walls


| PRODUCT ATTRIBUTES | |
|------------------------------------------|--|
| Material: Spring Steel;Steel | |
| Finish: nVent CADDY Armour;Pregalvanized | |
| Hole Size 1: 1/4" | |
| Hole Type 1: Plain | |
| Hole Size 2: 3/8" | |
| Hole Type 2: Threaded | |
| Static Load: 160 lb | |

ADDITIONAL PRODUCT DETAILS

Loads indicated are for nVent CADDY Fasteners only.

Method of attachment to structure must be evaluated separately.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

nVent reserves the right to change specifications without notice.