

Tigerloop® OIL DEAERATORS

PRODUCT SHEET

Description:

Tigerloop® oil deaerators eliminate many common oil heating problems which prevent a burner from operating at peak performance by removing air from the system, delivering foam-free fuel to the nozzle and reducing issues caused by cold fuel — benefits which ultimately provide for cleaner, maximized combustion.

Located in North Ridgeville, Ohio, R.W. Beckett has produced liquid fuel burners for residential and commercial applications since 1937. Expanding into other areas of heating and air conditioning, Beckett products can now be found in over 50 million homes in North America and Canada. From Tank to Flame, trust Beckett products for years of safe, clean and reliable performance of our burners, controls, tank accessories, and service components.



The Most Advanced Oil Deaerator in the World

With its unmatched performance, Tigerloop® can handle capacities up to 50 GPH and is compatible with different heating fuels, depending on the model. The Tigerloop models are compatible with #1 and #2 heating oil. Catering to many needs, our oil deaerator is also a safe, economical, and environmentally friendly choice for all supply systems.

Beckett®

Tigerloop Advantages

- Removes air bubbles and foam from the fuel.
- Combines the benefit of a two-pipe fuel supply with a single-pipe.
- Reduces potential leak hazard by eliminating the return line to the tank.
- Extends filter life by reducing fuel flow through the filter.
- Preheats the fuel up to 25°F for better combustion.

Features

- Tigerloop Plus utilizes a M20 X 1.5 thread spin on filter.
- Select models cULus Listed
- Dual chamber design for maximum air removal.
- Tough zinc castings – Compatible with renewable fuels.
- Models available with integral filter.
- High capacity model for burners up to 50 gph.
- Cold temperature model for applications to -40°F.

Model	Description	Capacity	Filter
S220-20	Tigerloop TN – cULus Listed	29gph	N

S258-M	Tigerloop Plus – With M20 X 1.5 Spin-On Filter - cULus Listed	29gph	Y
--------	---	-------	---

Model	Description	Biodiesel Rating
S223-24	Flexible Fuel Line 1/4" MPT X 1/4" MPT – 24" Long	B100
S223-36	Flexible Fuel Line 1/4" MPT X 1/4" MPT – 36" Long	B100

S220-40	Replacement Fitting – 3/8" Inv Flare X 1/4" MPT	
---------	---	--

S220-20



S258-M



S223-36



USA: **R.W. Beckett Corporation**, 1-800-645-2876
Canada: **R.W. Beckett Canada Ltd**, 1-800-665-6972
Printed in USA 04/25 Form No. 66059-001

This document and all information contained herein are the sole property of the R.W. Beckett Corporation and cannot be reproduced or transmitted in whole or part without express written permission of the R.W. Beckett Corporation.

Beckett