



OVER 30 YEARS OF
LIGHTING EXCELLENCE



PRODUCT
CATALOG
2020-2021

TABLE OF CONTENTS

- | | | | |
|-----------|--------------------------|-----------|------------------------------|
| 2 | About Us | 3 | Filament Lamps |
| 8 | General Purpose Lamps | 12 | Reflectors & Spotlights |
| 15 | Commercial Lamps & Tubes | 19 | Downlights |
| 25 | Flush Mounts | 34 | Undercabinet Lighting |
| 44 | Step Lights | 47 | Commercial Fixtures |
| 50 | Exit & Emergency Lights | 53 | Freight / Warranty / Returns |

CNA Lighting is a division of **CNA International Enterprises Inc.**, a privately held company founded in 1988. CNA Lighting is dedicated in providing high quality lighting products and excellent prompt service to our customers across Canada. We are proud to be on the cutting leading edge of lighting technology and energy-saving advances. From our first halogen light bulb in 1988 to our latest LED fixture, we strive to provide you with the best value in our lighting industry. Currently, CNA offers our customers a wide range of LED light bulbs and fixtures, while maintaining a limited line of halogen, CFL, and HID products. Our customers include lighting distributors, electrical wholesalers, and lighting showrooms from all corners of Canada.

Year after year we introduce new and innovative lighting products to our market. We stand by our products by putting the CNA brand name on everything we sell. With well-stocked inventory in three warehouses in Canada, we are ready to serve you!

What's New?

We continually introduce new products every month. Please contact us if you are a customer and want to subscribe to our email list for new product introductions.

LED PRODUCTS

LED



FILAMENT

LAMPS

A15 Frosted



SKU# - Model
#940 - LED4.5WA15-FR 30K



Wattage (W)	4.5W
Voltage (V)	120V
Lumens (lm)	450 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W Incandescent
Base	E26 / Medium Base
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	A15 Frosted - All Glass
Length	8.7 cm (3-7/16")
Diameter	4.8 cm (1-7/8")

A19 Frosted



SKU# - Model
#941 - LED6.5WA19-FR 30K



Wattage (W)	6.5W
Voltage (V)	120V
Lumens (lm)	810 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium Base
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	A19 Frosted - All Glass
Length	10.4 cm (4-3/32")
Diameter	6 cm (2-3/8")

A19 Clear



SKU# - Model
#930 - LED6.5WA19-CL 30K



Wattage (W)	6.5W
Voltage (V)	120V
Lumens (lm)	810 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium Base
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	A19 Frosted - All Glass
Length	10.4 cm (4-3/32")
Diameter	6 cm (2-3/8")

B10 Chandelier Clear



SKU# - Model
#1011 - LED5.2WB10 27K
#1012 - LED5.2WB10 30K
#1013 - LED5.2WB10 40K
#1071 - LED5.2WB10 50K



Wattage (W)	5.2W
Voltage (V)	120VAC
Lumens (lm)	500 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E12 / Candelabra
Color temperature	2700K / 3000K / 4000K / 5000K
Shape	B10 / Chandelier / C35
Length	96 mm (3-3/4")
Diameter	35 mm (1-3/8")
Dimmable	Yes

G16 Clear



SKU# - Model
#976 - LED3.5WG16 30K



Wattage (W)	3.5W
Voltage (V)	120V
Lumens (lm)	350 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W Incandescent
Base	E12 / Candelabra
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	G16 – All Glass
Length	78 mm (3-1/16")
Diameter	44.5mm (1-3/4")

G16 Frosted



SKU# - Model
#1065 - LED3.5WG16-FR 30K



Wattage (W)	3.5W
Voltage (V)	120V
Lumens (lm)	300 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W Incandescent
Base	E12 / Candelabra
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	G16 – Frosted Glass
Length	78 mm (3-1/16")
Diameter	44.5mm (1-3/4")

G25 Clear



SKU# - Model
#814 - LED5WG25-CL 30K



Wattage (W)	5.0W
Voltage (V)	120V
Lumens (lm)	450 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	50W Incandescent
Base	E26 / Medium Base
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	G25 – All Glass
Length	117.2 mm (4-13/16")
Diameter	80 mm (3-1/8")

G25 Frosted



SKU# - Model
#1066 - LED5.5WG25-FR 30K



Wattage (W)	5.5W
Voltage (V)	120V
Lumens (lm)	500 lm
Life (Hrs)	5,000 Hrs
Incandescent Equivalent	50W Incandescent
Base	E26 / Medium Base
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	Damp Location
Shape	G25 – Frosted Glass
Length	117 mm (4-5/8")
Diameter	80 mm (3-1/8")

ST19 Vintage



SKU# - Model
#983 - LED5.5WST19 22K



Wattage (W)	5.5W
Voltage (V)	120VAC
Lumens (lm)	400 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium Base
Color temperature	2200K
Dimmable	Yes
Shape	ST19 (Vintage Edison Style)
Length	12.8 cm (5-1/32")
Diameter	5.9 cm (2-5/16")

ST19 Vintage



SKU# - Model
#984 - LED5.5WST19 27K
#1002 - LED5.5WST19 30K
#1088 - LED5.5WST19 40K



Wattage (W)	5.5W
Voltage (V)	120VAC
Lumens (lm)	550 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium Base
Color temperature	2700K / 3000K / 4000K
Dimmable	Yes
Shape	ST19 (Vintage Edison Style)
Length	12.8 cm (5-1/32")
Diameter	5.9 cm (2-5/16")

T10 Clear



SKU# - Model
#831 - LED 4.5WT10-FLDIM 30K



Wattage (W)	4.5W
Voltage (V)	110V-130V
Lumens (lm)	450 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W – 50W Incandescent
Base	E26 / Medium Base
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	T10
Length	12.5 cm (4-15/16")
Diameter	3.25 cm (1-1/4")

T25 Clear



SKU# - Model
#1050 - LED3.5WT25 30K



Wattage (W)	3.5W
Voltage (V)	120V
Lumens (lm)	350 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W Incandescent
Base	E12 / Candelabra
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	T25 – All Glass
Length	83 mm (3-1/4")
Diameter	25 mm (1")

T25 Frosted



SKU# - Model

#1064 - LED3.5WT25-FR 30K



T30 Vintage

SKU# - Model

#1046 - LED8WT30 27K



Wattage (W)	3.5W
Voltage (V)	120V
Lumens (lm)	300 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W Incandescent
Base	E12 / Candelabra
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	T25 – Frosted Glass
Length	83 mm (3-1/4")
Diameter	25 mm (1")

Wattage (W)	8W
Voltage (V)	120V
Lumens (lm)	750 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium Base
Color temperature	2700K
Dimmable	Yes
Environmental Rating	Enclosed Fixtures
Shape	T30
Length	295 mm (11-5/8")
Diameter	30mm (1-3/16")

LED PRODUCTS

**GENERAL
PURPOSE
LAMPS**



A19 5-PACK



SKU# - Model

- #959 - LED9WA19NSD 30K-5PK
- #900 - LED9WA19NDS 40K-5PK



Wattage (W)	9W
Voltage (V)	120V
Lumens (lm)	800 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium
Color temperature	3000K / 4000K
Dimmable	No
Beam angle (degrees)	240°
Dimensions	109mm x 60mm
Box Quantity	5-Pack Box
Case Quantity	20 Boxes (100 bulbs) per Case
Environmental Rating	Not for Enclosed Fixtures

A19 - Enclosed & Dim



SKU# - Model

- #947 - LED9WA19-EC 27K
- #948 - LED9WA19-EC 30K
- #949 - LED9WA19-EC 40K
- #1072 - LED9WA19-EC 50K



Wattage (W)	9W
Voltage (V)	120V
Lumens (lm)	800 lm
Life (Hrs)	25,000 Hrs
Incandescent Equivalent	60W Incandescent
Base	E26 / Medium
Color temperature	2700K / 3000K / 4000K / 5000K
Dimmable	Yes
Beam angle (degrees)	300°
Energy Star	Yes
Dimensions	110mm x 60mm
Environmental Rating	Enclosed Fixtures

A19 - 14W



SKU# - Model

- #1034 - LED14WA19 27K
- #1032 - LED14WA19 30K
- #1033 - LED14WA19 40K



Wattage (W)	14W
Voltage (V)	120V
Lumens (lm)	1600 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	100W Incandescent
Base	E26 / Medium
Color temperature	2700K / 3000K / 4000K
Dimmable	Yes
Beam angle (degrees)	300°
Energy Star	Yes
Dimensions	112mm x 60mm
Environmental Rating	Not for Enclosed Fixtures

A21 - High Output



SKU# - Model

- #1058 - LED24WA21-EC 30K
- #1059 - LED24WA21-EC 40K



Wattage (W)	24W
Voltage (V)	120V
Lumens (lm)	2600 lm
Life (Hrs)	25,000 Hrs
Incandescent Equivalent	200W Incandescent
Metal Halide Equivalent	MH70W / MH100W
Base	E26 (Medium)
Color temperature	3000K / 4000K
Dimmable	Yes
Beam angle (degrees)	230°
Environmental Rating	Enclosed Fixtures
Dimensions	126 mm x 70 mm
Shape	A-Shape

G25 Non-Dim



SKU# - Model
#993 - LED5WG25 27K



Wattage (W)	5W
Voltage (V)	120V
Lumens (lm)	350 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	40W Incandescent
Base	E26 / Medium Base
Color temperature	2700K
Dimmability	Non-Dimmable
Environmental Rating	Damp Location
Shape	G25 Frosted
Length	120.1 mm (4-3/4")
Diameter	79.9 mm (3-1/8")

E11 Mini-Can



SKU# - Model
#899 - LED3WE11-DIM 3000K



Wattage (W)	3W
Voltage (V)	120VAC
Lumens (lm)	300 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	50W Halogen
Base	E11 / Minican
Color temperature	3000K
Dimmable	Yes
Environmental Rating	Not for use in enclosed fixtures
Shape	JD / Peanut
Length	49.5 mm (1-15/16")
Diameter	17.5 mm (11/16")

G4 Bi-pin



SKU# - Model
#929 - LED1.5WG4SM 30K



Wattage (W)	1.5W
Voltage (V)	12VAC / 12VDC
Lumens (lm)	150 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	20W Halogen
Base	G4
Color temperature	3000K
Dimmability	Depends on transformer and/or dimmer
Shape	JC / Peanut
Length	32 mm (1-1/4")
Width	12.5 mm (1/2")
Height	9 mm (11/32")

G9 3W



SKU# - Model
#878 - LED3WG9 30K
#879 - LED3WG9 41K
#1080 - LED3WG9 50K



Wattage (W)	3W
Voltage (V)	120VAC
Lumens (lm)	300 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	40W Halogen
Base	G9
Color temperature	3000K / 4100K / 5000K
Dimmable	Yes
Environmental Rating	Not for Enclosed Fixtures
Shape	JCD / Peanut
Length	4.8 cm (1-7/8")
Diameter	1.75 cm (11/16")

G9 5W



SKU# - Model

- #866 - LED5WG9-DIM 30K
- #1020 - LED5WG9-DIM 40K



Wattage (W)	5W
Voltage (V)	120VAC
Lumens (lm)	500 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	60W Halogen
Base	G9
Color temperature	3000K / 4000K
Dimmable	Yes
Environmental Rating	Not for Enclosed Fixtures
Shape	JCD / Peanut
Length	54 mm (2-1/8")
Diameter	19.5 mm (3/4")

J78 Linear



SKU# - Model

- #956 - LED6WJ78 30K
- #957 - LED6WJ78 41K



Wattage (W)	6W
Voltage (V)	120VAC
Lumens (lm)	600 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	100W Halogen
Base	R7s
Color temperature	3000K / 4000K
Dimmable	Yes – with Lutron DVELV-300P / DVCL-153P
Shape	J Type Linear 78mm (Q100T3/CL/78m)
Length	78 mm (3-1/16")
Diameter	30 mm (1-3/16")

J118 Linear



SKU# - Model

- #981 - LED14WJ118 30K



Wattage (W)	14W
Voltage (V)	120VAC
Lumens (lm)	1400 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	150W - 200W
Base	R7s
Color temperature	3000K
Dimmable	Yes – with Lutron DVELV-300P / DVCL-153P
Shape	J-Type Linear 118 QT3 / CL / 118
Length	118 mm (4-5/8")
Diameter	30 mm (1-5/32")

E26 TO E12



SKU# - Model

- #887 - E26 to E12

E26 (Male) to E12 (Female) Base Adapter

GU24 TO E26



SKU# - Model

- #886 - GU24 to E26

GU24 (Male) to E26 (Female) Base Adapter

LED PRODUCTS

REFLECTORS



&

SPOTLIGHTS

GU10



SKU# - Model

- #933 - LED6.5WGU10-CB 27K
- #934 - LED6.5WGU10-CB 30K
- #951 - LED6.5WGU10-CB 40K




Wattage (W)	6.5W
Voltage (V)	120VAC
Lumens (lm)	500 lm
Life (Hrs)	25,000 Hrs
Halogen Equivalent	50W Halogen
Base	GU10
Color temperature	2700K / 3000K / 4000K
Beam angle (degrees)	40° / 35° (4000K)
Environmental Rating	Damp Location & Recessed
Length	2-1/8" / 54 mm
Diameter	1-31/32" / 50 mm
Shape	JCDR / MR16 / GU10

MR16



SKU# - Model

- #858 - LED7WMR16-CB 27K
- #833 - LED7WMR16-CB 30K
- #914 - LED7WMR16-CB 40K



Wattage (W)	6.5W
Voltage (V)	12VAC / 12VDC
Lumens (lm)	500 lm
Life (Hrs)	25,000 Hrs
Halogen Equivalent	50W Halogen
Base	GU5.3
Color temperature	2700K / 3000K / 4000K
Beam angle (degrees)	35°
Dimmable	Yes
Length	1-7/8" / 48.2 mm
Diameter	1-31/32" / 50 mm
Shape	MR16

Par16 Short



SKU# - Model

- #1028 - LED6WPar16-SRT 30K
- #1029 - LED6WPar16-SRT 40K



Wattage (W)	6W
Voltage (V)	120VAC
Lumens (lm)	500 lm
Life (Hrs)	15,000 Hrs
Incandescent Equivalent	50W Halogen
Base	E26 Medium
Color temperature	3000K / 4000K
Beam angle (degrees)	40°
CIR	≥ 80
Length	2-1/4" / 57 mm
Diameter	1-31/32" / 50 mm
Shape	Par16 / MR16 / HR16 / JDR

Par20



SKU# - Model

- #1001 - LED7WPar20-CB 30K
- #922 - LED7WPar20-CB 40K



Wattage (W)	7W
Voltage (V)	120VAC
Lumens (lm)	500 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	50W Incandescent
Base	E26
Color temperature	3000K / 4000K
Beam angle (degrees)	40°
CRI	80
Length	3-5/32 inches / 80 mm
Diameter	2-1/2 inches / 63 mm
Shape	Par20 Shape

Par30 Short Neck



SKU# - Model
 #1078 - LED10WPar30S-CB 30K
 #1077 - LED10WPar30S-CB 40K



Par30 Long Neck



SKU# - Model
 #1030 - LED10WPar30L-CB 30K
 #1076 - LED10WPar30L-CB 40K



Wattage (W)	10W
Voltage (V)	120VAC
Lumens (lm)	800 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	75W Halogen
Base	E26
Color temperature	3000 / 4000K
Beam angle (degrees)	40°
CRI	83
Length	3-1/4 inches / 82 mm
Diameter	3-5/8 inches / 92 mm
Shape	Par30S Shape

Wattage (W)	10W
Voltage (V)	120VAC
Lumens (lm)	800 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	75W Halogen
Base	E26
Color temperature	3000K / 4000K
Beam angle (degrees)	40°
CRI	83
Length	4-15/16 inches / 109.7 mm
Diameter	3-5/8 inches / 92.1 mm
Shape	Par30L Shape

Par38



SKU# - Model
 #1031 - LED15WPar38-CB 30K



BR30



SKU# - Model
 #1010 - LED9WBR30 2700K



Wattage (W)	15W
Voltage (V)	120VAC
Lumens (lm)	1200 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	90W Halogen
Base	E26
Color temperature	3000K
Beam angle (degrees)	40°
CRI	83
Length	5 inches / 128.5 mm
Diameter	4-9/16 inches / 115.7 mm
Shape	Par38 Shape

Wattage (W)	9W
Voltage (V)	120VAC
Lumens (lm)	800 lm
Life (Hrs)	15,000 Hrs
Halogen Equivalent	65W Incandescent
Base	E26
Color temperature	2700K
Beam angle (degrees)	110°
CRI	80
Length	5-1/4 inches / 133 mm
Diameter	3-3/4 inches / 95 mm
Shape	BR30 Shape

LED PRODUCTS

COMMERCIAL LAMPS & TUBES



CFL 13W 2-pin Replacement



SKU# - Model

#979 - LED6WPL13-HY 30K

#980 - LED6WPL13-HY 40K



CFL 13W 4-pin Replacement



SKU# - Model

#1023 - LED7WPLC13-HY 30K

#916 - LED7WPLC13-HY 40K



Wattage (W)	6W
CFL PLC Equivalent	2-Pin PL13 / PL-13
Color Temperature	3000K / 4000K
Voltage (V)	120-277V
Ballast Compatible	HYBRID – Ballast Compatible & Ballast Bypass 110V-277V
Light Output (lm)	600 lm
Rated Life	40,000 Hrs.
Beam angle (degrees)	360° - Omni
Dimmable	No
Power Factor	0.9
CRI	80
Safety Certification	cUL
Operating Temperature	-20°C to +45°C
Environmental Rating	Not for Enclosed Fixtures
Length	6-15/16 inches / 176 mm
Width	1-1/4 inches / 31 mm
Base	GX23
Carton Quantity	100 Pieces Per Carton
Warranty	5 Years

Note: This lamp has been tested to be compatible with the vast majority of models among major ballast manufacturers. As such, there still may be a chance your ballast will not work with this lamp. A trial test is always recommended.

Wattage (W)	7W
CFL PLC Equivalent	4-Pin PLC13 / PLC-13
Color Temperature	3000K / 4000K
Voltage (V)	120V-277V
Ballast Compatible	HYBRID – Ballast Compatible & Ballast Bypass 110V-277V
Light Output (lm)	750 lm
Rated Life	40,000 Hrs.
Beam angle (degrees)	360° - Omni
Dimmable	No
Power Factor	0.9
CRI	80
Safety Certification	cUL
Operating Temperature	-20°C to +45°C
Environmental Rating	Not for Enclosed Fixtures
Length	5-1/32 inches / 128mm
Width	1-7/16 inches / 37 mm
Base	G24q Universal 4-Pin
Carton Quantity	50 / 200 Pieces Per Carton
Warranty	5 Years

Note: This lamp has been tested to be compatible with the vast majority of models among major ballast manufacturers. As such, there still may be a chance your ballast will not work with this lamp. A trial test is always recommended.

CFL 26W/32W/42W Replacement



SKU# - Model

#917 - LED11WPL26/32/42-HY-30K

#1000 - LED11WPL26/32/42-HY-40K



T8 Hybrid



SKU# - Model

#1014 - LED14WT8-HY 40K (1800LM)

#1015 - LED14WT8-HY 50K (1800LM)

Wattage (W)	11W
CFL PLC Equivalent	4-Pin PLC 26/32/42 4-Pin PLT 26/32/42
Color Temperature	3000K / 4000K
Voltage (V)	120V-277V
Operation	HYBRID – Ballast Compatible & Ballast Bypass 110V-277V
Light Output (lm)	1300 lm
Rated Life	40,000 Hrs.
Beam angle (degrees)	360° - Omni
Dimmable	No
Power Factor	0.9
CRI	80
Safety Certification	cUL
Operating Temperature	-20°C to +45°C
Environmental Rating	Not for Enclosed Fixtures
Length	6-7/16 inches / 165 mm
Width	1-7/16 inches / 37 mm
Base	G24q / GX24q Universal 4-Pin
Carton Quantity	50 / 200 Pieces Per Carton
Warranty	5 Years

Note: This lamp has been tested to be compatible with the vast majority of models among major ballast manufacturers. As such, there still may be a chance your ballast will not work with this lamp. A trial test is always recommended.

Operation	1 - Ballast Compatible 2 - Ballast Bypass 110-130V (Double Ended)
Rated Power (W)	14 Watts
Colour Temperatures Available	4000K , 5000K
Power Factor	0.99
Total Harmonic Distortion (THD)	16%
Socket Compatibility	Shunted & Non-Shunted
Light Output	1800lm
Efficacy	137 lm/W
Colour Rendering Index (CRI)	≥ 80
Rated Life	50,000 Hrs.
Nominal Length	4 Feet
Diffuser Material	Glass (Non-Yellowing, Rigid)
Beam Angle	150°
Certifications	DLC / cUL / cUL Classified / NSF
Classification Type	DLC & cUL Type A & Type B
Operating Voltage	120VAC - 277VAC
Carton Quantity	25 pieces / box
Warranty	5 Years

T8 - 347V



SKU# - Model
#852 - LED14WT8-347V 40K



T5HO



SKU# - Model
#869 - LED25WT5 840 COMP (3500lm)
#955 - LED25WT5 850 COMP (3500lm)



Operation	Ballast Bypass (Double Ended)
Voltage (V)	347VAC
Rated Power (W)	14 W
Color Temperature	4000K
Power Factor	0.9048
THD	20%
Ignition Time	≤ 1.0 second
Light Output	1800 lm
Efficacy	128.6 lm/W
CRI	85.1
Rated Life	50,000 Hrs.
Nominal Length	4 Feet
Diffuser Material	Glass
Beam Angle	230°
Certifications	cULus / DLC / NSF
Warranty	5 Years

Electronic Ballast Compatibility	Instant Start & Program Start
Rated Power (W)	28 W (High Ballast Factor)
Colour Temperature	4000K / 5000K
Direct Replacement For	F54/T5/HO
Total Harmonic Distortion (THD)	20%
Power Factor	0.9
Light Output	3500 lm
Efficacy (lm/W)	125 lm/W
Colour Rendering Index (CRI)	80
Rated Life (Hours)	50, 000 Hrs.
Beam Angle	185°
Nominal Length	4 Feet
Diffuser Material	Glass (Non-Yellowing - Rigid)
Certifications	DLC, NSF, cULus
Classification Type	Replacement Lamps (plug and play) UL Type A
Carton Quantity	25 pieces / box

LED PRODUCTS

DOWNLIGHTS



4" Round Panel



SKU# - Model
#1007 - LED DP4-3WH



Wattage (W)	9W
Trim Colour	White
Colour Temperature	3000K
Voltage	120VAC
Light Output	550 lm
Rated Life	50,000 Hrs.
Base Type	Hardwire
Dimmable	Yes
Certifications	cETLus, Type IC Rated
CRI	80
Beam Angle	120°
Operating Temperature	-20° to 45°
Environmental Rating	Damp Location, Type IC Rated
Hole Saw Cut-Out	4-1/4" Diameter
Carton Quantity	18 per Carton
Warranty	5 Years

6" Round Panel



SKU# - Model
#1039 - LED DP6-345K-WH



Wattage (W)	14W
Trim Colour	White
Colour Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Light Output	1000 lm
Rated Life	50,000 Hrs.
Base Type	Hardwire
Dimmable	Yes
Certifications	cETLus
CRI	80
Beam Angle	120°
Operating Temperature	-20° to 45°
Environmental Rating	Wet Location, Type IC Rated
Hole Saw Cut-Out	6-1/4" Diameter
Carton Quantity	18 per Carton
Warranty	5 Years

DP Black Trims



SKU# - Model
#1042 - LEDDP-4-BK-Trim
#1043 - LEDDP-6-BK-Trim

Description	4" Black Trim for #1007 LED DP4-3WH 6" Black Trim for #1039 LED DP6-345K-WH
-------------	--

Rough-in Plates



SKU# - Model
#1079 - RIP-35
#885 - RIP-4
#888 - RIP-6

Description	3.5" Rough-In Plate 4" Rough-In Plate 6" Rough-In Plate
-------------	---

4" Gimbal



SKU# - Model
 #1089 - LED DGIM-4-3CCT-BK
 #985 - LED DGIM-4-3CCT-WT



3.5" Eyeball



SKU# - Model
 #1037 - LEDDG-4-345K-BK
 #1038 - LEDDG-4-345K-WH



Wattage (W)	9W
Trim Colour	White or Black
Gimbal Head	Yes
Colour Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Light Output	600 lm
Rated Life	50,000 Hrs.
Base Type	Hardwire
Dimmable	Yes
Certifications	cETLus, Type IC Rated, Airtight
CRI	> 80
Beam Angle	40°
Environmental Rating	Damp Location
Height	1-9/16" / 40 mm
Diameter	5-3/16" / 131 mm
Driver Height	1-3/8" / 35 mm
Hole Saw Cut-Out	3.5" – 4" Diameter
Carton Quantity	30 per Carton
Warranty	5 Years
IES Photometric Files	Available on website

Wattage (W)	12W
Trim Colour	White or Black
Gimbal Head	Yes
Colour Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Light Output	800 lm
Rated Life	50,000 Hrs.
Base Type	Hardwire
Dimmable	Yes
Certifications	cETLus
CRI	≥ 90
Beam Angle	40°
Environmental Rating	Wet Location, Type IC Rated
Height	2-1/8" / 15.4 cm
Diameter	4-7/8" / 12.4 cm
Driver Height	1-3/8" / 36 mm
Hole Saw Cut-Out	3-3/4" Diameter
Carton Quantity	18 per Carton
Warranty	5 Years

3.5" Eyeball



SKU# - Model
 #1040 - LEDRG-4-345K-BK
 #1041 - LEDRG-4-345K-WH



4" Floating Gimbal



SKU# - Model
 #1097 - TL4-3CCT-WH
 #1098 - TL4-3CCT-BK



Wattage (W)	12W
Trim Colour	White or Black
Gimbal Head	Yes
Colour Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Light Output	705 lm / 845 lm / 840 lm
Rated Life	50,000 Hrs.
Base Type	Hardwire
Dimmable	Yes
Certifications	cETLus
CRI	≥ 90
Beam Angle	40°
Environmental Rating	Wet Location, Type IC Rated
Height	3-3/8" / 8.5 cm
Diameter	4-11/32" / 11 cm
Driver Height	1-3/8" / 3.6 cm
Hole Saw Cut-Out	3-3/4" Diameter
Carton Quantity	18 per Carton
Warranty	5 Years
IES Photometric Files	Available on website

Wattage (W)	9W
Colour Temperature	Colour Selectable 3000K / 4000K / 5000K
Voltage (V)	120VAC
Light Output	900 lm
Rated Life	50,000 Hrs.
Base Type	Hardwire
Efficiency	100 lm/W
Dimmable	Yes
Certifications	cETLus, Type IC Rated, Airtight
CRI	> 80
Gimball Articulation	90° Tilt 360° Rotation
Height (Excluding Driver)	1.38 inches / 36 mm
Diameter	4.88 inches / 125 mm
Driver Height	1.38 inches / 36 mm
Beam Angle	30°
Environmental Rating	Wet Location
Hole Size Cutout	4"
Carton Quantity	40 per Carton
Warranty	5 Years

4" Retrofit Kit



SKU# - Model
#1049 - LE9WRT4-3CCT



Wattage (W)	9W
Voltage (V)	120VAC
Lumens (lm)	650 lm
Life (Hrs)	50,000 Hrs
Colour Temperatures	3000K / 4000K / 5000K
Base	E26 / Hardwire
Dimmable	Yes
CRI	80
Energy Efficiency	72.2
Certification	cUL Classified
Height (Excluding Base)	2-1/2" / 64 mm
Diameter	5-1/2" / 139 mm
Fixture Type	4" Pot Light Downlight Retrofit
Environmental Rating	Wet Location
Carton Quantity	20 per Carton
Warranty	5 Years

5/6" Retrofit Kit



SKU# - Model
#1051 - LED12WRT5/6-3CCT



Wattage (W)	12W
Voltage (V)	120VAC
Lumens (lm)	950 lm
Life (Hrs)	50,000 Hrs
Colour Temperatures	3000K / 4000K / 5000K
Base	E26 / Hardwire
Dimmable	Yes
CRI	80
Energy Efficiency	79.2
Certification	cUL Classified
Height (Excluding Base)	2-7/8" / 74 mm
Diameter	7-5/16" / 186 mm
Fixture Type	5"/6" Pot Light Downlight Retrofit
Environmental Rating	Wet Location
Carton Quantity	20 per Carton
Warranty	5 Years

6" Commercial Downlight



SKU# - Model
#1056 - LED RT6-3X3CCT




8" Goof Ring



SKU# - Model
#1057 - LED RT6-GOOF8

Inside diameter	6.25"
Outside diameter	10.5"

Large Vapour Barrier



SKU# - Model
#1024 - G-59 Vapour Barrier

Flange Dimensions	29" x 22-3/4"
Recess Dimensions	22-1/4" x 14" x 8-3/4"
Rib-reinforced	Yes
Use	For all sizes pot lights

Small Vapour Barrier



SKU# - Model
#1025 - VB02 Vapour Barrier

Flange Dimensions	24" x 20"
Recess Dimensions	20" x 8" x 3-1/2"
Rib-reinforced	No
Use	For Slim LED Lights

Wattage (W)	7W / 10W / 18W
Lumens (lm)	700 lm / 1000 lm / 1500 lm
Colour Temperatures	3000K / 3500K / 4000K
Voltage (V)	120VAC – 277VAC
Life (Hrs)	50,000 Hrs
Base	Hardwire – 24" Conduit – 3/8" Snap-In Fitting
Dimmable	Yes – 0-10V – down to 5%
CRI	> 90
Energy Efficiency	83.3 – 100
Certification	cUL
Height (Excluding Base)	5-3/16" / 131 mm
Diameter	8-1/4" / 210 mm
Hole Size Cutout	6-1/4" / 158.75 mm
Environmental Rating	Wet Location, Type IC Rated
Operating Temperature	-30°C to 40°C
Carton Quantity	4 per Carton
Warranty	5 Years
Optional Accessory	#1057 – LED RT6-GOOF8 (Goof Ring for 8" Hole Size)

LED PRODUCTS

FLUSH



MOUNTS

6" Motion Sensor Disk



SKU# - Model
#978 - LED CL-6-PIR



8" Motion Sensor Disk



SKU# - Model
#1055 - LED CL-8-PIR



Wattage (W)	10W
Voltage (V)	120VAC
Lumens (lm)	600 lm
Rated Life (Hrs):	50,000 Hrs
Finish	White
Diffuser Type	Acrylic
CRI	> 80
Energy Efficiency	60 lm/W
Power Factor	0.81
Dimensions	6-7/8" x 1"
Color temperature	3000K
Safety Certification	cETLus
PIR Sensor	Yes
Auto Shut-off	Yes – After 30 seconds
Carton Quantity	20 per Carton
Warranty	5 Years

Wattage (W)	15W
Voltage (V)	120VAC
Lumens (lm)	900 lm
Rated Life (Hrs):	50,000 Hrs
Finish	White
Diffuser Type	Acrylic
CRI	> 80
Energy Efficiency	60 lm/W
Power Factor	0.81
Dimensions	8" x 1"
Color temperature	3000K
Safety Certification	cETLus
PIR Sensor	Yes
Auto Shut-off	Yes – After 30 seconds
Carton Quantity	20 per Carton
Warranty	5 Years

11" Mushroom



SKU# - Model
#1016 - LED CL-11-3CCT



Wattage (W)	15W
Voltage (V)	120VAC
Lumens (lm)	1050 lm
Rated Life (Hrs):	50,000 Hrs
Finish	White
Diffuser Type	Acrylic
Dimmable	Yes
CRI	80
Energy Efficiency	70 lm/W
Dimensions	11" x 3"
Color Changing Temperatures	3000K / 4000K / 5000K
Safety Certifications	cETLus
Carton Quantity	8 per Carton
Warranty	5 Years

14" Mushroom



SKU# - Model
#1044 - LED CL-14-3CCT



Wattage (W)	20W
Voltage (V)	120VAC
Lumens (lm)	1600 lm
Rated Life (Hrs):	50,000 Hrs
Finish	White
Diffuser Type	Acrylic
Dimmable	Yes
CRI	80
Energy Efficiency	80 lm/W
Dimensions	14" x 3"
Color Changing Temperatures	3000K / 4000K / 5000K
Safety Certifications	cETLus
Environmental Rating	Damp Location
Carton Quantity	6 per Carton
Warranty	5 Years

12" Twin Ring - Brushed Nickel



SKU# - Model
#794 - LED CL-2R-12-3CCT



Wattage (W)	15W
Voltage (V)	120VAC
Delivered Light Output (lm)	1100 lm
L70 Rated Life (Hrs)	50,000 Hrs
Finish	Brushed Nickel
Diffuser Type	Acrylic
Dimmable	Yes
CRI	80 lm/W
Energy Efficiency	70
Power Factor	0.99
Dimensions	12" x 3"
Color Changing Temperatures	3000K / 4000K / 5000K
Safety Certification	cETLus
Energy Star	Yes
Carton Quantity	6 per Carton
Warranty	5 Years

12" Twin Ring - Black



SKU# - Model
#1074 - LED CL-2R-12-3CCT-BK



Wattage (W)	15W
Voltage (V)	120VAC
Lumens (lm)	1100 lm
Rated Life (Hrs):	50,000 Hrs
Finish	Matte Black
Diffuser Type	White Acrylic
Dimmable	Yes
CRI	80
Energy Efficiency	80 lm/W
Power Factor	0.99
Dimensions	12" x 3"
Color Changing Temperatures	3000K / 4000K / 5000K
Safety Certifications	cETLus
Energy Star	Yes
Carton Quantity	6 per Carton
Warranty	5 Years

16" Twin Ring - Brushed Nickel



SKU# - Model
#1045 - LED CL-2R-16-3CCT



Wattage (W)	26W
Voltage (V)	120VAC
Lumens (lm)	2100 lm
Rated Life (Hrs):	50,000 Hrs
Finish	Brushed Nickel
Diffuser Type	Acrylic
Dimmable	Yes
CRI	80
Energy Efficiency	80.8 lm/W
Environmental Rating	Damp Location
Dimensions	16" x 3"
Color Changing Temperatures	3000K / 4000K / 5000K
Safety Certifications	cETLus
Energy Star	Yes
Carton Quantity	5 per Carton
Warranty	5 Years

16" Twin Ring - Black



SKU# - Model
#1085 - LED CL-2R-16-3CCT BK



Wattage (W)	26W
Voltage (V)	120VAC
Lumens (lm)	2100 lm
Rated Life (Hrs):	50,000 Hrs
Finish	Matte Black
Diffuser Type	White Acrylic
Dimmable	Yes
CRI	80
Energy Efficiency	80.8 lm/W
Power Factor	0.99
Dimensions	16" x 3"
Color Changing Temperatures	3000K / 4000K / 5000K
Safety Certifications	cETLus
Energy Star	Yes
Carton Quantity	5 per Carton
Warranty	5 Years

4" Slim Downlight



SKU# - Model
#1081 - DPS-4-30K



DPS Trim Black



SKU# - Model
#1082 - DPS-4-BK-TRIM

Description 4" Black Trim

DPS Trim Brushed Nickel



SKU# - Model
#1083 - DPS-4-BN-TRIM

Description 4" Brushed Nickel Trim

Wattage (W)	9W
Voltage (V)	120VAC
Rated Lumens (lm)	700 lm
L70 Rated Life (Hrs):	50,000 Hrs
Base	Hardwire (E26 Optional with Accessory Kit)
Color Temperature	3000K
Housing Material	Aluminum
Trim Colour Included	White
Trim Mounting	Magnetic – Interchangeable
Dimmable	Yes
CRI	80
Energy Efficiency	77.7 lm/W
Beam Angle	110°
Mounting	4" Octagonal J-BOX or 4" Recessed Housing with Optional Accessory
Environmental Rating	Wet Location, Type IC Rated
Safety Certification	cETLus
Dimensions	4-7/8"D x 1-1/8"H
Carton Quantity	24 per Carton
Warranty	5 Years

DPS Retrofit Accessory



SKU# - Model
#1084 - DPS-ACC

Description	Accessory Kit for 4" Recessed Housing Mounting Option
-------------	---

5" Slim Flushmount



SKU# - Model
#1053 - LED DS-5-3CCT



Wattage (W)	10W
Voltage (V)	120VAC
Color Temperatures	3000K / 4000K / 5000K
Rated Lumens (lm)	600 lm / 680 lm / 620 lm
Rated Life (Hrs)	50,000 Hrs
Finish	White
Diffuser Type	Acrylic – Low Glare
Dimmable	Yes – TRIAC / ELV
CRI	≥ 80
Energy Efficiency	60 lm/W
Base	Hardwire – 4" J-Box
Environmental Rating	Wet Location
Safety Certification	cETLus
Diameter	5-5/16" / 135 mm
Height	5/8" / 17 mm
Carton Quantity	20 per Carton
Warranty	5 Years
IES Photometric Files	Available on website

7" Slim Flushmount



SKU# - Model
#1054 - LED DS-7-3CCT



Wattage (W)	15W
Voltage (V)	120VAC
Color Temperatures	3000K / 4000K / 5000K
Rated Lumens (lm)	900 lm
Rated Life (Hrs)	50,000 Hrs
Finish	White
Diffuser Type	Acrylic – Low Glare
Dimmable	Yes – TRIAC / ELV
CRI	≥ 80
Energy Efficiency	60 lm/W
Base	Hardwire – 4" J-Box
Environmental Rating	Wet Location
Safety Certification	cETLus
Diameter	7-7/8" / 202 mm
Height	5/8" / 17 mm
Carton Quantity	20 per Carton
Warranty	5 Years

DS-5 Trim - Black



SKU# - Model
#1021 - LED DS-5-Black Trim

DS-7 Trim - Black



SKU# - Model
#1022 - LED DS-7-Black Trim

12” Slim Flushmount



SKU# - Model
#982 - LED DS-12-3CCT-D



Wattage (W)	23W
Voltage (V)	120VAC
Color Temperatures	3000K / 4000K / 5000K
Rated Lumens (lm)	1480 lm / 1780 lm / 1510 lm
L70 Rated Life (Hrs)	50,000 Hrs
Finish	White
Diffuser Type	Acrylic – Low Glare
Dimmable	Yes – TRIAC / ELV
CRI	≥ 80
Energy Efficiency	65.2 lm/W
Base	Hardwire – 4” J-Box
Environmental Rating	Wet Location
Safety Certification	cETLus
Housing Material	Die Cast
Dimensions	12-1/8” D x 31/32” H
Carton Quantity	6 per Carton
Warranty	5 Years
IES Photometric Files	Available on website

DS-12 Trim - Black



SKU# - Model
#1048 - LED DS-12-BK-Trim

4" Square Slim Flushmount



SKU# - Model
#952 - LED DSQ-4-30K



6" Square Slim Flushmount



SKU# - Model
#953 - LED DSQ-6-30K



Wattage (W)	10W
Voltage (V)	120VAC
Rated Lumens (lm)	600 lm
L70 Rated Life (Hrs)	50,000 Hrs
Finish	White
Diffuser Type	Acrylic – Low Glare
Dimmable	Yes – TRIAC / ELV
CRI	≥ 80
Energy Efficiency	60 lm/W
Base	Hardwire – 4" J-BOX
Enrronmental Rating	Wet Location
Color temperature	3000K
Safety Certification	cETLus
Energy Star	Yes
Dimensions	4-3/8"D x 5/8"H
Carton Quantity	20 per Carton
Warranty	5 Years

Wattage (W)	15W
Voltage (V)	120VAC
Rated Lumens (lm)	900 lm
L70 Rated Life (Hrs)	50,000 Hrs
Finish	White
Diffuser Type	Acrylic – Low Glare
Dimmable	Yes – TRIAC / ELV
CRI	≥ 80
Energy Efficiency	60 lm/W
Base	Hardwire – 4" J-Box
Enrronmental Rating	Wet Location
Color temperature	3000K
Safety Certification	cETLus
Energy Star	Yes
Dimensions	6-1/4" D x 5/8" H
Carton Quantity	20 per Carton
Warranty	5 Years

LED PRODUCTS

UNDERCABINET



LIGHTING

11" Undercabinet Strip 120V



SKU# - Model
#1091 - T5Bar-11-3CCT



24" Undercabinet Strip 120V



SKU# - Model
#1092 - T5Bar-24-3CCT



Selectable Color Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Wattage	5 W
Light Output	420 lm
Efficiency	84 lm/W
Rated Life	50,000 Hrs
CRI	80
Max Linkable	10 Fixtures
Nominal Length	1 Foot
Length	11-1/2"
Width	1/2"
Height	5/8"
Dimmable	Dimmable
Safety Certification	cETLus
Carton Quantity	12
Warranty	5 years

Selectable Color Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Wattage	9 W
Light Output	760 lm
Efficiency	84.4 lm/W
Rated Life	50,000 Hrs
CRI	80
Max Linkable	10 Fixtures
Nominal Length	2 Feet
Length	22-5/8"
Width	1/2"
Height	5/8"
Dimmable	Dimmable
Safety Certification	cETLus
Carton Quantity	12
Warranty	5 years

Junction Box



SKU# - Model
#1095 - T5Bar-Jbox



12" Link Cable



SKU# - Model
#1090 - T5Bar-Link12



Description	Junction Box with On/Off Switch
-------------	---------------------------------

Description	12-inch Flexible Link Cable
-------------	-----------------------------

36" Undercabinet Strip 120V



SKU# - Model
#1093 - T5Bar-36-3CCT



48" Undercabinet Strip 120V



SKU# - Model
#1094 - T5Bar-48-3CCT



Selectable Color Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Wattage	14 W
Light Output	1120 lm
Efficiency	80 lm/W
Rated Life	50,000 Hrs
CRI	80
Max Linkable	10 Fixtures
Nominal Length	3 Feet
Length	34-1/2"
Width	1/2"
Height	5/8"
Dimmable	Dimmable
Safety Certification	cETLus
Carton Quantity	12
Warranty	5 years

Selectable Color Temperature	3000K / 4000K / 5000K
Voltage	120VAC
Wattage	18 W
Light Output	1530 lm
Efficiency	85 lm/W
Rated Life	50,000 Hrs
CRI	80
Max Linkable	10 Fixtures
Nominal Length	4 Feet
Length	46-1/4"
Width	1/2"
Height	5/8"
Dimmable	Dimmable
Safety Certification	cETLus
Carton Quantity	12
Warranty	5 years

6' Cord w/ Plug



SKU# - Model
#1096 - T5Bar-Plug



Description	6FT Length AC Power Cord Plug
-------------	-------------------------------

Panel Light



SKU# - Model
#904 - LED6WPANEL 30K



Wattage	6W
Colour Temperature	3000K
Voltage	12VDC
Light Output	450lm
Rated Life	50,000 Hrs.
Finish	Aluminum
Dimmable	Yes
Safety Certification	cUL
Length	7-9/16" / 192 mm
Width	5-7/16" / 113 mm
Surface Mount Height	3/8" / 9.5 mm
Carton Quantity	50 Pieces Per Carton
Warranty	3 Years

Puck Light



SKU# - Model
#902 - LED3WPUCK 30K



Wattage	3W
Colour Temperature	3000K
Voltage	12VDC
Light Output	280 lm (3000K)
Rated Life	50,000 Hrs.
Finish	Aluminum
Dimmable	Yes
Safety Certification	cUL
Diameter	2-7/16" / 62 mm
Surface Mount Height	1/2" / 12 mm
Recessed Cutout Diameter	2-1/8" / 55 mm
Carton Quantity	100 Pieces Per Carton
Warranty	3 Years

Surface Mount Ring



SKU# - Model
#905 - LED-SMRing

Wattage	3W
Colour Temperature	3000K
Voltage	12VDC
Light Output	280 lm (3000K)
Rated Life	50,000 Hrs.
Finish	Aluminum
Dimmable	Yes
Safety Certification	cUL
Diameter	2-7/16" / 62 mm
Surface Mount Height	1/2" / 12 mm
Recessed Cutout Diameter	2-1/8" / 55 mm
Carton Quantity	100 Pieces Per Carton
Warranty	3 Years

Ribbon Lights 3200K



SKU# - Model
#960 - LED RL-1FT 3200K



Ribbon Lights 5000K



SKU# - Model
#942 - LED RL-1FT 5000K



Wattage	3.5 Watts / ft
Voltage	12VDC
CRI	90
Life(Hrs)	50,000 Hrs
Nominal Length	12 inches / 1 FT
Colour Temperature	3000K / 5000K
Waterproofing	IP55 – Indoor / Outdoor
LED Quantity	18 LEDs / FT
Light Output	280 lm / FT
Current Draw	0.292 A / FT
LED Type	2835 SMD LEDs
Dimmable	Yes
Maximum Linkable Length	24 Feet Max

Wattage	3.5 Watts / ft
Voltage	12VDC
CRI	90
Life(Hrs)	50,000 Hrs
Nominal Length	12 inches / 1 FT
Colour Temperature	3000K / 5000K
Waterproofing	IP55 – Indoor / Outdoor
LED Quantity	18 LEDs / FT
Light Output	280 lm / FT
Current Draw	0.292 A / FT
LED Type	2835 SMD LEDs
Dimmable	Yes
Maximum Linkable Length	24 Feet Max

Ribbon to Supply Connector



SKU# - Model
#577 - RDC-60
#517 - RDC-24
#576 - RDC-48

12" Ribbon to Ribbon Connector



SKU# - Model
#578 - RLC-12
#597 - RLC-24
#598 - RLC-36

Description	24"-60" Flexible 4-Pin Ribbon to DC Barrel (F) Power Supply Connector Cable
-------------	---

Description	12"-36" Flexible Ribbon to Ribbon 4-Pin Connector Cable
-------------	---


4-way Ribbon Connector



SKU# - Model
#599 - RLC-4RS

Description Flexible 4-Way Ribbon Connector

DC Barrel Hardwire Connector



SKU# - Model
#613 - DC-HW

Description DC Barrel (Male) to Hardwire
- For RDC Cable to Hardwire
Driver

L Ribbon Connector



SKU# - Model
#607 - RL-L

Description "L" Connector - 90° Ribbon to Ribbon
Connector

T Ribbon Connector



SKU# - Model
#600 - RL-T

Description "T" Connector - Ribbon to Ribbon
Connector


X Ribbon Connector



SKU# - Model
#609 - RL-X

Description "X" Connector - Ribbon to Ribbon
Connector

End to End Connector



SKU# - Model
#611 - RL-4P

Description 4-Pin Male to Male Connector

End Caps



SKU# - Model
#612 - RL-4PEC (End Cap)

Description End cap for LED Ribbon (Epoxy not
included)

Ribbon Mounting Clips



SKU# - Model
#687 - RL-CLIPS

Description LED Ribbon Mounting Clips with
screws (10/pk)

Surface Aluminum Channel



SKU# - Model
#994 - FP20-1M

Description SURFACE Mount Aluminum Channel - 1 meter

Recessed Aluminum Channel



SKU# - Model
#996 - RP20-1M

Description RECESSED Mount Aluminum Channel - 1 meter

End Cap Set



SKU# - Model
#995 - FP20-CAPS

Description END CAP SET for Surface Mount Channels

End Cap Set



SKU# - Model
#997 - RP20-CAPS

Description END CAP SET for Recessed Mount Channels

Mounting Clip



SKU# - Model
#998 - FP20-M-CLIPS

Description MOUNTING CLIP & Wood Screw

Spring Clip



SKU# - Model
#999 - RP20-S-CLIPS

Description SPRING CLIP & Machine Screw

LED DRIVERS

For Low Voltage 12V Cabinet Lighting

- Puck Lights
- Ribbon Lights
- Panel Lights

12W Round LED Driver



SKU# - Model
#1060 - PS12W-ETL-RD



Output Power (W)	12W
Input Voltage (VAC)	100V-130VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Output Current	1000 mA
Power Factor (PF)	>0.95
Minimum Load	70% for Best Dimming
Connection Type	Terminal Block
IP Rating	IP20
Dimensions	67 mm D x 20 mm H 2-5/8" D x 3/4" H
Life (Hrs)	50,000 Hrs

20W Round LED Driver



SKU# - Model
#1061 - PS20W-ETL-RD



Output Power (W)	20W
Input Voltage (VAC)	100V-130VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Output Current	1600 mA
Power Factor (PF)	>0.95
Minimum Load	70% for Best Dimming
Connection Type	Terminal Block
IP Rating	IP20
Dimensions	73 mm D x 27 mm H 2-7/8" D x 1-1/16" H
Life (Hrs)	50,000 Hrs

40W Round LED Driver



SKU# - Model
#1062 - PS40W-ETL-RD



Output Power (W)	40W
Input Voltage (VAC)	100V-130VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Output Current	3300 mA
Power Factor (PF)	>0.5
Minimum Load	No Minimum Load
Connection Type	Terminal Block
IP Rating	IP20
Dimensions	100 mm D x 30 mm H 3-15/16" D x 1-3/16" H
Life (Hrs)	50,000 Hrs

60W Round LED Driver



SKU# - Model
#1063 - PS60W-ETL-RD



Output Power (W)	60W
Input Voltage (VAC)	100V-130VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Output Current	4500 mA
Power Factor (PF)	>0.5
Minimum Load	No Minimum Load
Connection Type	Terminal Block
IP Rating	IP20
Dimensions	100 mm D x 30 mm H 3-15/16" D x 1-3/16" H
Life (Hrs)	50,000 Hrs

100W LED Driver



SKU# - Model
#1035 - PS100W-ETL-DIM



Output Power (W)	100W
Input Voltage (VAC)	100V-120VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Output Current	8000 mA
Power Factor (PF)	>0.5
Minimum Load	No Minimum Load
Connection Type	Terminal Block
IP Rating	IP20
Dimensions	236 mm x 68 mm x 40 mm
Life (Hrs)	50,000 Hrs

18W Metal Jbox LED Driver



SKU# - Model
#945 - PS-18W-BOXDIM



Output Power (W)	18W
Input Voltage (VAC)	90V-130VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Dimmable	Yes - down to 15%
Environmental Rating	Type IC Recessed, Damp Locations
Dimensions (without tabs)	117 mm x 85 mm x 39 mm
Life (Hrs)	50,000 Hrs

40W Metal Jbox LED Driver



SKU# - Model
#946 - PS-40W-BOXDIM



Output Power (W)	40W
Input Voltage (VAC)	90V-130VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Dimmable	Yes - down to 15%
Environmental Rating	Type IC Recessed, Damp Locations
Dimensions (without tabs)	157 mm x 85 mm x 39 mm
Life (Hrs)	50,000 Hrs

36W Plug LED Driver



SKU# - Model
#619 - PS36W-PLUG



72W Plug LED Driver



SKU# - Model
#620 - PS72W-PLUG



Wattage (W)	36W
Current(IA)	3A
Input Voltage (VAC)	120VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Life (Hrs)	50,000 Hrs

Wattage (W)	72W
Current(IA)	6A
Input Voltage (VAC)	100VAC-240VAC
Output Voltage (VDC)	12VDC – Constant Voltage
Life (Hrs)	50,000 Hrs

100W Metal Chassis LED Driver



SKU# - Model
#467 - PS100W-MC



150W Metal Chassis LED Driver



SKU# - Model
#625 - PS150W-MC



Output Power (W)	102W
Current(IA)	8.5A
Input Voltage (VAC)	100VAC-240VAC
Output Voltage (VDC)	12VDC - Constant Voltage
Life (Hrs)	50,000 Hrs

Output Power (W)	150W
Current(IA)	12.5A
Input Voltage (VAC)	100VAC-240VAC
Output Voltage (VDC)	12VDC - Constant Voltage
Life (Hrs)	50,000 Hrs

LED PRODUCTS

STEP



LIGHTS

Edge Style Steplight - Black



SKU# - Model
#1004 - LED SL-BK



Edge Style Steplight - Brushed Nickel



SKU# - Model
#1005 - LED SL-BN



Wattage (W)	5 Watts
Voltage (V)	120VAC
Color Temperature	3000K
Water Resistance Rating	IP66 Outdoor Rated
Orientation	Horizontal
Overall Light Output	400 lm
Rated Life	50,000 Hrs.
Electrical Fitting Size	Fits 1-Gang Box
Dimmable	Yes
Safety Certification	cETLus
Warranty	5 Years
Carton Quantity	20 Pieces Per Carton

Wattage (W)	5 Watts
Voltage (V)	120VAC
Color Temperature	3000K
Water Resistance Rating	IP66 Outdoor Rated
Orientation	Horizontal
Overall Light Output	400 lm
Rated Life	50,000 Hrs.
Electrical Fitting Size	Fits 1-Gang Box
Dimmable	Yes
Safety Certification	cETLus
Warranty	5 Years
Carton Quantity	20 Pieces Per Carton

Edge Style Steplight - White



SKU# - Model
#1003 - LED SL-WH



Step Light Engine (Trim Required)



SKU# - Model
#729 - LED STE-2W Light Engine



Wattage (W)	5 Watts
Voltage (V)	120VAC
Color Temperature	3000K
Water Resistance Rating	IP66 Outdoor Rated
Orientation	Horizontal
Overall Light Output	400 lm
Rated Life	50,000 Hrs.
Electrical Fitting Size	Fits 1-Gang Box
Dimmable	Yes
Safety Certification	cETLus
Warranty	5 Years
Carton Quantity	20 Pieces Per Carton

Wattage (W)	2 Watts
Voltage (V)	110V - 120VAC
Color Temperature	3000K
Water Resistance Rating	IP67 Outdoor Rated
Light Output	250 lm
Rated Life	50,000 Hrs.
Electrical Fitting Size	Fits 1-Gang Box
Dimmable	No
Safety Certification	cETLus
Warranty	3 Years
Carton Quantity	1 Piece Per Carton

Black Louver Trim



SKU# - Model
#736 - LED ST-Black Louver
(Requires #729
LED STE-2W Light Engine)

Colour	Matte Black
Accessory Type	Metal Faceplate
Length	133 mm / 5.24 inches
Height	84 mm / 3.31 inches
Carton Quantity	10 Pieces Per Carton

Black Window Trim



SKU# - Model
#770 - LED ST-Black Window
(Requires #729
LED STE-2W Light Engine)

Colour	Matte Black
Accessory Type	Metal Faceplate
Length	133 mm / 5.24 inches
Height	84 mm / 3.31 inches
Carton Quantity	10 Pieces Per Carton

Nickel Louver Trim



SKU# - Model
#731 - LED ST-Nickel Louver
(Requires #729
LED STE-2W Light Engine)

Colour	Brushed Nickel
Accessory Type	Metal Faceplate
Length	133 mm / 5.24 inches
Height	84 mm / 3.31 inches
Carton Quantity	10 Pieces Per Carton

Nickel Window Trim



SKU# - Model
#748 - LED ST-Nickel Window
(Requires #729
LED STE-2W Light Engine)

Colour	Brushed Nickel
Accessory Type	Metal Faceplate
Length	133 mm / 5.24 inches
Height	84 mm / 3.31 inches
Carton Quantity	10 Pieces Per Carton

White Louver Trim



SKU# - Model
#737 - LED ST-White Louver
(Requires #729
LED STE-2W Light Engine)

Colour	Matte White
Accessory Type	Metal Faceplate
Length	133 mm / 5.24 inches
Height	84 mm / 3.31 inches
Carton Quantity	10 Pieces Per Carton

White Window Trim



SKU# - Model
#769 - LED ST-White Window
(Requires #729
LED STE-2W Light Engine)

Colour	Matte White
Accessory Type	Metal Faceplate
Length	133 mm / 5.24 inches
Height	84 mm / 3.31 inches
Carton Quantity	10 Pieces Per Carton

LED PRODUCTS

COMMERCIAL



FIXTURES

High Bay



SKU# - Model
#958 - HB180W50K



High Bay-347V



SKU# - Model
#877 - HB190W50K-347V



Wattage	180W
Colour Temperature	5000K
Light Output	23,800 lm
Voltage	110V-277VAC
Dimmable	Yes, 0-10V down to 10%
Rated Life	50,000 Hrs.
Base Type	Hardwire
Certifications	cUL, DLC
CRI	80
Energy Efficiency	134 lm/W
Power Factor	0.9
THD	15%
Fixture Colour	White
Beam Angle	120°
Diffuser Type	Clear Acrylic Diffuser
Dimensions	23.9" x 19.7" x 1.8"
Warranty	5 Years

Wattage	190W
Colour Temperature	5000K
Light Output	25,000 lm
Voltage	347VAC
Dimmable	Yes, 0-10V down to 10%
Rated Life	50,000 Hrs.
Base Type	Hardwire
Certifications	DLC, cUL
CRI	80
Energy Efficiency	132 lm/W
Power Factor	0.9
THD	15%
Fixture Colour	White
Beam Angle	120°
Diffuser Type	Clear Acrylic Diffuser
Dimensions	23.9" x 19.7" x 1.8"
Warranty	5 Years

Wall Pack 60W



SKU# - Model
#1087 - WPGR60HV740DS11



Wattage	59.97 W (60W)
Colour Temperature	4000K
Light Output	7,825.8 lm
Voltage	120V – 347VAC
Dimmable	Yes – 0-10V
Rated Life	50,000 Hrs.
Certifications	DLC, cETLus
CRI	72
Energy Efficiency	130.51 lm/W
Power Factor	0.9204
THD	10.76%
Fixture Colour	Dark Bronze

Wall Pack 120W



SKU# - Model
#1086 - WPGR120HV740DS11



Wattage	114.1 W (120W)
Colour Temperature	4000K
Light Output	15,029 lm
Voltage	120V – 347VAC
Dimmable	Yes – 0-10V
Rated Life	50,000 Hrs.
Certifications	DLC, cETLus
CRI	72.2
Energy Efficiency	131.75 lm/W
Power Factor	0.9095
THD	19.85 %
Fixture Colour	Dark Bronze

Commercial Strip Light



SKU# - Model
#1017 - LED35WSTP 40K



Wattage	35W
Colour Temperature	4000K
Light Output	4585 lm
Voltage	120V – 347VAC
Dimmable	0-10V Dimming
Rated Life	50,000 Hrs.
Certifications	DLC, cUL
CRI	82
Energy Efficiency	131 lm/W
Fixture Color	White
Dimensions (mm)	1202 L x 60.2 W x 71.2 H
Dimensions (inches)	47.3"L x 2.4"W x 2.8"H

LED PRODUCTS

EXIT & EMERGENCY



LIGHTS

Running Man Exit Sign



SKU# - Model
#989 - LED EX100-SP



System Power	2 W
Battery Type:	Sealed Ni-Cd
Voltage	120V-347VAC
Illuminated Sides	Single/Double Sided
Safety Certification	cCSAus
Width	13.2 inches / 335 mm
Height	9 inches / 230 mm
Depth	2 inches / 50 mm
Environmental Rating	Damp Location
Warranty	5 Years

Running Man Combo Unit



SKU# - Model
#990 - LED EX101-CB



System Power	6 W
Battery Type:	Sealed Ni-Cd
Voltage	120V-347VAC
Illuminated Sides	Single Sided
Safety Certification	cCSAus
Width	13.2 inches / 335 mm
Height	12 inches / 305 mm
Depth	3.15 inches / 80 mm
Adjustable Head	Yes
Head Size	2-5/8 inches
Environmental Rating	Damp Location
Warranty	5 Years

Running Man Exit Sign (Edge-Lit)



SKU# - Model
#991 - LED EX102-EDGE



System Power	2 W
Battery Type:	Sealed Ni-Cd
Voltage	120V-347VAC
Illuminated Sides	Double Sided
Safety Certification	cCSAus
Width	13.3 inches / 338 mm
Height	10.8 inches / 275 mm
Depth	1.6 inches / 40 mm
Environmental Rating	Damp Location
Warranty	5 Years

Battery Pack 36W



SKU# - Model
#1067 - BP-36W



Battery Capacity	36W (6V 6Ah)
Battery Type	Lead Acid
Output Voltage	6VDC
Input Voltage	100V-347VAC
Safety Certification	cCSAus
Width	11.8 inches / 300 mm
Height	5.5 inches / 140 mm
Depth	3 inches / 75 mm
Adjustable Head	Yes
LED Lumen Output	260lm (2 x 130lm)
Environmental Rating	Damp Location
Warranty	5 Years

Battery Pack 72W



SKU# - Model
#1068 - BP-72W



Battery Capacity	72W (12V 7Ah)
Battery Type	Lead Acid
Output Voltage	12VDC
Input Voltage	100V-347VAC
Safety Certification	cCSAus
Width	12.2 inches / 310 mm
Height	7.87 inches / 200 mm
Depth	2.75 inches / 70 mm
Adjustable Head	Yes
LED Lumen Output	260lm (2 x 130lm)
Environmental Rating	Damp Location
Warranty	5 Years

Single Remote Head



SKU# - Model
#1069 - RH-1



Lamp Power	2W
LED Lumen Output	130 lm
Light Efficacy	65 lm/W
Input Voltage	6V-12VDC
Safety Certification	cCSAus
Base Diameter	5 inches / 128 mm
Height	5.5 inches / 140 mm
Adjustable Head	Yes
Lens Material	Polycarbonate UL 94v0
Environmental Rating	Damp Location
Warranty	5 Years

Double Remote Head



SKU# - Model
#1070 - RH-2



Lamp Power	4W (2 x 2W)
LED Lumen Output	260 lm (2 x 130 lm)
Light Efficacy	65 lm/W
Input Voltage	6V-12VDC
Safety Certification	cCSAus
Dual Head Length	7.8 inches / 198 mm
Base Diameter	5 inches / 127 mm
Height	4.9 inches / 123 mm
Adjustable Head	Yes
Lens Material	Polycarbonate UL 94v0
Environmental Rating	Damp Location
Warranty	5 Years

Prepaid Freight Guideline

Domestic Shipments from Vancouver Warehouse

Minimum Order: \$ 50.00

Location	Prepaid Freight*	Delivery Time
In Greater Vancouver	\$200 and Over	1 - 2 days
In British Columbia	\$300 and Over	1 - 2 days
In Alberta	\$500 and Over	1 - 2 days
In Saskatchewan	\$500 and Over	2 - 3 days
In Manitoba	\$500 and Over	4 - 5 working days
In Ontario	\$500 and Over	5 working days
In Quebec	\$500 and Over	5 working days

* Prepaid Freight subject to stock availability

Domestic Shipments from Toronto Warehouse

Minimum Order: \$ 100.00

Location	Prepaid Freight*	Delivery Time
In Greater Toronto	\$200 and Over	1 - 2 days
In Ontario	\$300 and Over	1 - 2 days
In Quebec	\$500 and Over	2 days
In Atlantic Provinces	\$500 and Over	3 days

* Prepaid Freight subject to stock availability

SEND ORDERS TO:

Tel. 604.438.2862 (Toll Free: 877.772.2862)

Fax. 604.438.2972 (Toll Free: 877.772.2972)

Email. orders@cnalighting.com

Warranty

CNA International Enterprises Inc. ("CNA") warrants that its products against failure due to defect in material or workmanship as per the following product categories:

LED Products: 2-5 year warranty starting from the date of sale to the end customer unless otherwise specified in product specification sheets. 10 year warranty on our LED Exit Sign products.

CFL Products: 1 year warranty starting from the date of sale to the end customer.

Warranty for our Distributors & Retailers:

Should a failure occur during the warranty period, it is at the sole discretion of CNA to either replace the product

or credit the customer's account. Credit will be based on current distributor price list or invoice dollars, whichever is lesser.

For product replacement, this does not include any freight, removal, re-installation, labour or equipment costs. Warranty will only cover products that have not been subject to accident, neglect, abuse, misuse or acts of God.

Warranty for End Customers:

For warranty claims, please contact the distributor who sold you the product. If you want to make a warranty claim directly, you must send back defective product (freight at your cost), original receipt, and indicate RMA# (contact CNA for RMA#). Replacements will be freight prepaid by us.

General Return Policy

CNA accepts product returns with a 20% restocking charge provided that returned goods are new, unused, in original packaging, and in re-sellable condition. Freight for returns is paid by the customer. Always contact CNA prior to any returns to get a return authorizing number. Unauthorized returns will not be accepted. Discontinued products are not eligible for returns.

CNA LIGHTING

A DIVISION OF CNA INTERNATIONAL ENTERPRISES INC.

#8 – 8980 Fraserwood Court,
Burnaby, BC, Canada V5J 5H7

Tel. 604.438.2862
(Toll Free: 877.772.2862)

Fax. 604.438.2972
(Toll Free: 877.772.2972)

Email. orders@cnalighting.com

cnalighting.com