HGTV SERIES / Expansion tank with replaceable bladder

U	יט	1		ы				
	г\	u	J	_				


Representative:	Project:
Date Submitted:	Submitted by:
Date Approved:	Approved by:
Model Number:	Quantity:

DESCRIPTION

The expansion tank from the HGTV Series are offered in sizes going from 13 to 74 gallons, on stand. These expansion tanks are build of two welded part to resist high pressures for a secure installation. The EPDM bladder separates the air from the water inside the tank saving space and energy. These devices are suitable for hot water, solar and cooling in addition to being compatible with glycol.

- Acceptance factor of 100%
- ▶ Water remains permanently separated from the air throughout the useful life of the installation
- ▶ The water does not escape the circuit. The steel tank never comes into contact with water
- Pre-charged at the factory to 12 PSI; tank need to be adjusted on site at the system operating pressure

Model#	Volume	Conn. FNPT	Pre- charge	Max. temp.	Maximum operating	Dimension				Maialah		
	voiume					А		В		Weight		
	gal	L		onargo	tompi	pressure	in	mm	in	mm	lb	kg
HGTV-30	13	50	1"	12 PSI	240°F	115 PSI	14.9	380	25.3	645	25	12
HGTV-40	21	80	1"	12 PSI	240°F	115 PSI	17.7	450	26.7	680	29	13
HGTV-60	26	100	1"	12 PSI	240°F	115 PSI	17.7	450	30.1	765	35	16
HGTV-90	40	150	1¼"	12 PSI	240°F	115 PSI	19.7	500	41.1	1045	49	22
HGTV-110	57	215	1¼"	12 PSI	240°F	115 PSI	19.7	500	52.1	1325	77	35
HGTV-150	74	280	1¼"	12 PSI	240°F	115 PSI	19.7	500	63.1	1605	102	46



TYPICAL SPECIFICATIONS

Furnish and install, as shown on the plans, a _____ gallons/liters____ in/mm diameter × _____ precharged steel expansion tank, with an EPDM replaceable bladder that separate water from touching the steel shell of the tank. The tank must have a 100% acceptance factor and shall have NPT connection as well as a .302"-32 charging valve (standard tire valve) to facilitate the on-site charging of the tank to meet system requirements. Each tank shall be a CALEFACTIO model HGTV-____ or approved equal.

Quebec (Canada)

T 450 951.0818

F 450 951.2165