


SIMPLY THE STRONGEST MADE TANKS ON THE MARKET.



A LOGICAL AND RESPONSIBLE CHOICE

SAFE.

ECOGARD double-bottom system with leak detection system.

ENVIRONMENT FRIENDLY.

Respond to environmental concerns and requirements.

GUARANTEED DURABILITY.

Polyurethane coating for external protection available on 20PLUS and ECOPLUS models.

With 50+ years of experience, Granby Industries is known for its quality and proven track record in innovation and design.







Residential oil tanks / UL 80

Product #	Capacity	Model	Gauge thickness	Di	Weight		
	(US gal.)			Н	W	L	(lb.)
209101	120	vert.	12	47"	23"	30"	170
208101	138	vert.	12	44"	27"	30"	160
208601	138	horiz.	12	27"	44"	30"	160
207101	220	stubbies/vert.	12	44"	27"	48"	220
203201G	230	thin/vert. grey	12	44"	22"	60"	235
203701G	230	thin/horiz. grey	12	22"	44"	60"	235
202201	240	narrow/vert.	12	47"	23"	60"	265
202701	240	narrow/horiz.	12	23"	47"	60"	265
204201	275	vert.	12	44"	27"	60"	255
204701	275	horiz.	12	27"	44"	60"	255
211201	275	vert.	10	44"	27"	60"	330
211701	275	horiz.	10	27"	44"	60"	330
205201	330	vert.	12	44"	27"	72"	290
205701	330	horiz.	12	27"	44"	72"	290



Warranty*: 10 years



Cylindrical models horizontal

Product #	Capacity (US gal.)	Model	Gauge cover thickness	Di Shell	mension Dia.	ıs Height	Weight (lb.)
3005224	138	horiz.	12	12	26"	60"	165

External finish: BLACK electrostatic paint

Warranty*: 3 years



20PLUS Residential oil tanks with polyurethane coating



Product #	Capacity (US gal.)	Model	Gauge thickness	Dimensions H W L	Weight (lb.)
204201P	275	vert.	12	44" 27" 60"	257
204701P	275	horiz.	12	27" 44" 60"	257
205201P	330	vert.	12	44" 27" 72"	290
205701P	330	horiz.	12	27" 44" 72"	290

UL 142 also available (275 and 330 gal.)

External finish: BEIGE polyurethane coating Touch up paint: PEOO56C "BEIGE" KROO01 (repair kit)

Warranty*: 20 years



ECOGARD

Residential oil tanks with double-bottom protection system



Product #	Capacity	Model	Gauge		Din	nensions	3	Weight
	(US gal.)		thickness		Н	W	L	(lb.)
244201	275	vert.	12	4	44"	27"	60"	290
245201	330	vert.	12	4	44"	27"	72"	334

External finish: BEIGE powder paint coating Touch up paint: PEOO55C "BEIGE"

Warranty*: 25 years



ECOPLUS


Residential oil tanks with ECOGARD + 20PLUS with polyurethane coating




Product #	Capacity (US gal.)	Model	Gauge thickness	Di H	mension: W	s L	Weight (lb.)
244201P	275	vert.	12	44"	27"	60"	295
245201P	330	vert.	12	44"	27"	72"	340

External finish: BEIGE polyurethane coating Touch up paint: PEOO56C "BEIGE" KR0001 (repair kit)

Warranty*: 30 years





Technical specifications

- Steel ASTM A1011
- Female threaded openings
- Pressure tested at 5 to 7 PSIG
- UL 80 and UL 142 listed
- Operation at atmospheric pressure

2-IN-1 DOUBLE-WALL TANKS

HDPE plastic tanks inside a galvanized secondary containment



Model #	Top opening qty	Burner oil supply opening size / location	Capacity L/USG	Dim H	ensions ((in.) L	Weight lb.	Approved usage
961225	4	3/8" and 1/2" / top duplex bushing	720 / 190	48	28	44	150	Indoors / outdoors
961226	4	3/8" and 1/2" / top duplex bushing	1000 / 265	63	28	44	185	Indoors / outdoors

Warranty: 30 years*

All tanks include the following accessories

- 1 Sealed rope gauge
- 1 NPT metallic 2" fill pipe adaptor
- 1 NPT 2" metallic low-restriction vent alarm
- 1 Metallic duplex bushing
- 2 Burner oil lines 1/2" x 1/2" NPT fitting
- 2 Burner oil lines 3/8" x 1/2" NPT fitting



Gauge PN: 962247 - 720 L / 190 USG 962248 - 1000 L / 265 USG



Vent alarm 2" NPT PN: E540-999



Galvanized cover



Duplex bushing, 3/8" tube adaptor PN: E207F-999S Duplex bushing, 3/8" tube adaptor PN: E208F-999S

2-in-1 safety tank system optional and/or spare accessories

Model #	Description
960000	Rain cover—mandatory for outdoor installations
962245	Installation tie-down kit for 720 L / 190 USG
962246	Tie-down kit for 1000 L / 265 USG
962247	Leak indicator assembly for 720 L / 190 USG
962248	Leak indicator assembly for 1000 L / 265 USG
962266	Sealed fuel oil rope gauge 720 L / 190 USG
962267	Sealed fuel oil rope gauge 1000 L / 265 USG
962280	Metallic cap nut ADC12
971040	2" transition fiting for gauge
E206-0001	Compression fitting 1/2" x 1/2" tube
E207F-999S	Duplex bushing with 3/8" x 1/2" NPT fitting
E208F-999S	Duplex bushing with 1/2" x 1/2" NPT fitting
E209-0001	Compression fitting 1/2" x 3/8" tube
E250-999S	Threaded 2" NPT fill pipe adaptor
JE03002	Gauge gasket 3.275 x 2.725 x 0.125 UL157
JE15020	Metallic cap nut O-ring seal CDPM
E540-999	2" NPT low-restriction vent and overfill alarm

2-in-1 safety tanks general characteristics; ULC/ORD-C80.1 listed

- Primary tank made of blow-molded high-density polyethylene (HDPE)
- Internal tank is fluorination treated for odor and chemical resistance, which is unique to the Granby 2-in-1 tanks
- Secondary containment made of galvanized steel on both sides, tightly welded and edged using state-of-the-art manufacturing equipment
- Visual leak indicator for the monitoring of the integrity of the primary tank
- Connection fittings made of cast aluminum for greater torque resistance and greater peripheral sealing
- Rugged floor stand made entirely of galvanized steel

- Tanks come completely equipped from factory with necessary installation accessories
 - 2" NPT galvanized steel fill pipe adaptor
 - Low-pressure vent and overfill protection alarm
 - Oil level gauge
 - Oil burner supply duplex bushing with tube adaptors
- Optimal space utilization
 - Suited for basements with headrooms as low as 60"
 - Ease in maneuverability and access through narrow doorways only 28" wide
- Easy carrying due to light weight and welded handles
- 30-year limited warranty
- B100 bio-fuel ready
- Optional rain cover mandatory for outdoor installation



FOR MORE INFORMATION, PLEASE CONTACT OUR MAIN OFFICE AT:

1020 André-Liné Street Granby QC J2J 1J9 Canada 1-800-839-2070 sales@granbytanks.com