


THE NEW GENERATION OF OIL-FIRED WARM AIR FURNACES



LOWBOY REAR BREECH (KLR)

+ PERFORMANCE



ENERGY STAR® CERTIFIED AT ALL FIRING RATES*

+ ECONOMICAL OPERATION

ANNUAL EFFICIENCY RANGING FROM 86% TO 95.8% HIGH-EFFICIENCY BLOWER MOTORS

+ COMFORTABLE

A MORE EVEN HEAT AND A QUICKER, MORE PRECISE RESPONSE TO A CALL FOR HEAT FROM THE THERMOSTAT

+ EASE OF MAINTENANCE

DUE TO ITS NON-REFRACTORY COMBUSTION CHAMBER AND TUBULAR SECONDARY HEAT EXCHANGERS



AFUE 95.8% UP TO 95.8%



GET THE MAXIMUM OUT OF YOUR HEATING APPLIANCE

AFUE* 95.8%

COMPARATIVE ANNUAL HEATING OIL CONSUMPTION CHART

	2,000 L		2,500 L		3,000	
FURNACE AFUE OF 65%	3,000					
FURNACE AFUE OF 75%	2,600					
FURNACE AFUE OF 85% (ENERGY STAR minimum)	2,294			74		
GRANBY CONFORTO 88.6%	2,213					
GRANBY CONFORTO CHE 95.8%	2,044					

Example of a yearly heating oil consumption (liters) * Annu

* Annual Fuel Utilization Efficiency

ECM HIGH-EFFICIENCY MOTORS VERSUS PSC MOTORS

UP TO 82% ENERGY EFFICIENCY DUE TO ECM[†] TECHNOLOGY!

Represents savings of up to 50% (watts) during heating and cooling mode and of up to 75% (watts) during continuous fan operation.

†Electronically controlled motor

UNMATCHED PERFORMANCE, SAVINGS AT YOUR REACH



CONDENSING HIGH EFFICIENCY









THE CONFORTO CHE (CONDENSING HIGH EFFICIENCY) FURNACE IS THE FIRST OIL-FIRED FURNACE BUILT FOR HOMEOWNERS WHO EXPECT UNSURPASSED PERFORMANCE AND ENERGY EFFICIENCY. ITS INNOVATIVE OPERATION WILL HAVE YOU PROFIT FROM A 95%+ HEATING EFFICIENCY ALONG WITH SUPERIOR PERFORMANCE AND COMFORT. THIS PERFORMANCE COULD HELP YOU SAVE UP TO 40% ON YOUR HEATING OIL CONSUMPTION AND COULD REDUCE YOUR GREENHOUSE GAS (GHG) EMISSIONS BY UP TO 3,000 LB./YR! IN ADDITION TO ITS ATTRACTIVE LOOK, THE CONFORTO CHE HOLDS THE ENERGY STAR® CERTIFICATION AT ALL FIRING RATES. ITS CONCEPTION COMBINING PERFORMANCE AND DURABILITY WILL BRING YOU THE BEST COMFORT POSSIBLE AND THE EASE OF MAINTENANCE THAT YOU ARE LOOKING FOR.

FEATURES

1 ROBUST AND DURABLE COMBUSTION CHAMBER

- 100% premium stainless steel construction
- European design
- Heats up more quickly
- Helps in maintaining a more even temperature in the home
- Brings additional heating oil savings compared to conventional appliances
- More durable
- Easier to service

2 SECONDARY TUBULAR HEAT EXCHANGERS

- 100% welded one-piece heat exchanger, no bolts and fastners
- 100% premium stainless steel
- Provided with stainless steel baffles to maximize heat transfer from the heat exchanger
- The tubular design of the secondary heat exchanger provides a quiet and maximum thermal exchange
- Due to its low restriction to the circulating air, this appliance is compatible with today's high-efficiency heat pumps or air conditioning systems

3 HIGH-EFFICIENCY BLOWER

- Blower supplied with high-efficiency ECM motor
- Brings additional operating utility savings compared to conventional blower motors
- Innovative blower removal system for easy servicing and maintenance

4 SAFE AND EASY-TO-USE ELECTRONIC CONTROL

- Oversees the safe burner operation and speeds of the fan motor
- Provides on-board connections for optional electronic air cleaner and humidifier
- On-board connections for A/C systems
- · Continuous low-speed fan switch
- Compatible with heat pumps operating controls

5 HIGH-EFFICIENCY BURNERS


- Offered with high static pressure oil burners that offer a better control of the combustion excess air allowing for a cleaner and more efficient combustion
- Electronic safety controls
- High-power electronic ignition

6 VENTING OPTIONS

- Balanced flue burner with through-the-wall or through-the-roof coaxial or two-pipe venting systems using PVC plastic piping
- Single-pipe PVC plastic venting using an existing chimney chase along with a standard burner
- Comes standard with an auto-reset pressure switch protection device in case of flue or air intake blockage

7 NO DAMAGE TO THE ENVIRONEMENT

- Factory-installed condensate neutralizing cartridge
 - Neutralizes the acid content on the condensate liquid to allow evacuation of the condensate liquid to the house's plumbing
 - Supplied with every furnace
 - Easy to replace





THE CONFORTO FURNACE IS THE FIRST NORTH AMERICAN OIL-FIRED APPLIANCE THAT HOLDS THE ENERGY STAR® CERTIFICATION AT ALL FIRING RATES. THE CONFORTO WAS ENGINEERED WITH PERFORMANCE IN MIND, WHICH WILL BRING YOU QUALITY AND COMFORT WITH NO COMPROMISE. ITS ATTRACTIVE LOOK COMBINES THE DURABILITY AND EASE OF MAINTENANCE THAT YOU ARE LOOKING FOR.




FEATURES

1 ROBUST AND DURABLE COMBUSTION CHAMBER

- 100% premium stainless steel construction
- European design
- Heats up more quickly
- Helps in maintaining a more even temperature in the home
- Brings additional heating oil savings compared to conventional appliances
- More durable
- Easier to service

2 SECONDARY TUBULAR HEAT EXCHANGERS

- 100% welded one-piece heat exchanger, no bolts and fasteners
- Premium steel
- Provided with stainless steel baffles to maximize heat transfer from the heat exchanger
- The tubular design of the secondary heat exchanger provides a quiet, and maximum thermal exchange
- Due to their low restriction to the circulating air, these appliances are compatible with today's highefficiency heat pumps or air conditioning systems



3 BLOWER OPTIONS

- Comes standard with standard efficiency PSC blower motors or with high-efficiency ECM blower motors
 - The ECM type motor provides additional operating utility savings compared to conventional motors
- Easy-to-remove system for service and maintenance

4 SAFE AND EASY-TO-USE ELECTRONIC CONTROL

- Oversees the safe burner operation and speeds of the fan motor
- Provides on-board connections for optional electronic air cleaner and humidifier
- On-board connections for A/C systems
- · Continuous low-speed fan switch
- Compatible with heat pumps operating controls

5 HIGH-EFFICIENCY BURNERS

 Offered with high static pressure oil burners that offer a better control of the combustion excess air allowing for a cleaner and more efficient combustion

Electronic safety controls


High-power electronic ignition

6 VENTING OPTIONS

- Rear breech (KLR) or front breech (KLF & KHM)
- Can be vented using a standard chimney and standard burner or using the Granby DVS (Direct Vent System) – through-the-wall venting with a balanced flue burner

HIBOY - MULTIPOISE (KHM)

- One unit 4 installation options
 - Upflow
 - Downflow
 - Horizontal right
 - Horizontal left
- Can be installed anywhere due to its small footprint
- Triple-pass heat exchanger offering the highest heating efficiency for a standard hiboy furnace – the most performant unit of its kind on the market



KLR KLF KHM

VENTING OPTIONS



DIRECT VENT SYSTEM (DVS)




- Replaces conventional chimneys
- · 100% stainless steel coaxial terminal
- Sealed combustion using balanced flue burners
- Comes standard with an auto-reset pressure switch protection device in case of flue or air intake blockage
- Brings outside combustion air, ideal for air-tight homes
- Stainless steel flue pipe available in 10, 15 or 20-feet length




(KLC)

COAXIAL PVC PLASTIC VENTING THROUGH THE WALL OR THROUGH THE ROOF



- Ideal for installation where there is no chimney
- Sealed combustion using balanced flue burner
- Simple installation

TWO-PIPE PVC PLASTIC VENTING THROUGH THE WALL



- Ideal for installation where there is no chimney
- Sealed combustion using balanced flue burner
- Can run greater distances than plastic coaxial venting
- Simple installation

SINGLE-PIPE PVC PLASTIC VENTING THROUGH AN EXISTING CHIMNEY CHASE





- Single-pipe venting using an existing chimney chase
- The most economical and simple venting option
- Single-pipe installation using a standard burner
- Can run long horizontal distances
- Ideal when through-the-wall venting options are not possible











Specifications

Furnace model	KLC-100	KLR-100	KLR-200	KLF-200	KHM-100	KHM-200
Firing rate USGPH	0.55 - 0.65	0.55 - 0.65 - 0.75	0.85 - 1.00 - 1.15	0.75 - 0.85 - 1.00 - 1.10	0.55 - 0.65 - 0.75	0.85 - 1.00 - 1.15
Input capacity MBTU/H	77 – 91	77 — 91 — 105	119 — 147 — 161	105 - 119 - 140 - 154	77 — 91 — 105	119 — 147 — 161
Output capacity MBTU/H	74 – 87	66 – 79 – 91	102 - 126 - 139	93 - 102 - 119 - 132	66 – 79 – 91	102 - 126 - 139
AFUE %	95.8	86.2 to 87.1	86.5 to 87.8	86.3 to 88.6	86.0 to 86.8	86.4 to 87.5
ENERGY STAR certification at every firing rate*	Yes	Yes	Yes	Yes	Yes	Yes
A/C ready electronic operating control	Yes	Yes	Yes	Yes	Yes	Yes
Chimney vent	No	Yes	Yes	Yes	Yes	Yes
Direct vent — Granby DVS	No	Optional	Optional	Optional	Optional	Optional
PVC plastic through the wall or roof venting options	Yes	No	No	No	No	No
PSC blower motor hp — number speeds	N/A	1/2 hp — 4	3/4 hp — 4	3/4 hp — 4	1/2 hp — 4	3/4 hp — 4
CFM at 0.50" wc (ext. static pressure)	N/A	1275	2030	2030	1275	2030
ECM blower motor hp — number speeds*	1/2 hp — 5	1/2 hp — 5	3/4 hp — 5	1/2 hp — 5 and 3/4	1/2 hp — 5	3/4 hp — 5
CFM at 0.50" wc (ext. static pressure)	1230	1230	1910	1230 1910	1230	1910

Dimensions (in.)

Height	36 7/8	33	33	35 1/8	46 1/4	49 7/8
Width	21 1/2	21 1/2	21 1/2	21 1/2	21 7/16	21 7/16
Depth	50 1/4	49 1/8	55 1/8	52 5/8	26	30
Supply plenum size	20 x 20	20 x 20	20 x 24	20 x 24	20 x 20	24 x 20
Return plenum size	20 x 20	20 x 20	20 x 22	20 x 20	18 x 18	23 x 18

^{*}Certification to ENERGY STAR version 4.0

ABOUT GRANBY

Since 1954, Granby Industries has been the North American leader in manufacturing and marketing steel tanks for storage of oil products and high-efficiency boilers and furnaces. Our continuous research and development program answers the needs of our customers in regards to energy efficiency and comfort by providing affordable and innovative solutions.

Granby Industries offers a complete line of safe, durable and reliable quality-built products. For over five decades, service and innovation have helped Granby gain an enviable reputation as well as value-added expertise for its customers.



GRANBY FURNACES INC. 12118 Hwy 209, P.O.Box 637 Parrsboro, NS BOM 1SO Canada 902-254-2543 1-800-477-4328

sales@granby industries.com







