

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Metal-working product
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes

PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 3 H229 Pressurised container: May burst if heated.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

H229 Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

IE-EN

(Contd. on page 2)

www.griffon.eu 1/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Metal working product

· Dangerous components:		
CAS: 10024-97-2		1-2.5%
EINECS: 233-032-0	🕸 Ox. Gas 1, H270; 🥎 Press. Gas (Liq.), H280	
Reg.nr.: 01-2119970538-25	•	
CAS: 137-16-6	sodiumlaurylsarcosinate	<1%
Reg.nr.: 01-2119527780-39	Acute Tox. 2, H330; Sepe Dam. 1, H318; Skin Irrit. 2, H315	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · **6.2 Environmental precautions:** No special measures required.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

- IE-EN

www.griffon.eu 2/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 2)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

10024-97-2 dinitrogen oxide

OEL (Ireland) Long-term value: 90 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye protection: Not required.

IE-EN

(Contd. on page 4)

www.griffon.eu 3/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 3)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: 0 °C Initial boiling point and boiling range: 100 °C

• **Flash point:** Not applicable, as aerosol.

• Flammability (solid, gas): Not applicable.

• **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· Explosive properties: Not determined.

· Explosion limits:

Lower: 2.6 Vol % Upper: 12.6 Vol %

· Vapour pressure at 20 °C: 23 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

• Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic at 20 °C:O.952 mPas **Kinematic:**Not determined.

· Solvent content:

 Water:
 98.4 %

 Solids content:
 0.3 %

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

(Contd. on page 5)

- IF-FN

www.griffon.eu 4/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 4)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

10024-97-2 dinitrogen oxide

Inhalative LC50/4 h 1.06 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes: Not hazardous for water.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

IE-EN -

(Contd. on page 6)

www.griffon.eu 5/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 5)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/ADN 1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, non-flammable

· 14.3 Transport hazard class(es)

· ADR/ADN



· Class 2 5A Gases.

· Label 2.2

· IMDG, IATA



· Class 2.2 · Label 2.2

· 14.4 Packing group

· ADR/ADN, IMDG, IATA not regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code): -

· EMS Number: F-D,S-U

• Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

(Contd. on page 7)

- IE-EN

www.griffon.eu 6/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.06.2021 Version number 30 Revision: 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

	(Contd. of pag
	Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision class 2.
 14.7 Transport in bulk according to Annex of Marpol and the IBC Code 	II Not applicable.
· Transport/Additional information: · Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Remarks:	Under certain conditions substances in Class (flammable liquids) can be classified packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

IE-EN

(Contd. on page 8)

www.griffon.eu 7/8



Safety data sheet according to 1907/2006/EC, Article 31

Version number 30 Revision: 16.06.2021 Printing date 16.06.2021

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H270 May cause or intensify fire; oxidiser.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Aerosols Bridging principles

Department issuing SDS: Bison QESH

Contact: Reach coordinator

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 3: Aerosols - Category 3

Ox. Gas 1: Oxidizing gases - Category 1

Press. Gas (Liq.): Gases under pressure - Liquefied gas

Acute Tox. 2: Acute toxicity – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

* Data compared to the previous version altered.

IF-FN

8/8 www.griffon.eu