

Spec Sheet

GF-1042DMM

Type	Flow-Through Humidifier
GPD (Based on 120° Plenum Temperature)	17
Dimensions (Inches)	14 H x 15.125 W x 9 D
Weight (Pounds)	13
Replacement Vapor Pad® (Replace Once Each Season)	GF-990-13
Home Size (Sq. Ft.)	To 2,800
Installation	Warm Air / Return Air Plenum / Right of Left Side
Plenum Opening (Inches)	13.625 W X 9.5 H
Bypass Opening (Inches)	6
Pallet Qty.	30
Cabinet Construction	UV-Stable Automotive Grade Plastic
Humidistat	GF-MHX3 (Included with GF-1042DMM)
Optional Humidistat	GF-X3 (Included with GF-1042DMD)
Voltage (Volts)	24
Warranty (Years)	5
Typical Installation	For newer homes up to 2,800 square feet and homes with a forced-air heating system
In The Box	Humidifier, humidistat, Installation Instructions, Vapor Pad®, Parts Kit, Drain Hose, Transformer, Metal Distributor Tube, Damper, 15'-5/8" Drain Hose, Drain Pan, Solenoid Valve.



GF-1042DMM



GF-MHX3
Manual Humidistat
Included in
GF-1042DMM



GF-X3 Digital
Humidistat
Included in
GF-1042DMD

Accessories



GF-990-53
Solenoid Valve


Spec Sheet

Models GF-1042DMM Features

- Model GF-1042DMM accommodates up to 2800 square feet.
- Cover is UV stable.
- Stainless steel distributor tube allows for either cold or hot water supply.
- GF-MHX3 manual control humidistat is included.
- A long-standing model; considered the “work horse” of humidifiers.

Installation

Vertical plenum surface of any forced air furnace



Installs Quickly & Easily

Installation Options:

- Warm Air Plenum
- Return Air Plenum
- Right or Left Bypass
- Vertical or Horizontal
- Furnace or Air Handler

Maintenance

Change the Vapor Pad® at least once per year.

Product Support

- Installation Manual
- Home Owner Brochure
- Competitive Comparison
- www.GeneralAireIAQ.ca
 - Maintenance Video
 - Help Topics
 - Product Information
- Tech Support (888) 216-9184



GF-990-13 Vapor Pad®