

RESIDENTIAL

STORAGE TANKS

| 30 | 40 | 60 | IMP. GALLONS





ANTICIPATE THE NEEDS OR YOUR FAMILY

When selecting your storage tank, optimize your comfort and choose a potable water or space heating application. These storage tanks are ideal for modern households that require larger volumes of hot water for multiple full bathrooms, multi shower head systems, extra-large bathtubs or whirlpools, spas, etc.

BENEFITS

HIGH DEMAND APPLICATION

Available in 30, 40 and 60 lmp. Gallon, these tanks will store your hot water at a constant temperature no matter the intensity of your draws.

HIGH QUALITY MAGNESIUM ANODE

Provides excellent protection against the corrosive effects of water and extends tank life.

BRASS COMBINATION INLET DRAIN VALVE

A high quality one-piece brass combination inlet drain valve is installed for easy drainage and recirculation.

FACTORY INSTALLED 3/4" NPT DI-ELECTRIC NIPPLES

Extend the life of the water heater by providing excellent corrosion protection.

FACTORY INSTALLED T&P RELIEF VALVE

Protects the tank from the damaging effects of excessive temperature and pressure.

GLASS-LINED INNER TANK

A uniquely formulated blue cobalt glass enriched with zircon is fused to specially treated steel at 1,600°F (871°C) to provide the best coating available against corrosion for many years. The tank is certified at a test pressure of 300 PSI (2,068 kPa) and a working pressure of 150 PSI (1,035 kPa).







7 - INSULATION

A thick uniform blanket blanket of GREENFOAM eco-friendly insulation keeps the water hotter for longer periods, reduces standby losses and energy costs. GREENFOAM contains no HCFC'S (hydrochlorofluorocarbons), CFC'S (chlorofluorocarbons), HFC'S (hydrofluorocarbons) nor VOC's (volatile organic compounds).

OVERFLOW SYSTEM

A 90° horizontal overflow elbow tube is supplied with each storage tanks.





SPECIFICATIONS & DIMENSIONS														
Models	Storage Capacity			Α		В		С		D	Е		Estimated shipping weight	
	US gal.	Litres	Imp. gal.	inches	(cm)	inches	(cm)	inches	(cm)		inches	(cm)	lb	(kg)
142ETE-9G7M	34	130	29	22	(56)	36 1/4	(92)	2 1/8	(5)	45°	4	(10)	115	(52)
I52ETE-9G7M	49	184	41	22	(56)	49 1/4	(125)	2 1/8	(5)	45°	4	(10)	140	(64)
172ETE-9G7M	74	279	61	24	(61)	60	(152)	2 1/8	(5)	45°	4	(10)	185	(84)



Giant offers a FIVE (5) year limited warranty against inner tank leakage from the date of installation on all residential storage tanks. They also benefit from a ONE (1) year limited warranty on component parts. For more specific warranty details including exceptions, consult the owner's manual provided with each tanks.



A family company since 1945.

40 Lesage Avenue, Montréal-East, Québec, Canada, H1B 5H3 Telephone: 514 645-8893 • Toll free: 1 800 363-9354

General fax: 514 640-0969

Customer Service fax: 514 645-8413

In accordance with our company policy of on-going product improvement, Giant Factories Inc. reserves the right to make changes without prior notice. www.giantinc.com