



SPECIFICATIONS:

Light Output: 500 LM/m (154 LM/ft.)
Power: 5 Watts/m (1.5 Watts/ft.)
Voltage: 12V
Efficacy (Lumens per Watt): 100 LM/W
Colour Accuracy (CRI): 80+
Light Colour: 3000K Warm White
Beam Angle: 120°
Length: 16'-3" / 5m
Width: 0-1/2" / 12mm
Depth: 0-3/16" / 4mm
Cuttable every 2" / 50mm
Dimmable
Waterproof IP67 (with sealed connections)
50,000 Life Hours
Included: 4 x Silicone End Caps per Roll

LIGHTING FACTS


REG DENSITY RIBBON

ITEM NO. **GLF-RD-12V-30K-V2**

Light Output (Lumens) **500/m**
Watts **5/m**
Lumens per Watt (Efficacy) **100**

Colour Accuracy **80+**
Colour Rendering Index (CRI)

Light Colour **3000K Warm White**



PHOTOMETRICS:

MOUNTING HEIGHT (FT.)	CENTER BEAM FOOT CANDLES (FC)	EDGE BEAM FOOT CANDLES (FC)	BEAM AREA COVERED (FT.)
5 FT.	0.0 FC	0.0 FC	0'-0"
7 FT.	0.0 FC	0.0 FC	0'-0"
9 FT.	0.0 FC	0.0 FC	0'-0"
12 FT.	0.0 FC	0.0 FC	0'-0"
16 FT.	0.0 FC	0.0 FC	0'-0"
18 FT.	0.0 FC	0.0 FC	0'-0"

COMING SOON





REGULAR DENSITY LED RIBBON

PART NUMBER: GLF-RD-12V-30K-V2

PRODUCT BENEFITS:

Regular density ribbon is perfect for many applications including millwork accents such as toe kick lighting, niches, display cases/open shelving and more!

AVAILABLE ACCESSORIES:

12V Dimmable Drivers

25W • GLS-12025-TD
50W • GLS-12050-TD
100W • GLS-12100-TD
150W • GLS-12150-TD
200W • GLS-12200-TD

Quick Clip Feed

GLF-FEED

Quick Clip Flexible Joiner

GLF-FLEX

Aluminum Channels

Deep Recess • GLF-1201REC-1M
Deep Surface • GLF-1202SUR-1M
45° Angle • GLF-1203ANG-1M
Shallow Recess • GLF-1204RECS-1M
Shallow Surface • GLF-1205SURS-1M

Drywall Channel Lighting System

Chopstick Lighting System