



GLT-PUCK-12V-BK	LIGHTING SPECS
Light Output (Lumens) 130Lm±10%	
Power 2 Watts	
Lumens per Watt (Efficacy) 65	
Colour Accuracy (CRI) 90+	
Light Colour 3000k Warm White	
LED Chip Epistar	
Size 75.4mm W x 6mm H (3mm high when recessed)	
2.97" W x 0.24" H (0.12" high when recessed)	
2¼" hole cut	
60cm (23.62") AMP connector	
Beam Angle 120°	
Dimmable	
Energy Star Rating	
35,000 Life Hours	
3 Year Warranty	



Lighting Specs PUCK LIGHT	
ITEM NO.	GLT-PUCK-12V-BK
Light Output (Lumens)	130
Watts	2
Lumens per Watt (Efficacy)	65
Colour Accuracy	90+
Colour Rendering Index (CRI)	
Light Colour	3000 (Warm White)
	
2700K	3000K
4500K	6500K
2 Watt Warm White	

GLT-PUCK-12V-BK PHOTO METRICS			
MOUNTING HEIGHT	CENTER BEAM FOOT CANDLES (FC)	EDGE OF BEAM FOOT CANDLE (FC)	BEAM AREA COVERED
4FT	53.6FC	18.3FC	3'
6FT	24FC	8.1FC	4' 6"
8FT	13.1FC	5.9FC	6"
10FT	8.1FC	2.6FC	8'
12FT	5.6FC	1.9FC	9' 6"
14FT	3.6FC	1.3FC	11'
16FT	2.7FC	1.1FC	12'6"

