

Firestrap



"In-Hole" firestop device that has preformed 3M™ Interam™ Ultra GS Wrap material in a foil encapsulated package that is wrapped around the pipe and fitted into the substrate.



Available Sizes:
1-1/2", 2" and 3"

Ultra GS Intumescent Wrap Strip



The Ultra GS Wrap Strip is a flexible, black coloured, highly intumescent (25 times expansion) material. It can be used to seal combustible PEX pipe applications as well.



Available Sizes:
2" x 40' x 1/8" thick rolls

Ultra Plastic Pipe Device



Ultra Plastic Pipe Device is red coloured, contains 3M™ Interam™ Ultra GS wrap material in a preformed collar. When exposed to temperatures of 121°C the wrap material expands (up to 25 times) to seal combustible pipe service penetrations.



Available Sizes: 1-1/2", 2", 3", 4" and 6"

RC-1 Collar



The RC-1 Collar is a 28 gauge steel preformed collar that is cut to size and is used in conjunction with the Ultra GS Wrap Strip and the FS-195+ Wrap Strip.



Cast-In-Place Device



Fire Barrier Cast-in-Place device is a one-piece plastic body assembly. Easily adjustable bodies can be adapted to concrete height, simply with a pair of pliers.



IC 15WB+ Sealant



The IC 15WB+ is an intumescent firestop sealant that is yellow in colour for easy identification. It is used to seal smaller sized DWV penetrations through fire rated substrates.



FS-195+ Wrap Strip



The FS-195+ Wrap Strip is a flexible, reddish brown, foil backed, intumescent (6 to 10 times expansion) material that is used in conjunction with an RC-1 Collar.



Available Sizes:
2" x 24" x 1/4" thick strips

FireDam™ 150+ Caulk



FireDam™ 150+ Caulk is an acrylic, blue or limestone coloured, latex-based, non-sag, paintable sealant that bonds to most construction materials including concrete, metals, wood and cable jacketing.

