



REVISION								
REV	DATE	DESCRIPTION						
Α	10/13/22	525769GCP - RELEASE MRY						

1								
NO	COMPONEN	IT NO	DES	CRIPTION	QTY/M	U/M		
			BILL OF N	/ATERIAL				
<s></s>		CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE						
		DENOTES CRITICAL CHARACTERISTICS.						
(PK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE						
<	ST)	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.						
	СР	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.						
MATL SPEC				FINISH				
DRW JMoler			DATE 10/11/2022	SCALE NTS	FINISH GOOD V	NT IS/PIEC		

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE PROJECTION $\oplus \Box$

TITLE

JTD-ID 225-400A OUTLINE



DRWG NO. SHEET 1 OF 1

OL-0JTD400ID