

BLUELINE™

WIRE CONNECTORS

FEATURES + BENEFITS

- Comprehensive wire-range capacity; accommodates combinations from 22 to 8 AWG
- Pre-threaded, zinc-plated spring provides secure wire grip
- No pre-twisting required
- Deep skirt provides extra protection against over-stripping
- Compact design saves space in tight applications
- Ergonomic design for a comfortable and secure grip



PRODUCT SPECIFICATIONS

WIRE RANGE

- 22-8 AWG
- Max: 4 #12
- Min: 3 #22 solid

WIRE TYPE

- Copper wire only

TEMPERATURE

- Temperature rating: 105°C (221°F)

VOLTAGE

- 600V maximum (building wire)
- 1000V maximum (fixtures and signs)

QUANTITY

Pail (150)

Jar (475)

Drum (30,000)

PART NUMBER

WWC-BL-P

WWC-BL-J

WWC-BL-D

BLUELINE™

CONNECTEURS DE FILS

CARACTÉRISTIQUES ET AVANTAGES

- Convient à un vaste éventail de calibres et combinaisons de fils de 22 à 8 AWG
- Ressort plaqué zinc pré-fileté qui permet de fixer solidement le fil
- Aucune torsion préalable nécessaire
- Colerette profonde qui offre une protection supplémentaire contre le dénudage excessif
- Format compact qui convient aux espaces restreints
- Forme ergonomique pour une prise confortable et sécuritaire



SPÉCIFICATIONS DU PRODUIT

CALIBRE DE FIL

- 22-8 AWG
- Max: 4 n° 12
- Min: 3 n° 22

TYPE DE FIL

- Fil de cuivre seulement

TEMPÉRATURE

- Température nominale : 105°C (221°F)

TENSION

- 600 V maximum (fils de bâtiment)
- 1 000 V maximum (luminaires et enseignes)

QUANTITÉ

Seau (150)

Bocal (475)

Baril (30 000)

N° DE PIÈCE

WWC-BL-P

WWC-BL-J

WWC-BL-D