SPT-1 (Parallel Lamp Cord)



Conductor Annealed stranded copper
Insulation Rip type Black, White, Brown, Clear or Gold PVC
Temperature -20C to +60C or +105C
Packaging 75m, 150m & 300m spools, long length reels.
Approvals CSA FT1, UL 62
Applications For use on clock, radios, TV sets, stereos, lamps, household fans, and appliances not subject to hard usage.

Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thick. (Inches)	Sgstd Wrkn Voltage	Nominal O.D. (Inches)	Colour Code	Ship. Wght lbs/kft
39C1802	18	2	42	.031	300	.105x.198	See Above	21

SPT-2 (Parallel Lamp Cord)



Conductor Annealed stranded copper
Insulation Rip type Black, White, Brown, Clear or Gold PVC
Temperature -20C to +60C or +105C
Packaging 75m, 150m & 300m spools, long length reels.
Approvals CSA FT1, UL 62
Applications For use on clock, radios, TV sets, stereos, lamps, household fans, and appliances not subject to hard usage.

Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thick. (Inches)	Sgstd Wrkn Voltage	Nominal O.D. (Inches)	Colour Code	Ship. Wght lbs/kft
39CA1802	18	2	41	.045	300	.135x.260	See Above	28
39CA1602	16	2	65			.145x.285		39