



Oil-Tight Knockout Seals

Galvanized Steel

Features

- Oil-tight with one side gasket with wing clip for installation

Applications

- Inserted in discontinued, open box, or enclosure knockouts to protect exposed wires
- Gasket for use in oil-tight applications

Standard Material

- Galvanized Steel, Epoxy Coated
- Gasket

Certification

- UL File #: UL, CUL, RoHS Compliant



Catalog Number	UPC	Size	Box Qty	Ship Case	Weight (lb) per 100	Inches	
						A	B
KOS-50-OT	15801	1/2"	50	---	5	0.63	1.39
KOS-75-OT	14273	3/4"	50	---	5.4	0.63	1.57
KOS-100-OT	14240	1"	25	---	5.6	0.63	1.89
KOS-125-OT	14243	1-1/4"	10	---	10.7	0.63	2.19
KOS-150-OT	14246	1-1/2"	10	---	15	0.63	2.51
KOS-200-OT	14249	2"	10	---	24	0.63	3.00
KOS-250-OT	14252	2-1/2"	10	---	32.1	0.63	3.50
KOS-300-OT	14255	3"	1	---	44.8	0.63	4.12
KOS-350-OT	14258	3-1/2"	1	---	48.6	0.63	4.63
KOS-400-OT	14261	4"	1	---	69.4	0.63	5.13

Nesco Inc.

1039 Cardiff Blvd., Mississauga, ON L5S 1P4

TF: (866) 466-3726 Tel: (905) 793-2218 Fax: (905) 793-2268

www.nescocanada.com