



Energy Advantage IR PAR38

Energy Advantage IR 55PAR38/IRC+/FL25 120V 12/1

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

Product data

General Information	
Cap-Base	E26/50X39 [Skirted Medium Screw (PAR Lamps)]
Operating Position	Universal [Universal]
Main Application	Flood and Ambient Lighting
Gas Filling	Gas
Life with 3 Hour Per Day Use	3.8 a
Light Technical	
Beam Angle (Nom)	25 °
Luminous Flux (Nom)	1100 lm
Luminous Intensity (Nom)	4100 cd
Beam Description	Flood [Flood]
Correlated Color Temperature (Nom)	2700 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	55 W
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	CL [Clear (CL)]

Cap-Base Information	Brass [Brass Base]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [Axial]

Approval and Application


Estimated Energy Cost Per Year	6.62 \$
--------------------------------	---------

Product Data

Order product name	Energy Advantage IR 55PAR38/IRC+/FL25 120V 12/1
EAN/UPC - Product	046677238650
Order code	238659
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	924757133801
Net Weight (Piece)	355.000 g

Energy Advantage IR PAR38

Dimensional drawing



Product	D	C (max)
Energy Advantage IR 55PAR38/IRC+/FL25 120V 12/1	4.75 in	5.313 in

PAR38 IRC 55W E26/50x39/BRC 120V FL 25D

