

PHILIPS**Lighting**

Energy Advantage IR PAR38

Energy Advantage IR 55PAR38/IRC+/WFL40 120V 12/1


Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

Product data

General Information		Cap-Base Information	
Cap-Base	E26/50X39 [Skirted Medium Screw (PAR Lamps)]	Brass [Brass Base]	
Operating Position	Universal [Universal]	Bulb Material	Hard Glass
Main Application	Flood and Ambient Lighting	Reflector Finish	Aluminized
Gas Filling	Gas	Filament Shape	CC-8 [Axial]
Life with 3 Hour Per Day Use	3.8 a	Approval and Application	
Light Technical		Estimated Energy Cost Per Year	
Beam Angle (Nom)	40 °	6.62 S	
Luminous Flux (Nom)	1110 lm	Product Data	
Luminous Intensity (Nom)	1800 cd	Order product name	Energy Advantage IR 55PAR38/IRC+/WFL40 120V
Beam Description	Wide Flood [Wide Flood]	12/1	
Correlated Color Temperature (Nom)	2700 K	EAN/UPC - Product	046677238490
Color Rendering Index (Nom)	100	Order code	238493
Operating and Electrical		Numerator - Quantity Per Pack	1
Power (Rated) (Nom)	55 W	Numerator - Packs per outer box	12
Voltage (Nom)	120 V	Material Nr. (12NC)	924757133401
Mechanical and Housing		Net Weight (Piece)	355.000 g
Bulb Finish	CL [Clear (CL)]		

Energy Advantage IR PAR38

Dimensional drawing



Product	D	C (max)
Energy Advantage IR 55PAR38/IRC+/WFL40 120V 12/1	4.75 in	5.313 in

PAR38 IRC 55W E26/50x39/BRC 120V WFL 40D

