



SL8-LED60

LED Strip Light

SPECIFICATIONS

Watts	63
Lumens	8059
Efficacy	128.2 Lm/W
Replaces Up To	2 Lamp 8ft T8
Colour Temp**	Selectable - 3K, 4K, 5K
Certification	cULus, IP20
Operating Temp	-30°C to +40°C
Voltage	120-277V*, 120-347V*
LED Life (L70)	>100,000 hours
Housing Material	Steel
Lens Material	Polycarbonate
Lens Type	Frosted
Mounting	Surface mount, suspended mount using linear ceiling pendant mount
Total Harmonic Distortion	7.9%
Power Factor	0.90
CRI	80
Internal Surge Protection	2KV
Weight	7.7 lbs

* Standard Configuration

** Colour temperature is selectable and can be adjusted on the fixture through a switch. The default switch setting is set to 4K on the fixture.



DESCRIPTION

The SL8-LED60 strip light provides a highly efficient lumen output of approx. 8000 lumens ideal for replacing 2 lamp 8ft T8 fixtures. The frosted linear lens provides uniform light distribution ideal for use in shops, coves and general area lighting.

APPLICATIONS



Shops



Cove Lighting



General Area Lighting

FEATURES

- Fixture can be set at a colour temperature of 3000K, 4000K or 5000K through a switch inside the housing
- Narrow, linear design with frosted lens for uniform light distribution
- Join up to 12 fixtures on a single circuit using easy connector steel plates. Fixtures are daisy chained with line wires fished though the housing continuous row.
- Options: dimming high frequency sensor (inside housing), wire cage, reflector wings, linear ceiling pendant mount kit

FULL SPECIFICATIONS

DESCRIPTION	VOLTAGE (V)	INPUT POWER (W)	LIGHT OUTPUT	EFFICACY (Lm/W)	THD	PF	CRI
SL8-LED60-B-VK-DIM	120-277	63	8059	128	7.9	0.90	>80
SL8-LED60-H-VK-DIM	120-347	65	8533	132	3.6	0.99	>80


LEGEND

B - 120V-277V, H- 120-347V

VK - Selectable CCT

DIM - 0-10V Dimming

DIMENSIONS



COLOUR SELECTABLE SWITCH

The switch is located inside of the fixture.

1. 5000K
2. 4000K
3. 3000K

1. 5000K
2. 4000K
3. 3000K

(Default switch setting)

Easily change the colour temperature with the flip of a switch.

1. TOP position = 5000K
2. MIDDLE position = 4000K
3. BOTTOM position = 3000K

LINEAR CEILING PENDANT MOUNT KIT

Linear Ceiling Pendant Mount Kit

Contains 2 x 5 foot aircraft cables with ceiling mounting plates, fixture mounting rod and nut, 6 drywall anchors, and 6 screws.

SKU 089814

REFLECTOR WINGS

Reflector Wings Kit - Wings attach by inserting tabs into the cutouts on the fixture.

SKU 099513 X2 (order 2 pairs of SL4-LED REFLECTOR WINGS KIT - WHT for SL8-LED60 fixture)

WIRE CAGE

Wire Cage - To install, place wire cage over the fixture and screw the clips on to the mounting surface.

SKU 002271

ORDERING GUIDE

SL8	LED60		VK	DIM	
WATTS	VOLTAGE	COLOUR TEMP.	DRIVER	OPTIONS	
	B - 120 - 277V*	VK - COLOUR SELECTABLE*	DIM - 0-10V Dimming*	DHFS - Dimming High Frequency Sensor (factory installed inside the housing)	
	H - 120-347V*	(can be adjusted to 3K, 4K, or 5K)			

*Standard Configuration.

FIELD INSTALLED ACCESSORIES

CHECK THE ACCESSORIES YOU WISH TO ORDER:

002271 SL8-LED WIRE CAGE

089814 LINEAR CEILING PENDANT MOUNT KIT

099513 SL4-LED REFLECTOR WINGS KIT - WHT - Order 2 pairs for SL8-LED fixture.