

TANK ALERT® I ALARM SYSTEM

Easy to Install Liquid Level Alarm System for Indoor Use

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other water applications.

The Tank Alert® I alarm system can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds when a potentially threatening liquid level condition occurs. The horn can be silenced, but the warning light remains on until the condition is remedied. A green "power on" light indicates power to the alarm panel.

FEATURES

- NEMA 1 enclosure, designed for ease of installation, rated for indoor use
- Red "alarm" light, green "power on" light, alarm "test" switch, and horn "silence" switch
- Alarm horn sounds at 86 decibels at 10 feet (3 meters)
- Can be used with any UL Listed / Recognized switching mechanism rated to include 1 amp, 12 VAC load
- Alarm system (when installed on separate circuit) operates even if the pump circuit fails
- Switching mechanism operates on low voltage and is isolated from the power line to reduce the possibility of shock

OPTIONS

When ordered with the alarm, this system is available with:

- Alternate float switch models for high or low level warning
- 120 VAC primary voltage or 230 VAC primary voltage (230 VAC model is not UL Listed or CSA Certified)



Indoor Alarms



TANK ALERT® I - Easy-to-install liquid level alarm system for indoor use.

Part #	Description (120V)	Shipping Weight
1007457	101-01H (120 VAC w/15' SJE SignalMaster® High Level)	3.58 lbs
1009207	101-01HSPKT (120 VAC w/15' SJE SignalMaster® High Level) with splice kit	3.58 lbs.
1003104	101-01H (120 VAC w/15' Sensor Float® High Level)	3.58 lbs.
1003365	101-01L (120 VAC w/15' Sensor Float® Low Level)	3.58 lbs.
1002235	101-01X (120 VAC no float)	2.14 lbs.
Part #	Description (230V)	Shipping Weight
1008009	101-02H (230 VAC w/15' SJE SignalMaster® High Level)	3.58 lbs.
1003364	101-02H (230 VAC w/15' Sensor Float® High Level)	3.58 lbs.
1005420	101-02L (230 VAC w/15' Sensor Float® Low Level)	3.58 lbs.
1005419	101-02X (230 VAC no float)	2.14 lbs.

H = High Level L = Low Level X = No Float SPKT = Splice Kit MASTER CARTON holds 16 boxed units.

CONTROL SWITCH OPTIONS

The Tank Alert® I alarm system comes standard with a 15 foot SJE SignalMaster® control switch with mounting clamp. Other float switches are available. See control switch section of the catalog. To determine the price of alarm with an alternate float, add the price of the part number with "no float" to the price of the float switch.

SPECIFICATIONS

VOLTAGE FOR 120 VAC MODEL:

PRIMARY: 120 VAC, 50/60 Hz, 5 watts max. (alarm condition)

SECONDARY: 12 VAC

VOLTAGE FOR 230 VAC MODEL (not UL Listed or CSA Certified):

PRIMARY: 230 VAC, 50/60 Hz, 5 watts max. (alarm condition)

SECONDARY: 12 VAC

ALARM ENCLOSURE: 6 x 4 x 2.5 inch (15.24 x 10.16 x 6.35 cm), NEMA 1 metal

ALARM HORN: 86 decibels at 10 feet (3 meters)

POWER CORD: 6 foot (1.8 meter)

FLOAT SWITCH CONNECTION TERMINAL: For float switch connection only. Do not apply power. (Voltage across terminals is 12 VAC.)

FLOAT SWITCH: SJE SignalMaster® control switch with mounting clamp

CABLE: 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

FLOAT: 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high impact, corrosion resistant polypropylene housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

ELECTRICAL: 5 amps, 125 VAC/250 VAC, 50/60 Hz

Indoor Alarms