



MOL: 5/8 in. (15.90 mm)
Ø 1/4 in. (5.84 mm)

**T1.75-Midget Flanged
F6**



MOL: 1/4 in. (6.40 mm)
Ø 1/4 in. (5.84 mm)

T1.75-S4s/8



MOL: 13/16 in. (20 mm)
Ø 1/4 in. (5.50 mm)

T1.75-Wedge



MOL: 7/16 in. (11.40 mm)
Ø 3/16 in. (3.0 mm)

**T1-Wire
Terminal**



MOL: 1 11/16 in. (42.90 mm)
Ø 1/4 in. (6.40 mm)

**T2-Tel. Slide
No. 1**



MOL: 1 11/16 in. (42.90 mm)
Ø 1/4 in. (6.40 mm)

**T2-Tel. Slide
No. 2**



MOL: 1 1/8 in. (28.30 mm)
Ø 1/4 in. (6.40 mm)

**T2-Tel. Slide
No. 5**



MOL: 1 5/16 in. (33.30 mm)
Ø 1/4 in. (6.40 mm)

**T2-Tel. Slide
No. 6**

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Shape	Finish	Amps (A)	Average life (hrs)	LCL (in.) (mm)	Case qty (inner/master)
T (cont.)											
50253	T1.75/CL/28V/0.04A/25M/F6/STD	387	1	Midget Flanged F6	28	T-1.75	Clear	0.040	25 000	0.38 9.65	100/1 000
50246	T1.75/CL/28V/0.04A/7M/F6/STD	327	1	Midget Flanged F6	28	T-1.75	Clear	0.040	7 000	0.38 9.65	100/1 000
13369	T1.75/CL/28V/0.06A/F6	376	2	Midget Flanged F6	28	T-1.75	Clear	0.060	25 000	0.55 13.90	100/1 000
50503	T1.75/CL/12V/0.04A/S4s8/STD	7354	0.48	S4s/8	12	T-1.75	Clear	0.040	10 000	0.37 9.40	100/1 000
50494	T1.75/14V/0.08A/40M/S4s8/STD	386	1	S4s/8	14	T-1.75	Clear	0.080	40 000	0.58 14.73	100/1 000
50254	T1.75/CL/28V/0.04A/7M/S4s8/STD	388	1	S4s/8	28	T-1.75	Clear	0.040	7 000	0.38 9.65	100/1 000
50357	T1.75/CL/6.3V/0.2A/WDG/STD	86	1	Wedge	6	T-1.75	Clear	0.200	20 000	0.40 10.20	100/1 000
50699	T1.75/CL/14V/0.08A/WDG/STD	73	1	Wedge	14	T-1.75	Clear	0.080	15 000	0.40 10.20	100/1 000
50356	T1.75/CL/28V/0.04A/WDG/STD	85	1	Wedge	28	T-1.75	Clear	0.040	7 000	0.40 10.20	100/1 000
50317	T1.75/CL/14V/0.08A/50M/WT/STD	M2192	1	Wire Terminal	14	T-1.75	Clear	0.080	50 000	0.38 9.68	100/1 000
50489	T1.75/CL/24V/0.05A/WT/STD	M2176	1	Wire Terminal	24	T-1.75	Clear	0.050	2 000	0.38 9.61	100/1 000
50335	T2/CL/24V/0.035A/TS1/STD	24E	1	Tel. Slide No. 1	24	T-2	Clear	0.035	5 000	1.42 36.00	100/1 000
50255	T2/CL/48V/0.035A/TS1/STD	48C-1	2	Tel. Slide No. 1	48	T-2	Clear	0.035	5 000	1.41 35.80	100/1 000
50258	T2/CL/55V/0.052A/TS1/STD	55C-1	3	Tel. Slide No. 1	55	T-2	Clear	0.052	5 000	1.56 39.60	100/1 000
50244	T2/CL/24V/0.035A/TS2/STD	24X	1	Tel. Slide No. 2	24	T-2	Clear	0.035	5 000	1.50 38.00	100/1 000
50262	T2/CL/6V/0.14A/TS5/STD	6PSB	1	Tel. Slide No. 5	6	T-2	Clear	0.140	5 000	0.98 24.84	100/1 000
50243	T2/CL/24V/0.073A/TS5/STD	24PSB	2	Tel. Slide No. 5	24	T-2	Clear	0.073	5 000	0.91 23.10	100/1 000
50245	T2/CL/28V/0.04A/TS5/STD	28PSB	1	Tel. Slide No. 5	28	T-2	Clear	0.040	5 000	0.91 23.10	100/1 000
50231	T2/CL/120V/0.025A/TS5/STD	120PSB	3	Tel. Slide No. 5	120	T-2	Clear	0.025	5 000	0.91 23.10	100/1 000
50257	T2/CL/24V/0.03A/TS6/STD	52A	1	Tel. Slide No. 6	24	T-2	Clear	0.030	5 000	0.81 20.70	100/1 000



Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Shape	Finish	Amps (A)	Average life (hrs)	LCL (in.)	(mm)	Case qty (inner/master)
T (cont.)												
13626	T2.25/CL/12V/1A/G4	783	12	BiPin G4	12	T-2.25	Clear	1.00	50	0.77	19.50	1/10
50242	T2.5/CL/24V/0.073A/BA9S/STD	24MB	2	BA9s	24	T-2.5	Clear	0.07	5 000	0.79	20.00	100/1 000
10088	T2.5/CL/28V/0.04A/BA9S/STD	28MB	1	BA9s	28	T-2.5	Clear	0.04	5 000	0.79	20.00	100/1 000
50517	T2.5/CL/60V/0.05A/BA9s/STD	60MB	3	BA9s	60	T-2.5	Clear	0.05	5 000	0.79	20.00	100/1 000
50230	T2.5/CL/120V/0.025A/BA9s/STD	120MB	3	BA9s	120	T-2.5	Clear	0.02	5 000	0.79	20.00	100/1 000
50457	2T3.25/CL/6V/BA9s/STD	3895	2	BA9s	6	T-3.25	Clear	0.33	3 000	0.55	14.00	100/1 000
50346	T3.25/CL/6.3V/0.15A/3M/BA9s/STD	47	1	BA9s	6	T-3.25	Clear	0.15	3 000	0.78	19.80	100/1 000
50395	T3.25/6.3V/0.15A/20M/BA9S/STD	755	1	BA9s	6	T-3.25	Clear	0.15	20 000	0.78	19.80	100/1 000
50344	T3.25/6.3V/0.25A/3M/BA9S/STD	44	2	BA9s	6	T-3.25	Clear	0.25	3 000	0.78	19.80	100/1 000
50447	T3.25/6.3V/0.25A/5M/BA9s/STD	1866	2	BA9s	6	T-3.25	Clear	0.25	5 000	0.78	19.80	100/1 000
50455	2T3.25/CL/12V/BA9s/STD	3796	2	BA9s	12	T-3.25	Clear	0.16	3 000	0.55	14.00	100/1 000
50396	T3.25/CL/14V/0.08A/BA9S/STD	756	1	BA9s	14	T-3.25	Clear	0.08	15 000	0.63	15.90	100/1 000
50432	T3.25/CL/14V/0.2A/BA9s/STD	1815	3	BA9s	14	T-3.25	Clear	0.20	3 000	0.75	19.00	100/1 000
22074	T3.25/CL/14V/0.24A/BA9s/STD	1891	3	BA9s	14	T-3.25	Clear	0.24	500	0.63	15.90	100/1 000
50493	T3.25/CL/24V/0.06A/BA9s/STD	1437	1	BA9s	24	T-3.25	Clear	0.06	20	0.63	15.90	100/1 000
50456	2T3.25/24V/BA9s/STD	3797	2	BA9s	24	T-3.25	Clear	0.08	3 000	0.55	14.00	100/1 000
50434	T3.25/CL/24V/0.17A/BA9s/STD	1818	4	BA9s	24	T-3.25	Clear	0.17	250	0.63	15.90	100/1 000
50240	T3.25/CL/28V/0.022A/BA9S/STD	1843	1	BA9s	28	T-3.25	Clear	0.02	3 000	0.63	15.90	100/1 000
50435	T3.25/CL/28V/0.04A/BA9s/STD	1819	1	BA9s	28	T-3.25	Clear	0.04	1 000	0.63	15.90	100/1 000
50442	T3.25/CL/28V/0.07A/BA9s/STD	1829	2	BA9s	28	T-3.25	Clear	0.07	1 000	0.63	15.90	100/1 000
50397	T3.25/CL/28V/0.08A/BA9S/STD	757	2	BA9s	28	T-3.25	Clear	0.08	7 500	0.63	15.90	100/1 000
50436	T3.25/CL/28V/0.1A/BA9s/STD	1820	3	BA9s	28	T-3.25	Clear	0.10	1 000	0.63	15.90	100/1 000
50533	MIN T-3.25 28V 0.1A BA9s/BINGO	1820/B	3	BA9s	28	T-3.25	Clear	0.10	1 000	0.98	24.78	100/1 000
50446	T3.25/28V/0.17A/1.5M/BA9s/STD	1864	5	BA9s	28	T-3.25	Clear	0.17	1 500	0.63	15.90	100/1 000
50380	T3.25/CL/28V/0.17A/BA9S/STD	313	5	BA9s	28	T-3.25	Clear	0.17	500	0.63	15.90	100/1 000
50448	T3.25/CL/28V/0.2A/BA9s/STD	1873	6	BA9s	28	T-3.25	Clear	0.20	7 000	0.63	15.90	100/1 000
50438	T3.25/CL/36V/0.1A/BA9s/STD	1822	4	BA9s	36	T-3.25	Clear	0.10	1 000	0.63	15.90	100/1 000
50441	T3.25/CL/37.5V/0.05A/BA9s/STD	1828	2	BA9s	37	T-3.25	Clear	0.05	3 000	0.63	15.90	100/1 000
50443	T3.25/CL/55V/0.05A/BA9s/STD	1835	3	BA9s	55	T-3.25	Clear	0.05	5 000	0.63	15.90	100/1 000


 MOL: 1 3/16 in. (30 mm)
 Ø 7/16 in. (10.30 mm)

T3.25-BA9s


 MOL: 1 3/16 in. (30 mm)
 Ø 7/16 in. (10.30 mm)

T3.25-E10


 MOL: 1 1/16 in. (27 mm)
 Ø 7/16 in. (10.30 mm)

T3.25-Wedge


 MOL: 1 1/2 in. (38 mm)
 Ø 1/4 in. (6.35 mm)

T4-E12


 MOL: 1 1/2 in. (38 mm)
 Ø 1/4 in. (6.35 mm)

T4.5-E12


 MOL: 7/8 in. (22 mm)
 Ø 3/16 in. (4.80 mm)
T4.6-Slide Base 4x4
mm
 MOL: 1 1/2 in. (38 mm)
 Ø 5/8 in. (15.90 mm)

T5-BA15d


 MOL: 1 1/2 in. (38 mm)
 Ø 5/8 in. (15.90 mm)

T5-Wedge

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Shape	Finish	Amps (A)	Average life (hrs)	LCL (in.) (mm)	Case qty (inner/master)
T (cont.)											
50267	3T3.25/CL/125V/BA9s/STD	967	3	BA9s	125	T-3.25	Clear	0.025	5 000	0.63 15.90	10/1 000
50272	6T3.25/CL/125V/BA9s/STD	SP-114	6	BA9s	125	T-3.25	Clear	0.048	5 000	0.56 14.30	10/1 000
50706	T3.25/125V/0.3mA/BA9s/B1A/STD	B1A/NE-51	0.04	BA9s	125	T-3.25	Clear	0.001	15 000	0.63 16.00	10/1 000
50707	T3.25/125V/1.2mA/BA9s/B2A/STD	B2A/NE-51H	0.04	BA9s	125	T-3.25	Clear	0.001	15 000	0.63 16.00	10/1 000
10289	2.6T3.25/CL/130V/3M/BA9s/STD	949	3	BA9s	130	T-3.25	Clear	0.020	3 000	0.63 15.90	10/1 000
22066	2.6T3.25/CL/130V/1.5M/BA9s/STD	B3013	3	BA9s	130	T-3.25	Clear	0.020	1 500	0.81 20.60	10/1 000
50269	3T3.25/CL/130V/BA9s/STD	SP-105	3	BA9s	130	T-3.25	Clear	0.023	10 000	0.59 15.00	10/1 000
50391	T3.25/CL/24V/0.125A/E10/STD	599	3	E10	24	T-3.25	Clear	0.125	1 000	0.81 20.60	10/1 000
50375	T3.25/CL/6.3V/0.25A/5M/WDG/STD	259	2	Wedge	6	T-3.25	Clear	0.250	5 000	0.69 17.50	10/1 000
50875	T3.25/CL/14V/0.08A/WDG/STD	658	1	Wedge	14	T-3.25	Clear	0.080	1 500	0.56 14.30	10/1 000
50365	T3.25/CL/14V/0.19A/WDG/STD	161	3	Wedge	14	T-3.25	Clear	0.190	4 100	0.56 14.30	10/1 000
50368	T3.25/CL/14V/0.27A/WDG/STD	194	4	Wedge	14	T-3.25	Clear	0.270	2 500	0.56 14.30	10/1 000
13208	T3.25/CL/14V/0.33A/WDG/STD	193	5	Wedge	14	T-3.25	Clear	0.330	5 000	0.56 14.30	10/1 000
50366	T3.25/CL/14V/0.35A/WDG/STD	168	5	Wedge	14	T-3.25	Clear	0.350	1 500	0.56 14.30	10/1 000
10290	2T3.25/CL/24V/WDG/STD	2840	2	Wedge	24	T-3.25	Clear	0.083	5 000	0.56 14.30	10/1 000
50693	3T3.25/CL/24V/WDG/STD	2841	3	Wedge	24	T-3.25	Clear	0.125	3 000	0.56 14.30	10/1 000
50393	T3.25/28V/0.065A/2.5M/WDG/STD	656	2	Wedge	28	T-3.25	Clear	0.060	2 500	0.56 14.30	10/1 000
50394	T3.25/CL/28V/0.08A/WDG/STD	657	2	Wedge	28	T-3.25	Clear	0.080	7 500	0.56 14.30	10/1 000
22051	T3.25/CL/28V/0.2A/WDG/STD	655	6	Wedge	28	T-3.25	Clear	0.200	7 000	0.56 14.30	10/1 000
50710	4T4/CL/125V/E12/STD	SP-44	4	E12	125	T-4	Clear	0.032	3 000	1.00 25.40	10/1 000
50278	6T4/CL/125V/E12/STD	SP-43	6	E12	125	T-4	Clear	0.048	3 000	1.00 25.40	10/1 000
22128	T4.5/CL/2.0mA/E12/B7A/STD	B7A	0.25	E12	105-125	T-4.5	Clear	2.000	7 500	1.06 27.00	10/1 000
10419	T4.6/CL/30V/0.04A/SLB/STD	ATS3040	1	Slide Base 4x4 mm	30	T-4.6	Clear	0.040	5 000	0.77 19.44	10/1 000
13820	T5/CL/24V/0.21A/BA15D	B3524	5	BA15d	24	T-5	Clear	0.210	2 000	1.09 27.70	10/1 000
13825	T5/CL/140V/0.05A/BA15d	B3544	7	BA15d	140	T-5	Clear	0.050	2 000	1.01 25.70	10/1 000
13771	T5/CL/160V/0.031A/BA15d	A4047J	5	BA15d	160	T-5	Clear	0.031	2 000	1.09 27.70	10/1 000
22009	T5/CL/6V/0.62A/WDG/STD	909	4	Wedge	6	T-5	Clear	0.620	50	0.81 20.60	10/1 000
13737	T5/6.0V 0.9A WEDGE	939	5	Wedge	6	T-5	Clear	0.900	50	0.98 25.00	10/1 000
50405	T5/CL/6V/1.2A/WDG/STD	927	7	Wedge	6	T-5	Clear	1.200	50	0.81 20.60	10/1 000


MOL: 1 1/2 in. (38 mm)
0 5/8 in. (15.90 mm)

T5-Wedge


MOL: 2 1/8 in. (54 mm)
0 3/4 in. (18.90 mm)

T5.5-E14


MOL: 1 7/8 in. (48 mm)
0 3/4 in. (19.10 mm)

T6-BA15d


MOL: 1 3/16 in. (20 mm)
0 1/4 in. (6.80 mm)

T6.8-BA7s


MOL: 2 3/4 in. (69 mm)
0 1 in. (25.40 mm)

T8-BAY15d


MOL: 2 9/16 in. (65 mm)
0 1 in. (25.40 mm)

T8-E14


MOL: 1 9/16 in. (40 mm)
0 3/8 in. (10 mm)

T11-S8.5d


MOL: 2 3/4 in. (69 mm)
0 1 1/2 in. (38.10 mm)

T12-P28s


MOL: 2 1/8 in. (54 mm)
0 11/16 in. (17 mm)

T17-E14

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Shape	Finish	Amps (A)	Average life (hrs)	LCL (in.) (mm)	Case qty (inner/master)
T (cont.)											
50400	T5/CL/6V/1.5A/WDG/STD	908	9	Wedge	6	T-5	Clear	1.50	50	0.81 20.60	100/1 000
50402	T5/CL/12V/0.75A/WDG/STD	915	9	Wedge	12	T-5	Clear	0.75	50	0.81 20.60	100/1 000
50403	T5/CL/12.8V/0.56A/WDG/STD	918	7	Wedge	12	T-5	Clear	0.56	50	0.81 20.60	100/1 000
50401	T5/CL/12.8V/1A/WDG/STD	912	13	Wedge	12	T-5	Clear	1.00	1 200	0.81 20.60	100/1 000
50404	T5/CL/12.8V/1.4A/WDG/STD	921	18	Wedge	12	T-5	Clear	1.40	500	0.81 20.60	100/1 000
50399	T5/CL/13V/0.69A/WDG/STD	906	9	Wedge	13	T-5	Clear	0.69	1 000	0.81 20.60	100/1 000
50398	T5/CL/13.5V/0.69A/WDG/STD	904	9	Wedge	13	T-5	Clear	0.69	5 000	0.81 20.60	100/1 000
50318	9T5/CL/24V/WDG/STD	EMS-2409W	9	Wedge	24	T-5	Clear	0.37	75	0.81 20.60	100/1 000
50320	18T5/CL/24V/WDG/STD	EMS-2218W	18	Wedge	24	T-5	Clear	0.75	75	0.81 20.60	100/1 000
50709	10T6/CL/115V/BA15d/STD	SP-22	10	BA15d	115	T-6	Clear	0.08	1 000	1.13 28.60	100/1 000
50259	1.2T6.8/CL/60V/BA7s/STD	6020S	1	BA7s	60	T-6.8	Clear	0.01	5 000	0.75 18.98	100/1 000
22025	25T8/CL/24V/BAY15d/STD	2430U	25	BAY15d	24	T-8	Clear	1.04	1 000	1.38 35.00	100/1 000
22026	25T8/CL/32V/BAY15d/STD	3225U	25	BAY15d	32	T-8	Clear	0.78	1 000	1.38 35.00	100/1 000
50713	15T8/CL/130V/E14/STD	SP-59U	15	E14	130	T-8	Clear	0.11	2 000	1.73 43.90	100/1 000
22070	15T8/CL/240V/E14/STD	SP-61U	15	E14	240	T-8	Clear	0.06	2 000	1.73 43.90	100/1 000
10378	25T8/CL/240V/E14/STD	SP-70U	25	E14	240	T-8	Clear	0.10	2 000	1.73 43.90	100/1 000
22050	5T11/CL/12V/S8.5d/STD	A6413	5	S8.5d	12	T-11	Clear	0.41	4 100	0.79 20.00	100/1 000
50314	5T11/CL/24V/S8.5d/STD	A6423	5	S8.5d	24	T-11	Clear	0.20	1 000	0.79 20.00	100/1 000
22122	40T12/CL/24V/P28s/STD	2450C	40	P28s	24	T-12	Clear	1.66	1 000	1.77 45.00	100/1 000
50712	5T17mm/CL/24V/E14/STD	SP-56U	5	E14	24	T-17	Clear	0.20	2 000	1.38 35.00	100/1 000



T3-BiPin G4



T3.25-Rigid Loop



T3.25-S8.5d



T3.25-Wedge



T5-Wedge



Maglite-BiPin

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Shape	Finish	Amps (A)	Average life (hrs)	LCL (in.) (mm)		Case qty (inner/master)
XENON												
22089	X10T3/CL/12V/0.8333A/G4/STD	N/A	10	BiPin G4	12	T-3	Clear	0.83	10 000	1.14	29.00	10/1 000
55046	X20T3/CL/12V/1.667A/G4/STD	N/A	20	BiPin G4	12	T-3	Clear	1.67	5 000	1.14	29.00	10/1 000
22092	X20T3/F/12V/1.667A/G4/STD	N/A	20	BiPin G4	12	T-3	Frost	1.67	5 000	1.06	26.80	10/1 000
22103	X10T3/CL/24V/0.417A/G4/STD	N/A	10	BiPin G4	24	T-3	Clear	0.42	10 000	1.02	25.80	10/1 000
22099	X20T3/CL/24V/0.8333A/G4/STD	N/A	20	BiPin G4	24	T-3	Clear	0.83	5 000	1.14	29.00	10/1 000
22117	X5T3.25/CL/12V/0.417A/RL/STD	N/A	5	Rigid Loop	12	T-3.25	Clear	0.42	20 000	0.85	21.53	10/1 000
22104	X5T3.25/F/12V/0.417A/RL/STD	N/A	5	Rigid Loop	12	T-3.25	Frost	0.42	20 000	0.84	21.39	10/1 000
22108	X10T3.25/CL/12V/0.8333A/RL/STD	N/A	10	Rigid Loop	12	T-3.25	Clear	0.83	20 000	0.84	21.28	10/1 000
22088	X5T3.25/F/24V/0.208A/RL/STD	N/A	5	Rigid Loop	24	T-3.25	Frost	0.21	20 000	N/A	N/A	10/1 000
22082	X5T3.25/CL/12V/S8.5D/STD	N/A	5	S8.5d	12	T-3.25	Clear	0.42	20 000	N/A	N/A	10/1 000
22084	X5T3.25/F/12V/S8.5D/STD	N/A	5	S8.5d	12	T-3.25	Frost	0.42	20 000	0.64	16.28	10/1 000
22093	X10T3.25/F/12V/S8.5D/STD	N/A	10	S8.5d	12	T-3.25	Frost	0.83	20 000	0.83	21.20	10/1 000
22083	X5T3.25/CL/24V/S8.5D/STD	N/A	5	S8.5d	24	T-3.25	Clear	0.21	15 000	N/A	N/A	10/1 000
22085	X5T3.25/F/24V/S8.5D/STD	N/A	5	S8.5d	24	T-3.25	Frost	0.21	15 000	N/A	N/A	10/1 000
22091	X10T3.25/CL/24V/S8.5D/STD	N/A	10	S8.5d	24	T-3.25	Clear	0.42	10 000	N/A	N/A	10/1 000
22094	X3T3.25/CL/12V/0.24A/WDG/STD	N/A	3	Wedge	12	T-3.25	Clear	0.24	20 000	0.82	20.79	10/1 000
22086	X5T3.25/CL/12V/0.37A/WDG/STD	N/A	5	Wedge	12	T-3.25	Clear	0.37	10 000	0.63	16.00	10/1 000
22079	X12V10W/T3.25/CL/W/STD	N/A	10	Wedge	12	T-3.25	Clear	0.84	10 000	0.63	16.00	10/1 000
22095	X5T3.25/CL/24V/0.214A/WDG/STD	N/A	5	Wedge	24	T-3.25	Clear	0.21	10 000	0.63	16.00	10/1 000
22097	X18T5/CL/12V/1.4A/WDG/STD	N/A	18	Wedge	12	T-5	Clear	1.40	10 000	1.06	27.00	10/1 000
Maglite												
13865	LM2A001 MAG-LITE BULB/2P	LM2A001	0.9	BiPin	N/A	N/A	Clear	N/A	5.5	0.54	13.63	2/24