


# #120 Side Beam Bracket

**Finish:** Bare Metal, Zinc Plated, Hot Dipped Galvanized

**Material:** Carbon Steel  
Stainless Steel 304SS & 316SS

**Approvals:** Complies with MSS SP-58 and SP-69 (Type 34).

**Recommended:** Designed to be fastened to side of joist in order to support a hanger rod.



| SIZE | SPECIFICATION DATA |        |        | MATERIAL     | RECOM.<br>MAX. LOAD<br>(LBS) | APP'X WT.<br>PER 100<br>(LBS) | PC'S<br>PER<br>PKG. |
|------|--------------------|--------|--------|--------------|------------------------------|-------------------------------|---------------------|
|      | Hole Size A        | B      | C      |              |                              |                               |                     |
| 3/8  | 7/16               | 2 1/16 | 1 5/16 | 3/16 x 1 1/2 | 300                          | 23                            | 100                 |
| 1/2  | 9/16               | 2 1/8  | 1 3/8  | 1/4 x 1 1/2  | 560                          | 33                            | 100                 |
| 5/8  | 11/16              | 2 3/4  | 1 5/8  | 3/8 x 2 1/2  | 900                          | 113                           | 50                  |
| 3/4  | 13/16              | 3 1/4  | 2 3/16 | 3/8 x 2 1/2  | 900                          | 139                           | 50                  |

**TAYLOR walraven**

QWI 4.3.1 Issue Date Jul/21 Rev.6

Note: when referencing a printed copy of this specification page, please insure it is the latest version as found on our website at [www.taylorassociates.com](http://www.taylorassociates.com)

For more information, please contact Customer Service at 1-800-263-8652