



Residential Combustion Analyzer

KANE258

Residential Combustion Analyzer



Functions

- Measures: Flue temperature, Inlet temperature (Internal & External Sensor), CO, CO₂
- Calculates: O₂, CO/CO₂, Efficiency (Nett or Gross), Excess Air, Losses
- Low flow detection

Features

- Large 6 line display
- EOS Technology
- NO_x Filtered
- Water Trap Indication
- High Altitude Compensation
- Up to 6 year warranty with annual recertification

Includes

- Rechargeable batteries 3 (AA)
- USB Charging cable (WIR00067)
- Quick Start Guide



Residential Combustion Analyzer

KANE258

Specifications

Temperature Measurement

Parameter	Range	Resolution	Accuracy
Flue Temperature	32° to 1112°F (0° to 600°C)	0.1°F (0.1°C)	±1.0°F (0.5°C)
Inlet Temperature (Internal Sensor)	32° to 112°F (0° to 50°C)	0.1°F (0.1°C)	±2°F (1°C)
Inlet Temperature (External Sensor)	32° to 1112°F (0° to 600°C)	0.1°F (0.1°C)	±1.0°F (0.5°C)

Flue Gas Measurement

Parameter	Range	Resolution	Accuracy
Carbon Monoxide	0 to 2000 ppm	1 ppm	±3 ppm or ±5% rdg (whichever is greater)
Carbon Dioxide	0 to 20%	0.1%	±0.3% volume

Calculations

Parameter	Range	Resolution	Accuracy
Oxygen	0 to 21%	0.1%	±0.3% volume
Efficiency (Net or Gross)	0 to 99.9%	0.1%	±1% rdg
Excess Air	0 to 119.9%	0.1%	±0.2% rdg

Pre- Programmed Fuels	Natural Gas, Propane, LPG, Light Oil, Heavy Oil, Bio Oil, Pellets
-----------------------	---

Battery Life	>8 hours (continuous with pump on)
--------------	------------------------------------

Certification	The KANE258 is TUV-tested and certified to EN 50379, Parts 1-3 in accordance to 1st German Federal Emission Control Ordinance (BimSchV)
---------------	---

Operating Conditions

Temperature	32° to 113°F (0° to 45°C)
Humidity	15% to 90% R.H.

Storage Temperature	0° to 113°F (-18° to 50°C)
Power Supply	Rechargeable Batteries, USB Charging

Dimensions

Dimensions	8.54" x 4.18" x 1.86"
Weight	1 lb., 5.1 oz.

KANE258



Made in
UNITED KINGDOM

KANE258KIT



Made in
UNITED KINGDOM