WaterGroup®
Professional Treatment Solutions

ECONO FLO CABINET SPECIFICATION SHEET

Water Softener

Reliable, Affordable, Compact Size

WARRANTY 5 yr WARRANTY
CONTROL VALVE

WARRANTY 10 yr WARRANTY
PRESSURE TANK

The Econo Flo cabinet softener is perfect for homeowners looking for a reliable water softener that saves space. Third-party certified to provide soft water throughout the home, the Econo Flo is known for its long-lasting performance.

KEY FEATURES

OUTSTANDING VALUE: Simple electronics for the same price as mechanical metered units.

ESSENTIAL FEATURES: Adjustable cycle times and optional regeneration modes (meter immediate, meter delayed, meter override, calendar clock modes).

RELIABLE PERFORMANCE: 5-year control valve and 10-year pressure tank warranty.

CABINET FEATURES: Cabinet comes with safety float and air check.

VALVE FEATURES

SIMPLE ELECTRONICS
Just set time of day, hardness and number of people.

OPTIONAL REGENERATION MODES
Meter immediate, meter delayed, meter override, calendar clock modes.

48-HOUR PROGRAMMING MEMORY Automatic programming restore for up to 48 hours during power loss.

3/4" 90-DEGREE ELBOWS
Included for easy installation.

TIMESAVING QUICK CONNECT FITTINGS & PRE-INSTALLED BYPASS
Quick connect fittings on bypass, drain line (10' included), brine line and power cord, for easier, faster installations.

NSF COMPONENT

USES UP TO 50% LESS SALT & 28% LESS WATER

LEAD FREE UPC C ®

IAPMO R&T Certified to NSF/ANSI 44, 372 and CSA B483.1.

Technical Specifications

QUICK LINKS

Homeowner's Manual

Installation Guide

Maintenance Guide

Trouble Shooting Guide

Parts Breakdown

Programming Guide

Warranty Sheet

PROFESSIONALLY ENGINEERED FOR PERFORMANCE

MODEL NUMBER	EFC-100
Item Number	82118
CAPACITY (GRAINS)	
@ 10 lbs/Cubic Feet	26,500
@ 6 lbs/Cubic Feet Factory Setting	**22,000**
@ 3 lbs/Cubic Feet	14,000
Service Flow Rate	10.0 US gpm
Backwash Flow Rate	2.4 US gpm
Total Resin (Cubic Feet)	1.0 ft^3
Salt Storage Capacity	225 lbs
Shipping Weight	110 lbs
Regeneration Type	DOWNFLOW (COCURRENT)
Plumbing Connections	INCLUDES 3/4" 90° NPT ELBOWS
Resin Type	AQUAFINE® 8% CATION EXCHANGE RESIN
Electrical Requirements	INPUT 120V 60 Hz - OUTPUT 12V 650mA
Water Temperature Limits	MIN 40° - MAX 110° F (4° - 43° C)
Water Pressure Limits	MIN 30 - MAX 125 PSI (207 - 862 KPA)

DIMENSIONS

EFC-100
13.8" X 23.6" X 34.5"