

EP-PLV LED LAMP

ecoLEDTM
A DIVISION OF **ecopower**

FEATURES

- 360° light dispersion & 270° rotatable socket options
- Instant-start, no flickering, no humming
- 6w replaces 13w CFL
- 8w replaces 18w CFL
- 11w replaces 26w CFL



Vertical Mounting Version



G24 POT LIGHT LED LAMP. 6, 8 and 11 watt. Numerous base choices G24D / G24Q / GX24Q / GX23 / G23 / GU24 / E26. Changes out in seconds, lasts for years

TECHNICAL SPECIFICATIONS		OPTICAL & PERFORMANCE SPECIFICATIONS	
Housing	6060 Aluminum and hardened plastic	Lumen Output	6w: 560-620L 8w: 790-850L 11w: 1180-1270L
Finish	As shown	CRI	>83
Ingress Protection	IP40	Lens	Phosphor/Clear
Mounting	G24D / G24Q / GX24Q / GX23 / G23 / GU24 / E26	Beam Angles	120° 180° 360° options
Applications	Pots, hanging fixtures	L70	>50,000 hours
Dimensions	9watt: 127mm x 35mm x 35mm 11watt: 139mm x 35mm x 35mm	LM80	45°C 9000 hours 99%
		LM79	Up to 100 lumens per watt
		Certifications	Approved to CSA and UL standard E365384, CE & ROHS
ELECTRICAL SPECIFICATIONS			
Lighting Source	2835 SMD LED's		
Available Wattages	6w / 8w / 11w		
Power Factor	>0.9		
Ambient temperature	-25° to 40°C		
Available Voltages	100-277v		

info@ecopowerinc.com | ecoled.ecopowerinc.com | 1.800.564.8086



A Canadian
Manufacturer

Warranty is only valid based on fixtures operating for 12 hours or less per day.

©2019 Ecopower Inc. All rights reserved.
REV-0724.19-144912

DIMENSIONS CHART

W	L	D
6w	4.7"	2.2"
8w	4.7"	2.2"
11w	4.7"	2.2"

DIMENSIONS & BASES CHART

BEAM	WATTAGE	BASES	LENGTH W/ DIFFERENT BASES
HORIZONTAL	6W	G23/GX23	126mm
		G24/G24Q/G24D	120mm
		GU24	114mm
	8W	E26	128mm
		G23/GX23	126mm
		G24/G24Q/G24D	120mm
	11W	GU24	114mm
		E26	128mm
		G23/GX23	126mm
		G24/G24Q/G24D	120mm
		GU24	114mm
		E26	128mm

AVAILABLE MODELS

EP-PLV-WW-6W-V4-G24Q
 EP-PLV-WW-11W-V4-E26
 EP-PLV-N2-6W-V4-G23-L2
 EP-PLV-CW-82-V4-GU24
 EP-PLV-CW-11W-V4-GX24Q-4
 EP-PLV-11W-NW-V4-GX23
 EP-PLV-11W-CW-V4-G24Q

BASE SELECTION GUIDE



G23



GX23



G24D



G24Q



E26



GU24