

BL3IC

3" Miniature Low Voltage IC Housing


LAMP WATTAGE: (1) MAXIMUM 12V 50W MR16

Catalog Number:

Project Name:

Type:

Note:



DESCRIPTION

Small aperture, low voltage, thermally protected IC rated, specification grade recessed housing designed for new construction. Accommodates up to 50W MR16 lamps. Furnished with preinstalled adjustable bar hangers. Junction box is provided with four 1/2" KOs, one 3/4" KO and four Romex knockouts with strain relief.

SPECIFICATION

A. OUTER HOUSING - Die-formed aluminum construction for maximum heat dissipating air chamber on top of the housing. Junction box could be accessed from inside and outside housing.


B. INNER HOUSING - Deep-drawn single piece aluminum construction for maximum heat dissipation and rust protection. Adjusts vertically in plaster frame to accommodate 1/2" to 1-3/8" ceiling.

C. TRANSFORMER - Enhanced in heat dissipating cover, to provide noise free operation. Attached to junction box cover so it may be serviced from below the ceiling. Thermally protected.

- **M**-Class H dimming magnetic transformer.
- **E**-Class II dimming electronic transformer (LighTech part #LET 75 BF)
- **TOR**-Class H dimming toroidal transformer, providing 35% more lumens than traditional transformers. Constructed of M3 grade silicone steel. (Must use dimmers rated for electromagnetic transformer)

D. BAR HANGERS - Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span and can be shortened for 12" joists. They are designed to be hammered directly without using nails or screws and could be fit onto T-Bar spline for easy installation and quick alignment.

E. JUNCTION BOX - through-branch circuit wiring and has four 1/2" KOs, one 3/4" KO and four Romex knockouts with true pry-out slots and strain clamps.



FEATURES

- Integral low voltage transformer to prolong lamp life and increase lighting quality.
- Thermally Protected IC housing.
- Designed for accent and task lighting applications.
- Wire through junction box.
- Preinstalled adjustable bar hangers.
- Dependable, favorable design and effortless installation.
- 7-1/4" height allows use in 2" x 8" joist construction.
- Special screw on the frame locks bar hangers in place which prevents the housing from any movement once installed.

OPTIONS

1. AIR-SHUT

- Gasket to prevent air flow from heated or air conditioned spaces.
- Meets all national air flow requirements.



BL3IC - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE	BALLAST	TRIM TYPE				BAFFLE	REFLECTOR	TRIM RING	MR 16 LENS FILTER	
<input type="checkbox"/> 20W	<input type="checkbox"/> (M) Magnetic	<input type="checkbox"/> B1351 ¹	<input type="checkbox"/> B1372 ²	<input type="checkbox"/> B1395	<input type="checkbox"/> B1303	<input type="checkbox"/> W	<input type="checkbox"/> CL	<input type="checkbox"/> WH	<input type="checkbox"/> BP8MR16-BL (Blue)	<input type="checkbox"/> BP8MR16-FR (Frosted)
<input type="checkbox"/> 35W	<input type="checkbox"/> (E) Electronic	<input type="checkbox"/> B1353 ¹	<input type="checkbox"/> B1374 ²	<input type="checkbox"/> B1390	<input type="checkbox"/> B1314	<input type="checkbox"/> P	<input type="checkbox"/> RG	<input type="checkbox"/> BK	<input type="checkbox"/> BP8MR16-GR (Green)	<input type="checkbox"/> BP8MR16-SP (Spread)
<input type="checkbox"/> 50W	<input type="checkbox"/> (TOR) Toroidal*	<input type="checkbox"/> B1354 ¹	<input type="checkbox"/> B1375 ²	<input type="checkbox"/> B1391	<input type="checkbox"/> B1315	<input type="checkbox"/> SN	<input type="checkbox"/> W	<input type="checkbox"/> SN	<input type="checkbox"/> BP8MR16-PI (Pink)	<input type="checkbox"/> BP8MR16-SF (Soft Focus)
	VOLTAGE	<input type="checkbox"/> B1355 ¹	<input type="checkbox"/> B1376 ²	<input type="checkbox"/> B1320	<input type="checkbox"/> B1362	<input type="checkbox"/> CP	<input type="checkbox"/> MB	<input type="checkbox"/> CP	<input type="checkbox"/> BP8MR16-PU (Purple)	<input type="checkbox"/> BP8MR16-HC (Honey Comb)
	<input type="checkbox"/> 120	<input type="checkbox"/> B1356 ¹	<input type="checkbox"/> B1396	<input type="checkbox"/> B1325	<input type="checkbox"/> B1352	<input type="checkbox"/> BZ	<input type="checkbox"/> BZ	<input type="checkbox"/> CH	<input type="checkbox"/> BP8MR16-DL (Day Light)	<input type="checkbox"/> BP8MR16-LI (Linear)
	<input type="checkbox"/> 277	<input type="checkbox"/> B1357 ¹	<input type="checkbox"/> B1378	<input type="checkbox"/> B1324	<input type="checkbox"/> B1306		<input type="checkbox"/> CP	<input type="checkbox"/> PB	<input type="checkbox"/> BP8MR16-YE (Yellow)	<input type="checkbox"/> BP8MR16-SOL (Solite)
	OPTION	<input type="checkbox"/> B1358 ¹	<input type="checkbox"/> B1379	<input type="checkbox"/> B1301	<input type="checkbox"/> B1312			<input type="checkbox"/> BZ	<input type="checkbox"/> BP8MR16-AM (Amber)	<input type="checkbox"/> BP8MR16-CL (Clear)
	<input type="checkbox"/> AT (Air-Shut)	<input type="checkbox"/> B1359 ¹	<input type="checkbox"/> B1383	<input type="checkbox"/> B1302	<input type="checkbox"/> B1368			<input type="checkbox"/> SHZ	<input type="checkbox"/> BP8MR16-OR (Orange)	<input type="checkbox"/> BP8MR16-UV (Ultraviolet)
		<input type="checkbox"/> B1360 ¹	<input type="checkbox"/> B1380	<input type="checkbox"/> B1316	<input type="checkbox"/> B1304				<input type="checkbox"/> BP8MR16-RE (Red)	
		<input type="checkbox"/> B1370 ²	<input type="checkbox"/> B1384	<input type="checkbox"/> B1326	<input type="checkbox"/> B1377					
		<input type="checkbox"/> B1371 ²	<input type="checkbox"/> B1386	<input type="checkbox"/> B1366	<input type="checkbox"/> B1313					

*Toroidal = Available only in 120V

1 = CH - Chrome finished • 2 = SS - Stainless Steel finished

Specifications:

BL3IC

WATT BALLAST VOLTAGE OPTION TRIM TYPE BAFFLE REFLECTOR TRIM/RING FILTER (1) FILTER (2)

BAFFLE	REFLECTOR	TRIM/RING
W White	CL Chrome	WH White
P Black	RG Gold	BK Black
SN Satin Nickel	W White	SN Satin Nickel
CP Copper	MB Black	CP Copper
BZ Bronze	BZ Bronze	CH Chrome
	CP Copper	PB Polish Brass
	SN Satin Nickel	BZ Bronze
	SHZ Satin Haze	

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Submittal form is available @ www.iuseelite.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

REV: ELITE LIGHTING-SPEC-05-24-2011

3" Low Voltage Trims

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:

Project Name:

Type:

Note:



<p>B1351CH RUBY I</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1353CH RUBY II</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1354CH SAPPHIRE I</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1355CH SAPPHIRE II</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>
<p>B1356CH EMERALD I</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1357CH EMERALD II</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1358CH TOPAZ I</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1359CH TOPAZ II</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>
<p>B1360CH ONYX</p>  <p>O.D.: 3-7/8" FINISH TRIM: CH (CHROME)</p>	<p>B1370SS ADJ. STAINLESS STEEL GIMBAL TRIM</p>  <p>O.D.: 3-7/8" FINISH TRIM: SS (STAINLESS STEEL)</p>	<p>B1371SS STAINLESS STEEL LENSED TRIM</p>  <p>O.D.: 3-7/8" FINISH TRIM: SS (STAINLESS STEEL)</p> <p>FOR WET LOCATION</p>	<p>B1372SS STAINLESS STEEL EYEBALL TRIM</p>  <p>O.D.: 3-7/8" FINISH TRIM: SS (STAINLESS STEEL)</p>
<p>B1374SS ADJ. STAINLESS STEEL SQUARE GIMBAL TRIM</p>  <p>O.D.: 3-7/8" FINISH TRIM: SS (STAINLESS STEEL)</p>	<p>B1375SS STAINLESS STEEL SQUARE EYEBALL TRIM</p>  <p>O.D.: 3-7/8" FINISH TRIM: SS (STAINLESS STEEL)</p> <p>FOR WET LOCATION</p>	<p>B1376SS ADJ. STAINLESS STEEL SQUARE EYEBALL TRIM</p>  <p>O.D.: 3-7/8" FINISH TRIM: SS (STAINLESS STEEL)</p>	<p>B1396SN SQUARE BAFFLE W/ SQUARE TRIM RING</p>  <p>TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ</p>

3"

Low Voltage Trims

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:


Project Name:

Type:

Note:




B1378SN-SN
STEPPED BAFFLE (35° TILT)




AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ

B1379CL-WH
REFLECTOR (35° TILT)



AVAILABLE COLOR COMBINATIONS:
CL-WH, CL-SN, RG-WH, MB-WH, W-WH, MB-BK, RG-PB, SN-SN, CL-CH, CP-CP, CP-WH, SN-WH

B1383WH
SLOT APERTURE (35° TILT)




TRIM FINISH:
WH, BK, SN, CP, CH, PB, BZ

B1384P-WH
FULLY ADJUSTABLE W/ BAFFLE




(35° TILT, 359° ROTATION)




AVAILABLE COLOR COMBINATIONS:
W-WH, P-WH, P-BK, CP-CP, SN-SN, BZ-BZ

B1380WH
FULLY ADJUSTABLE (35° TILT, 359° ROT.)




TRIM FINISH:
WH, BK, SN, CP, CH, PB, BZ

B1386WH
FULLY ADJUSTABLE (75° TILT, 359° ROT.)



TRIM FINISH:
WH, BK, SN, CP, CH, PB, BZ

B1390WH-PEACH
METROPOLITAN ICE LITE




TRIM FINISH:
WH, BK, SN, CP, CH, PB

GLASS FINISH:
BLUE, PEACH, GREEN, CLEAR, AMBER, FROSTED

B1395CL-SN
SEMI-FROSTED SHOWER TRIM




FOR WET LOCATION



REFLECTOR FINISH:
CL


RING FINISH:
WH, BK, SN, CP, CH, PB, BZ

B1391P-WH
PINHOLE WITH BAFFLE




AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ

B1301CP-CP
STEPPED BAFFLE




AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ

B1302CP-WH
REFLECTOR




AVAILABLE COLOR COMBINATIONS:
CP-CP, CP-WH, W-WH, RG-WH, SN-SN, SN-WH, MB-WH, CL-WH, MB-BK, RG-PB, CL-CH, CL-SN

B1316CL-WH
REFLECTOR (35° TILT)




AVAILABLE COLOR COMBINATIONS:
CL-WH, CL-SN, CL-PB

B1326CL-WH
THE ILLUMINATOR II




AVAILABLE COLOR COMBINATIONS:
CL-WH, CL-SN, CL-BK, MB-BK

B1366CL-WH
THE ILLUMINATOR




AVAILABLE COLOR COMBINATIONS:
CL-WH, CL-SN, CL-BK, MB-BK

B1303WH
SLOT APERTURE



TRIM FINISH:
WH, BK, SN, CP, CH, PB, BZ

B1314P-WH
PINHOLE WITH BAFFLE



AVAILABLE COLOR COMBINATIONS:
CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ



Submittal form is available @ www.iuseelite.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

REV: MAXLUME-SPEC-05-26-2011

3" Low Voltage Trims

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)


Catalog Number:

Project Name:

Type:

Note:



<p>B1315RG-WH PINHOLE WITH REFLECTOR</p>  <p>AVAILABLE COLOR COMBINATIONS: CL-WH, CL-SN, RG-WH, MB-WH, W-WH, CP-CP</p>	<p>B1362WH SHOWER TRIM W/ FROSTED LENS</p>  <p>TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ</p>	<p>B1352CL-WH SHOWER TRIM WITH REFLECTOR</p>  <p>AVAILABLE COLOR COMBINATIONS: CL-WH, CL-CH, RG-WH, RG-PB</p>	<p>B1368W-WH FULLY ADJUSTABLE W/ BAFFLE (35° TILT)</p>  <p>AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK</p>
<p>B1312SN FULLY ADJUSTABLE (35° TILT)</p>  <p>TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ</p>	<p>B1304W-WH EYEBALL W/ BAFFLE (47° TILT)</p>  <p>AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK</p>	<p>B1306WH FULLY ADJUSTABLE (75° TILT, 359° ROT>)</p>  <p>TRIM FINISH: WH, BK, SN, CP, CH, PB, BZ</p>	<p>B1313P-SN PULL DOWN ADJUSTABLE</p>  <p>AVAILABLE COLOR COMBINATIONS: CP-CP, SN-SN, W-WH, P-WH, P-BK, BZ-BZ, P-SN</p>
<p>B1377CL-WH CROSSBLADE REFLECTOR</p>  <p>AVAILABLE COLOR COMBINATION: CL-WH</p>	<p>B1320WH-CRYSTAL METROPOLITAN MOON LITE</p>  <p>RING FINISH: WH</p> <p>GLASS FINISH: GREEN, BLUE, AMBER, PEACH, FROSTED, CRYSTAL</p>	<p>B1325WH-AMBER METROPOLITAN STEP LITE</p>  <p>RING FINISH: WH</p> <p>GLASS FINISH: GREEN, BLUE, AMBER, PEACH, FROSTED, CRYSTAL</p>	<p>B1324WH-RED METROPOLITAN HONEY LITE</p>  <p>RING FINISH: WH</p> <p>GLASS FINISH: GREEN, BLUE, AMBER, PEACH, FROSTED, CRYSTAL</p>

BAFFLE	REFLECTOR	TRIM RING
W White	CL Chrome	WH White
P Black	RG Gold	BK Black
SN Satin Nickel	W White	SN Satin Nickel
CP Copper	MB Black	CP Copper
BZ Bronze	CP Copper	CH Chrome
	SN Satin Nickel	PB Polish Brass
		BZ Bronze

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



Submittal form is available @ www.iuseelite.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

REV: MAXILUME-SPEC-05-26-2011