

BL4

4" Miniature Low Voltage "Noise-Free" **Non-IC Housing**

LAMP WATTAGE: (1) MAXIMUM 12V 75W MR16









BL4 - ITEM SELECTOR: (Please check the boxes below for the option desired)


	Catalog Number:	
١	Project Name:	Туре:
	Note:	elitë LIGHTING

DESCRIPTION

Small aperture low voltage, thermally protected, specification grade recessed housing. For new construction. Non-insulated ceilings or where insulation can be kept 3" from the housing. Accommodates up to 75W MR16 lamps. Furnished with preinstalled adjustable bar hangers. Junction box is provided with four ½" KOs, one ¾" KO and four Romex knockouts with strain relief.

A. HOUSING - High temperature painted 22 gauge deep drawn single piece housing. Adjusts vertically in plaster frame to accommodate 1/2" to 1-3/8" ceiling. Accommodates lamps up to 50W depending on trim used.

- B. TRANSFORMER Enhanced in heat dissipating cover, to provide noise free operation. Attached to junction box cover so it may be serviced from below the ceiling. Thermally protected.
- M-Class H dimming magnetic transformer.
- E-Class II dimming electronic transformer (LighTech part #LET 75 BF)
- . TOR-Class H dimming toroidal transformer, providing 35% more lumens than traditional transformers. Constructed of M3 grade silicone steel.(Must use dimmers rated for electromagnetic transformer)
- C. BAR HANGERS Preinstalled bar hangers allow housing to be positioned and locked at any point within a 24" joist span and can be shortened for 12" joists. They contain a double-headed real nail for secure attachment into the joist. Bar hanger nails are installed on a 20° downward angle for better contact, and the 90° pivoting mounting plate makes installation fast and accurate. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting methods if necessary.
- D. JUNCTION BOX UL listed for through-branch circuit wiring and has four ½" KOs, one 34" KO and four Romex knockouts with true pry-out slots and strain clamps.



FEATURES

- · Integral low voltage magnetic transformer to prolong lamp life and increase lighting quality.
- . Thermally Protected Non-IC housing
- · Designed for accent and task lighting applications.
- · Wire through junction box.
- · Preinstalled adjustable bar hangers.
- · Dependable, favorable design and effortless installation.
- 5-1/2" height allows use in 2" x 6" joist construction.
- Special screw on the frame locks bar hangers in place which prevents the housing from any movement once installed.

OPTIONS

1. AIR-SHUT

- · Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.

WATTAGE	TRIM TYPE						BAFFLE	TRIM RING	MR 16 LENS FILTER	ł			
□ 20W	□ B1451 ¹	☐ B1476 ²	□ B1494	□ B1425	□ B1439	□ B1411	□ W	□ WH	☐ BP8MR16-BL (Bli	ue)		BP8MR16-FR	(Frosted)
□ 35W	☐ B1453 1	☐ B1478	□ B1496	□ B1469	□ B1463	□ B1416	□ P	□ BK	☐ BP8MR16-GR (Gr	reen)		BP8MR16-SP	(Spread)
□ 50W	☐ B1454 1	☐ B1488	□ B1483	□ B1442	☐ B1464	☐ B1407	□ SN	□ SN	☐ BP8MR16-PI (Pin	ık)		BP8MR16-SF	(Soft Focus)
□ 75W	☐ B1455 1	□ B1486	□ B1432	□ B1420	□ B1465	□ B1414	□ CP	□ CP	☐ BP8MR16-PU (Pu	ırple)		BP8MR16-HC	(Honey Comb)
BALLAST	☐ B1456 1	□ B1489	□ B1434	☐ B1422	□ B1466	☐ B1415	□ BZ	□ CH	☐ BP8MR16-DL (Da	ay Light)		BP8MR16-LI	(Linear)
☐ (M) Magnetic	☐ B1457 1	□ B1479	□ B1435	□ B1413	□ B1467	□ B1404	REFLECTOR	□ PB	☐ BP8MR16-YE (Ye	llow)		BP8MR16-S0	L (Solite)
(E) Electronic	☐ B1458 1	☐ B1487	□ B1484	□ B1426	☐ B1408	☐ B1418	□ CL	□ BZ	☐ BP8MR16-AM (A	mber)		BP8MR16-CL	(Clear)
☐ (TOR) Toroidal ³	□ B1459 1	☐ B1485	□ B1436	□ B1427	□ B1406	□ B1419	□ RG	☐ CH 1	☐ BP8MR16-OR (O	range)		BP8MR16-UV	(Ultraviolet)
VOLTAGE	☐ B1460 1	□ B1491	□ B1440	☐ B1430	☐ B1401	□ B1433	□ W	☐ SS ²	☐ BP8MR16-RE (Re	ed)			
□ 120	□ B1470 ²	□ B1480	□ B1441	□ B1431	□ B1402	□ B1417	□ MB						
277	□ B1471 ²	□ B1495	□ B1421	□ B1462	□ B1412	□ B1477	□ BZ						
OPTION	□ B1472 ²	□ B1490	□ B1424	□ B1452	□ B1468		□ CP						
☐ AT (Air-Shut)	☐ B1474 ²	□ B1492	□ B1423	□ B1437	□ B1461		□ SN			BAFFLE W W		REFLECTOR CL Chrome	TRIM/RING WH White
	☐ B1475 ²	□ B1481	□ B1409	□ B1438	□ B1403		□ SHZ			P Bla	ick	RG Gold W White	BK Black SN Satin Nick
Specifications:				1=	CH - Chrome finish	ned • 2 = SS - Stair	lless Steel finished •	3 = TOR -Toroid	al available only in 120V	CP Co	pper onze	MB Black BZ Bronze CP Copper SN Satin Nicke SHZ Satin Haze	CP Copper CH Chrome PB Polish Bra
	VATT BAL	LAST VOL	TAGE OPT	TRIM T	TYPE BAFFLE	REFLECTOR	TRIM/RING	FILTER (1)	FILTER (2)	*For custos options, pl			plass color and lens

Sample of Catalog Number: BL4-20W-E-B1401-W-WH-BP8MR16-BL

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:					
Project Name:	Туре:				
Note:					

B1451CH RUBY I



0.D.: 4-7/8" FINISH TRIM: CH (CHROME)

B1453CH RUBY II



O.D.: 4-7/8"

FINISH TRIM: CH (CHROME)

B1454CH SAPPHIRE I



O.D.: 4-7/8"

FINISH TRIM: CH (CHROME)

B1455CH SAPPHIRE II



0.D.: 4-7/8"

FINISH TRIM: CH (CHROME)

B1456CH EMERALD I



0.D.: 4-7/8" **FINISH TRIM:** CH (CHROME) B1457CH EMERALD II



O.D.: 4-7/8"

FINISH TRIM: CH (CHROME)

B1458CH TOPAZ I



O.D.: 4-7/8"

FINISH TRIM: CH (CHROME)

B1459CH TOPAZ II



0.D.: 4-7/8" FINISH TRIM: CH (CHROME)

B1460CH ONYX



0.D.: 4-7/8" **FINISH TRIM:** CH (CHROME) B1470SS ADJ. STAINLESS STEEL GIMBAL TRIM



0.D.: 4-7/8" **FINISH TRIM:** SS (STAINLESS STEEL) B1471SS STAINLESS STEEL LENSED TRIM



0.D.: 4-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

B1472SS STAINLESS STEEL EYEBALL TRIM



0.D.: 4-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

SQUARE BAFFLE W/ SQUARE TRIM RING

B1474SS

ADJ. STAINLESS STEEL SQUARE GIMBAL TRIM



O.D.: 4-7/8"

FINISH TRIM: SS (STAINLESS STEEL)

B1475SS

STAINLESS STEEL SQUARE EYEBALL TRIM



WET

0.D.: 4-7/8" **FINISH TRIM:** SS (STAINLESS STEEL)

ADJ. STAINLESS STEEL SQUARE EYEBALL TRIM



0.D.: 4-7/8"

FINISH TRIM: SS (STAINLESS STEEL)



TRIM FINISH:

WH, BK, SN, CP, CH, PB, BZ



(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:	
Project Name:	Туре:
Note:	elite

B1478SN-SN STEPPED BAFFLE (35° TILT)



B1479CL-WH REFLECTOR (35° TILT)



B1494WH-BLUE DESIGNER SQUARE STEP LITE



B1485W-WH EYEBALL (47° TILT)



B1488CP SURFACE ADJUSTABLE (90° TILT, 359° ROT)



B1486WH FULLY ADJUSTABLE (75° TILT, 359° ROT)



B1489W-WH ADJ. PINHOLE W/ BAFFLE (35° TILT)



B1487WH ADJUSTABLE SPOT (40° TILT)



B1483WH SLOT APERTURE (35° TILT)



B1480WH FULLY ADJUSTABLE (35° TILT, 359° ROT.)



B1484P-WH FULLY ADJ. W/ BAFFLE (35° TILT, 359° ROT.)



B1481WH ADJUSTABLE GIMBAL (40° TILT)



B1495CL-SN SEMI-FROSTED SHOWER TRIM




B1491P-WH PINHOLE WITH BAFFLE



B1492WH-BLUE METROPOLITAN ICE LITE



B1490WH-PEACH METROPOLITAN ICE LITE





Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977 Specifications and Dimensions subject to change without notice.

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)


Catalog Number:	
Project Name:	Туре:
Note:	elite

B1401CP-CP STEPPED BAFFLE



BAFFLE FINISH: W, P, SN, CP, BZ

RING FINISH: WH, BK, SN, CP, CH, PB, BZ




B1402CP-WH REFLECTOR (35° TILT)



REFLECTOR FINISH: CL, RG, W, MB, CP, SN, BZ

RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B1463RG-WH ADJUSTABLE ANGLE-CUT REFLECTOR



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

RING FINISH: WH, BK, SN, CP, CH, PB

B1467CL-WH







RING FINISH: WH, BK, SN, CP, CH, PB

B1465CL-WH **ADJUSTABLE ANGLE-CUT PINHOLE**



REFLECTOR FINISH: CL, RG, W, MB, CP, SN

RING FINISH:

B1466CL-WH





AVAILABLE COLOR COMBINATIONS: CL-WH, CP-CP, MB-BK RG-WH, SN-SN, W-WH





REFLECTOR FINISH:

TRIM COVER:



CL, RG, W, MB, CP, SN

REFLECTOR WALL WASH





ONE PIECE SLOT APERTURE (35° TILT)



B1416P-WH **BAFFLE WALL WASH**



BAFFLE FINISH: W, P, SN, CP, BZ

WALL WASH COVER:



REFELCTOR FINISH: CL, RG, W, MB, CP, SN WALL WASH COVER:



B1414W-WH PINHOLE WITH BAFFLE



B1415CL-WH PINHOLE WITH REFLECTOR



B1404P-WH EYEBALL (47° TILT)



ADJ.PINHOLE W/ EYEBALL (35° TILT)



FULLY ADJUSTABLE (35° TILT, 359° ROT.)





Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:	
Project Name:	Туре:
Note:	elite

B1468W-WH

FULLY ADJ. W/ BAFFLE (35° TILT, 359° ROT.)



B1461SN ADJUSTABLE GIMBAL (40° TILT)



B1408WH FULLY ADJUSTABLE (75° TILT, 359° ROT.)



B1406CP SURFACE ADJUSTABLE (90° TILT, 359° ROT.)



B1413P-SN PULL DOWN ADJUSTABLE




B1419BK ADJUSTABLE SPOT (40° TILT)



B1433P-WH Adjustable Pinhole Baffle (15° Tilt)



B1417W-WH METAL STEPPED BAFFLE




B1426CL-WH THE ILLUMINATOR II



B1427CL-WH THE ILLUMINATOR



B1477CL-WH CROSSBLADE REFLECTOR



B1462CL-WH SEMI-FROSTED SHOWER TRIM



B1452CL-WH CLEAR LENS SHOWER TRIM



B1437WH SMOOTH FROST SHOWER LITE



B1438WH DESIGNER POINT SHOWER LITE



B1439WH SMOOTH FROST DOME SHOWER LITE




(LAMP WATTAGE: 75W 12V MR16 / 50W 120V GU10)

Catalog Number:	
Project Name:	Туре:
Note:	elite









B1440WH-PINK **TULIP LITE**



B1441WH-LIME **DESIGNER WALL WASH LITE**



B1424WH-RED **METROPOLITAN HONEY LITE**





GLASS FINISH: CRYSTAL/FROST



B1425WH-AMBER **METROPOLITAN STEP LITE**




B1442WH-PEACH **DESIGNER MOON LITE**



B1431WH **CRYSTAL STRIPE LITE**



R1432WH WALL WASH FROST LITE



B1421WH-FROSTED MINI-STEP LENS LITE



B1423WH-WHITE **METROPOLITAN OPAL LENS LITE**



B1409WH-BLUE **PYRAMID GLASS LITE**



B1469WH-BLUE **DESIGNER STEP LITE**



B1422WH-FROSTED METROPOLITAN ICE LITE



CRYSTAL ROSE LITE



elle lighting

Submittal form is available @ www.iuseelite.com Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.