




ST401



ST402



ST403



APPLICATION:

For concrete use only

BODY:

High-grade die-cast aluminum with 0.3% copper to prevent corrosion in concrete applications. Supplied standard with four 3/4" NPS holes.

FACE PLATE:

High-grade die-cast aluminum

GASKET:

Single-piece molded silicon for wet location

LENS:

Frosted tempered glass

FINISH:

White, Satin Aluminum, and Bronze thermoset powder coat

EXTERNAL LOUVER:

Anodized 45° cut-off louver

REFLECTOR:

High-performance aluminum reflector assembly for superb light output

INSTALLATION:

Two 1/2" NPS wiring holes
Feed-through listed

LISTING:

UL/C-UL for wet location

HOUSING AND FACE PLATE MUST BE ORDERED SEPARATELY.

Ordering Guide > Example: ST4BX-1X15-120-ST401-WH

ST4BX-1X15-120

HOUSING TYPE/WATTAGE

INCANDESCENT

- ST4BX-1X15-120V - 15W T7 DC BAYONET
- ST4BX-1X25-120V - 25W T8 DC BAYONET
- ST4BX-1X18-12V* - 18W T6 DC BAYONET

FACE PLATE

- ST401
- ST402
- ST403

FINISH

- WH - White
- BK - Black
- BZ - Bronze
- SN - Satin Nickel
- AL - Satin Aluminum

***MUST BE USED WITH REMOTE TRANSFORMER**