



510 nVent CADDY EZ Riser



- Recommended for suspending vertical steel pipe risers
- Slotted holes make assembly easy, eliminating loose hardware
- Serrated flange-head bolts eliminate need for wrenches on both bolt and nut
- Conforms with Federal Specification WW-H-171 (Type 8), Manufacturers Standardization Society (MSS) SP-58 (Type 8)



Part Number	Pipe Size	Outer Diameter OD	Hole Size HS	A	B	Static Load F	Certifications
Material: Steel – Finish: Electrogalvanized							
5100050EG	1/2"	0.840"	7/16"	8 1/2"	1"	255 lb	–
5100075EG	3/4"	1.050"	7/16"	9"	1"	255 lb	–
5100100EG	1"	1.315"	7/16"	9"	1"	255 lb	–
5100125EG	1 1/4"	1.660"	7/16"	9 7/16"	1"	255 lb	–
5100150EG	1 1/2"	1.900"	7/16"	9 7/8"	1"	255 lb	–
5100200EG	2"	2.375"	7/16"	10 1/4"	1 3/16"	255 lb	cULus, ITB
5100250EG	2 1/2"	2.875"	7/16"	11"	1 3/16"	390 lb	cULus, ITB
5100300EG	3"	3.500"	7/16"	11 3/4"	1 3/16"	530 lb	cULus, ITB
5100350EG	3 1/2"	4.000"	9/16"	12 5/8"	1 3/16"	670 lb	cULus
5100400EG	4"	4.500"	9/16"	13"	1 1/2"	810 lb	cULus, ITB
5100500EG	5"	5.563"	9/16"	14 1/2"	1 1/2"	1,160 lb	cULus
5100600EG	6"	6.625"	9/16"	16"	2"	1,570 lb	cULus
5100800EG	8"	8.625"	11/16"	18 1/4"	2"	2,500 lb	cULus
5101000EG	10"	10.750"	11/16"	20 5/8"	2"	2,500 lb	–
5101200EG	12"	12.750"	11/16"	22 3/8"	2"	2,700 lb	–
5101400EG	14"	14.000"	11/16"	24 1/8"	2"	2,700 lb	–
5101600EG	16"	16.000"	13/16"	27 7/8"	2 1/2"	2,900 lb	–
5101800EG	18"	18.000"	13/16"	29 13/16"	2 1/2"	2,900 lb	–
5102000EG	20"	20.000"	13/16"	32 1/4"	2 1/2"	2,900 lb	–
5102400EG	24"	24.000"	15/16"	36 1/8"	3"	2,900 lb	–

Part Number	Pipe Size	Outer Diameter OD	Hole Size HS	A	B	Static Load F	Certifications
Material: Steel – Finish: Hot-Dip Galvanized							
5100050HD	1/2"	0.840"	7/16"	8 1/2"	1"	255 lb	–
5100100HD	1"	1.315"	7/16"	9"	1"	255 lb	–
5100125HD	1 1/4"	1.660"	7/16"	9 7/16"	1"	255 lb	–
5100150HD	1 1/2"	1.900"	7/16"	9 7/8"	1"	255 lb	–
5100200HD	2"	2.375"	7/16"	10 1/4"	1 3/16"	255 lb	cULus
5100250HD	2 1/2"	2.875"	7/16"	11"	1 3/16"	390 lb	cULus
5100300HD	3"	3.500"	7/16"	11 3/4"	1 3/16"	530 lb	cULus
5100400HD	4"	4.500"	9/16"	13"	1 1/2"	810 lb	cULus
5100500HD	5"	5.563"	9/16"	14 1/2"	1 1/2"	1,160 lb	cULus
5100600HD	6"	6.625"	9/16"	16"	2"	1,570 lb	cULus
5100800HD	8"	8.625"	11/16"	18 1/4"	2"	2,500 lb	cULus
Material: Stainless Steel 304 [EN 1.4301]							
5100050S4	1/2"	0.840"	7/16"	8 1/2"	1"	255 lb	–
5100075S4	3/4"	1.050"	7/16"	9"	1"	255 lb	–
5100100S4	1"	1.315"	7/16"	9"	1"	255 lb	–
5100125S4	1 1/4"	1.660"	7/16"	9 7/16"	1"	255 lb	–
5100150S4	1 1/2"	1.900"	7/16"	9 7/8"	1"	255 lb	–
5100200S4	2"	2.375"	7/16"	10 1/4"	1 3/16"	255 lb	–
5100250S4	2 1/2"	2.875"	7/16"	11"	1 3/16"	390 lb	–
5100300S4	3"	3.500"	7/16"	11 3/4"	1 3/16"	530 lb	–
5100400S4	4"	4.500"	9/16"	13"	1 1/2"	810 lb	–
5100500S4	5"	5.563"	9/16"	14 1/2"	1 1/2"	1,160 lb	–
5100600S4	6"	6.625"	9/16"	16"	2"	1,570 lb	–
5100800S4	8"	8.625"	11/16"	18 1/4"	2"	2,500 lb	–
5101000S4	10"	10.750"	11/16"	20 5/8"	2"	2,500 lb	–

Clamp is fitted for steel pipe and should be installed below a coupling or shear lug, with bolts torqued to recommended value.

Slotted holes and bolts for pipe sizes up to 12" only.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

