



Residential/Commercial Combustion Analyzer KIT

KANE458SKIT

Residential/Commercial Combustion Analyzer Kit w/Printer



Functions

- Measures: CO (10,000ppm H2 Compensated), CO2, Differential Pressure, Flue and Inlet Temperature
- Calculates: Differential Temperature, Efficiency (Gross, Nett), Excess Air

Features

- LINK to wireless probes (DTHA2)
- Wireless Flow and Return Probes
- H2 Compensated CO sensor (10,000ppm range)
- Over-range protection pump
- NOx filtered CO sensor
- Low Flow Detection
- Room CO test
- Differential Pressure
- Heat Exchanger test
- Protective water trap
- Wireless connection to a Free KANE Printer App & KANE Live (iOS® and Android™ Compatible)
- Up to 6 year warranty with annual recertification



LINK to wireless Flow and Return pipe clamp probes.



Includes

- Flue Probe (CP2)
- IR Thermal Printer (KANEIRP-3)
- Printer Paper Roll (spare) (16646)
- Rechargeable Batteries 3 (AA)
- USB Charging Cable (WIR0067)
- Wireless Pipe Clamp Probes 2 (WPCP2)
- Tubing w/ connector (11000)
- K-Type Thermocouples 2 (ATT29)
- Particle Filter (spare) (17631)
- Carrying Case (AC509)
- Quick Start Guide





Residential/Commercial Combustion Analyzer

KANE458SKIT

Specifications

TEMPERATURE MEASUREMENT

Parameter	Range	Resolution	Accuracy
Flue temperature	32° to 1112°F (0° to 600°C)	0.1°F	+3.6°F +0.3% rdg
Inlet temperature (internal sensor)	32° to 112°F (0° to 50°C)	0.1°F	+1.8°C +0.3% rdg
Inlet temperature (external sensor)	32° to 1112°F (0° to 600°C)	0.1°F	+3.6°F +0.3% rdg

FLUE GAS

Parameter	Range	Resolution	Accuracy
Oxygen	0 to 21%	0.1%	+0.3%
Carbon Monoxide	0 to 100ppm	1ppm	±5ppm
	100 to 400ppm		±20ppm
	400 to 2,000ppm		±5%
	2,000 to 9,999ppm		±10%
Above 10,000ppm purge pump operates		Unspecified	
Carbon Dioxide	0 to 20%	0.1%	0.3% volume
Efficiency (Net or Gross)	0 to 99.9%	0.1%	+1.0% rdg
Efficiency High (C)	0 to 119.9%	0.1%	+1.0% rdg
Excess Air	0 to 250%	0.1%	+0.2% rdg
CO/CO2 ratio	0 to 0.999%	0.0001	+5% rdg

PRESSURE (DIFFERENTIAL)

Parameter	Range	Resolution	Accuracy
Normal range ±80mbar maximum over range without damage is ±400mbar	±32"WC (+80mbar)	Maximum 0.001" WC <9.9999" WC 0.001" WC >10.00" WC (0.001mbar <24.99mbar) (0.1mbar >25mbar)	±0.0002" WC (±0.005mbar)
±0.4" WC (±1mbar)			±0.01" WC (±0.03mbar)
±32"WC (±80mbar)			+3.6°F +0.3% rdg

PRE-PROGRAMMED FUELS	Natural Gas, Propane, Butane, LPG, Light Oils (28/35sec), Wood Pellets, Town Gas, Coke Gas, Gio Oil, Bio Gas
----------------------	--

STORAGE CAPACITY	45 tests
------------------	----------

NITRIC OXIDE SENSOR (optional)	0 to 100ppm Overrange to 1500ppm	1ppm	+ 2ppm <30ppm ¹ +5ppm <100ppm ¹ +5% reading >100ppm
--------------------------------	-------------------------------------	------	---



Independently tested by TUV SUD to EN50379 & EN50543
Use for BS7967, TB143, BS8494, CMDDA1 & COMCAT

KANE458s



Made in
UNITED KINGDOM

KANE458sKIT



Made in
UNITED KINGDOM

KANE458sNO



Made in
UNITED KINGDOM

KANE458sNOKIT



Made in
UNITED KINGDOM

KANE458sOILKIT



Made in
UNITED KINGDOM

KANE458sNOOILKIT



Made in
UNITED KINGDOM