

Job or Customer :	
Location :	
Engineer :	
☐ Complies with Spec ☐ Alternate	Notes :
Contractor :	
HeatLink Rep :	
Submitted By :	Date :
Approved By :	Date :
P.O. Number :	Date :


Description

Solid no lead (Eco) Brass PEX F1960 × MNPT adapters for PEX-a potable water expansion systems.

The use of PEX tubing in a potable hot-water plumbing system with an operating temperature above 140°F (60°C) or system pressure above 80 psig (550 kPaG) or highly aggressive water quality or any combination thereof can significantly reduce the service life of the tubing.

HeatLink requires following the guidelines described in Plastics Pipe Institute TN-53, Guide to Chlorine Resistance Ratings of PEX Pipes and Tubing for Potable Water Applications and HeatLink INFO 37, Domestic Hot Water Recirculation Systems.

Dimension, in/(mm)										
Qty	Stk. #	Size	A	B	C	D	E	ID1	ID2	Weight, lb/(kg)
	EX27505NL	½ PEX × ½ MNPT	0.71 (18.0)	0.24 (6.0)	0.55 (14.0)	0.87 (22.0)	0.98 (25.0)	0.38 (9.7)	0.59 (15.0)	0.099 (0.045)
	EX27552NL	½ PEX × ¾ MNPT	0.71 (18.0)	0.26 (6.5)	0.59 (15.0)	1.08 (27.5)	1.22 (31.0)	0.38 (9.7)	0.79 (20.0)	0.123 (0.056)
	EX27522NL*	¾ PEX × ¾ MNPT	0.94 (24.0)	0.26 (6.5)	0.59 (15.0)	1.08 (27.5)	1.22 (31.0)	0.60 (15.2)	0.79 (20.0)	0.190 (0.086)
	EX27521NL	¾ PEX × 1 MNPT	0.94 (24.0)	0.26 (6.5)	0.67 (17.0)	1.36 (34.5)	1.50 (38.0)	0.60 (15.2)	0.98 (25.0)	0.209 (0.095)
	EX27582NL	1 PEX × ¾ MNPT	1.18 (30.0)	0.26 (6.5)	0.59 (15.0)	1.08 (27.5)	1.22 (31.0)	0.80 (20.3)	0.80 (20.3)	0.179 (0.081)
	EX27528NL*	1 PEX × 1 MNPT	1.18 (30.0)	0.26 (6.5)	0.67 (17.0)	1.36 (34.5)	1.50 (38.0)	0.80 (20.2)	0.98 (25.0)	0.335 (0.152)
	EX27535NL*	1¼ PEX × 1¼ MNPT	1.44 (36.5)	0.26 (6.5)	0.83 (21.0)	1.69 (43.0)	1.85 (47.0)	0.96 (24.4)	1.24 (31.5)	0.496 (0.225)
	EX27541NL*	1½ PEX × 1½ MNPT	1.69 (43.0)	0.24 (6.0)	1.02 (26.0)	2.01 (51.0)	2.20 (56.0)	1.09 (27.6)	1.50 (38.0)	0.655 (0.297)
	EX27554NL*	2 PEX × 2 MNPT	2.15 (54.5)	0.50 (12.7)	1.06 (26.8)	2.44 (62.0)	2.68 (68.0)	1.55 (39.4)	2.01 (51.0)	1.731 (0.785)



Technical Data

Specifications

Material	No Lead (Eco) Brass - C69300
Operating pressure rating	180°F @ 100 psi (82.2°C @ 0.69 MPa)

Listings

ICC-ES PMG 1087
cNSFus-pw
cQALus P371
U.P. Code
Codes
IMC
IPC
IRC
NPC of Canada
NSPC
UMC
UPC

Standards

ASTM E84
ASTM F877
ASTM F1960
CSA B137.5
NSF/ANSI 14
NSF/ANSI 61
NSF/ANSI 372
ULC S102.2
*ANSI/CAN/UL 1821

Installation

Installation must follow all of HeatLink's instructions and guidelines.

Related Documents

F1960 PEX-a Potable Water Expansion System Installation Guide (L3240)

SureLink Fire Safety Installation Guide (L3245)

HeatLink Limited Plumbing Warranty