

LINEAR LOW DENSITY POLYETHYLENE TUBE (363 Series)



Fairview 363 Series tubing is produced from an advanced grade of LLDPE. It offers superior environmental stress cracking resistance - greatly exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (IGEPAL) tests.

Environmental stresses that can shorten the service life of tubing include chemical exposure, aging, connections with barb-type fittings, or high vibration loads with connections to compression fittings.

Features:

- Compliant to ANSI/NSF-51, 61, WRAS and FDA requirements for food contact
- Dimensional stability
- Uniformity and long-term strength
- Higher burst pressure
- Greater tensile strength
- Wide range of available colors

PART No.	Color	Tube O.D. (IN.)	Tube I.D. (IN.)	Length (Ft.)	Working Pressure (P.S.I.)
363-4-25	Natural	1/4	0.170	25	230
363-4-500	Natural	1/4	0.170	500	230
363-4BLK-25	Black	1/4	0.170	25	230
363-4BLK-500	Black	1/4	0.170	500	230
363-4BLU-25	Blue	1/4	0.170	25	230
363-4BLU-500	Blue	1/4	0.170	500	230
363-4ORA-500	Orange	1/4	0.170	500	230
363-4RED-500	Red	1/4	0.170	500	230
363-4WHI-500	White	1/4	0.170	500	230
363-6-25	Natural	3/8	0.250	25	170
363-6-500	Natural	3/8	0.250	500	170
363-6BLK-500	Black	3/8	0.250	500	170
363-6BLU-25	Blue	3/8	0.250	25	170