No Lead Brass PEX F1960 × Copper Press Adapters

Job or Customer :	
Location :	
Engineer :	
☐ Complies with Spec ☐ Alternate	Notes :
Contractor :	
HeatLink Rep :	
Submitted By :	Date :
Approved By :	Date :
P.O. Number :	Date :

Description

Solid no lead brass PEX F1960 x copper press adapters for PEX-a potable water expansion systems.


The use of PEX tubing in a potable hot-water plumbing system with an operating temperature above 140°F (60°C) or system pressure above 80 psig (550 kPaG) or highly aggressive water quality or any combination thereof can significantly reduce the service life of the tubing.

HeatLink requires following the guidelines described in Plastics Pipe Institute TN-53, Guide to Chlorine Resistance Ratings of PEX Pipes and Tubing for Potable Water Applications and HeatLink INFO 37, Domestic Hot Water Recirculation Systems.

			Dimension, in/(mm)						
Qty	Stk. #	Size	A	B	C	D	ID1	ID2	Weight, lb/(kg)
	EX27P05NL	½" PEX × ½" Copper Press	1.73 (44.0)	0.79 (20.0)	0.76 (19.3)	0.96 (24.5)	0.38 (9.7)	0.63 (16.0)	0.090 (0.040)
	EX27P22NL	¾" PEX × ¾" Copper Press	2.09 (53.0)	0.91 (23.0)	1.02 (25.9)	1.25 (31.7)	0.60 (15.2)	0.88 (22.4)	0.160 (0.072)
	EX27P28NL	1" PEX × 1" Copper Press	2.33 (59.2)	0.91 (23.0)	1.27 (32.3)	1.51 (38.3)	0.80 (20.3)	1.14 (29.0)	0.240 (0.108)
	EX27P35NL	1¼" PEX × 1¼" Copper Press	2.72 (69.0)	1.02 (26.0)	1.55 (39.4)	1.75 (44.4)	0.96 (24.4)	1.39 (35.2)	0.390 (0.179)
	EX27P41NL	1½" PEX × 1½" Copper Press	3.27 (83.0)	1.31 (33.3)	1.81 (46.1)	2.12 (53.8)	1.09 (27.6)	1.64 (41.6)	0.570 (0.261)
	EX27P54NL	2" PEX × 2" Copper Press	4.00 (101.5)	1.57 (40.0)	2.32 (58.9)	2.60 (66.0)	1.37 (34.9)	2.14 (54.3)	1.050 (0.477)

Technical Data

	Specifications
Material	No Lead Brass - C46500
Operating pressure rating	180ºF @ 100 psi (82.2ºC @ 0.69 MPa)



Installation

Installation must follow all of HeatLink's instructions and guidelines.

Related Documents

F1960 PEX-a Potable Water Expansion System Installation Guide (L3240)

HeatLink Limited Plumbing Warranty

Listings	Standards
IAPMO cUPC	IAPMO/ANSI/CAN Z1117
Codes	ASTM F1960 compliant
UMC	NSF/ANSI 14
UPC	NSF/ANSI 61
NPCC	NSF/ANSI 372

All information is subject to change without notice.
Please check our website to ensure you have the latest version of this document.

©2024 HeatLink Group Inc.