

ApolloPress 90° elbow (P x P)



group: 807 **category:** fittings **product line:** Apollo ApolloPress

The ApolloPress® 807 Small Diameter Press 90° Elbow features a lead free dezincification resistant copper body and an EPDM o-ring. ApolloPress® products are manufactured utilizing proven ASTM materials and standards.

Lead Free Construction
Leak Before Press® Technology

applications

potable water, heating, cooling,
steam, compressed air, sprinkler,
vacuum

segments

fire protection , utility , industry

approvals

CRN , FM , IAPMO/ANSI/CAN Z1117
, ICC LC1002 , NSF , UL , ULc

assortment

item code	size	dimensions	weight	packaging	gtin + upc
10075554	1/2"	1.97x1.97x0.95 "	0.11 lb	-	00683264755543
10077676	1/2"	-	0.11 lb	-	00683264776760
10075556	3/4"	2.58x2.58x1.24 "	0.19 lb	-	00683264755567
10077678	3/4"	-	0.19 lb	-	00683264776784
10075052	1"	2.97x2.97x1.49 "	0.3 lb	-	00683264750524
10077680	1"	-	0.19 lb	-	00191988101589
10075078	1 1/4"	3.83x3.83x1.75 "	0.44 lb	-	00683264750784
10077658	1 1/4"	-	0.44 lb	-	00191988107741
10075080	1 1/2"	4.37x4.37x2.11 "	0.78 lb	-	00683264750807
10077660	1 1/2"	-	0.78 lb	-	00191988107789
10075082	2"	5.35x5.35x2.58 "	1.03 lb	-	00683264750821
10077662	2"	-	1.31 lb	-	00191988107826

specifications - characteristics

color	copper
materials	copper (CW024A (UNS C12200))
finishing	none
manufacturer	Aalberts integrated piping systems Americas, Inc. (Apollo)
shape	Elbow (90°)
connection type	press (V)
sealing	EPDM

specifications - general

product group	fittings (accessories (fittings))
ETIM class	EC003024 Fitting with 2 connections
brand	Apollo
series	ApolloPress
product type	807
unsps	40172812

dimensions

item code	size	d1	DN1	l1	z1	d2	DN2	l2	z2	radius	angle
10075554	1/2"	0.63	1/2" (DN15)	1.50	0.75	0.63	1/2" (DN15)	1.50	0.75	0.75	90
10077676	1/2"	0.63	1/2" (DN15)	1.50	0.72	0.63	1/2" (DN15)	1.50	0.72	0.75	90
10075556	3/4"	0.88	3/4" (DN20)	1.94	1.03	0.88	3/4" (DN20)	1.94	1.03	1.05	90
10077678	3/4"	0.88	3/4" (DN20)	1.92	1.01	0.88	3/4" (DN20)	1.92	1.01	1.05	90
10075052	1"	1.13	1" (DN25)	2.19	1.28	1.13	1" (DN25)	2.19	1.28	1.35	90
10077680	1"	1.13	1" (DN25)	2.24	1.32	1.13	1" (DN25)	2.24	1.32	1.35	90
10075078	1 1/4"	1.38	1 1/4" (DN32)	2.68	1.65	1.38	1 1/4" (DN32)	2.68	1.65	1.65	90
10077658	1 1/4"	1.38	1 1/4" (DN32)	2.67	1.69	1.38	1 1/4" (DN32)	2.67	1.69	1.65	90
10075080	1 1/2"	1.63	1 1/2" (DN40)	3.39	1.96	1.63	1 1/2" (DN40)	3.39	1.96	1.95	90
10077660	1 1/2"	1.63	1 1/2" (DN40)	3.43	2.03	1.63	1 1/2" (DN40)	3.43	2.03	1.95	90
10075082	2"	2.13	2" (DN50)	4.14	2.56	2.13	2" (DN50)	4.14	2.56	2.55	90
10077662	2"	2.13	2" (DN50)	4.09	2.48	2.13	2" (DN50)	4.09	2.48	2.55	90

