

ApolloPress coupling with stop PxP 1/2"



this article is part of a product group (800)
that contains a total of 6 items

[view all 6 items](#)

group: 800 **article:** 10077692 **category:** fittings

The ApolloPress® 800 Small Diameter Press Coupling features a lead free dezincification resistant copper body and an EPDM o-ring. ApolloPress® products are manufactured utilizing proven ASTM materials and standards.

Lead Free Construction

Leak Before Press® Technology

applications

potable water, heating, cooling,
steam, compressed air, sprinkler,
vacuum

segments

fire protection , utility , industry

approvals

CRN , FM , IAPMO/ANSI/CAN Z1117
, ICC LC1002 , NSF , UL , ULc

specifications - characteristics

color	copper
materials	copper (CW024A (UNS C12200))
finishing	none
shape	straight
connection type	press (V)
sealing	EPDM

specifications - general

product group	fittings (accessories (fittings))
ETIM class	EC003024 Fitting with 2 connections
brand	Apollo
series	ApolloPress
product type	800
unsp	40172612

specifications - product Info

article	ApolloPress coupling with stop PxP 1/2"
article number with gtin	10077692 (00683264776920)
product number with gtin	10077692 (00683264776920)
manufacturer	Aalberts integrated piping systems Americas, Inc. (Apollo)
item group	800 - ApolloPress coupling (P x P)
size	1/2"
weight	0.08 lb

specifications - technical

max operating pressure liquid	300 psi
min. medium temperature	32 °F
max medium temperature	250 °F

dimensions

d1	DN1	l1	z1	d2	DN2	l2	z2
0.63	1/2" (DN15)	0.84	0.06	0.63	1/2" (DN15)	0.84	0.06

