

Hisense

Hi-UNI Single Zone Universal

09K-12K-18K-24K-36K BTU

R410A

10 YEAR
PARTS*

LIMITED WARRANTY

2 YEAR
LABOR*

LIMITED WARRANTY

*: follow instruction on service manual
or from your distributors



Hisense USA Corporation

Specifications



Type	9K	12K	18K	24K	36K
Single zone Outdoors	•	•	•	•	•
Cassette	•	•	•	•	•
Duct	•	•	•	•	•
Split	•	•	•	•	•

Standard Features

- Universal outdoor unit to connect with multiple indoor types.
- SEER2 up to 20.5, HSPF2 up to 10.
- Low temperature heating (24K): -25°C (-13°F).
- Low temperature cooling: -15°C (5°F).
- 9K~24K Cassette & 9K Duct are all Energy-Star qualified.
- Long connection pipes: up to 164 ft length, 98ft height.
- Condenser base heater.
- Low noise--16 level DC motor for ODU.
- Hi-Checker service checker.
- Integrated water pump for Duct and Cassette.

Optional Features

- WiFi control.
- Remote control or wired control.



Address: 7310 McGinnis Ferry Rd
Suwanee, GA, 30024, USA
Support Number: 1-888-767-4011
Website: hisensecomfort.com

